Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

IND-CBE-UVC-36-18X6-R4-120V-25C

UV Disinfection Conveyor Oven - 120V, 60Hz - (8) 18" UVC Lamps, UV Shield - Single Speed/25' Cord - Designed for Cleaning Small Components

Product ID: 273124

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

This unit is Made In USA - Manufactured in Texas

IND-CBE-UVC-36-18X6-R4-120V-25C UV Sanitation Conveyor System

Lamp Technology: UV-C Fluorescent

Lamp Qty: (8) 18"

Overall Dimensions: 68.263"-L x 23.00"-W x 24.00"-H

Conveyor Length: 34"-L

Component Dimensions: Can Accommodate Components Down to 1cm x 1cm

Weight: -

Voltage: 120 V AC, 60Hz

Phase: 1-phase

Total Watts: 350W

Single-lamp Watts: 15W

Total UV Output: 42.4W

Single-lamp UV Output: 5.3W

Total UV Irradiance: 352 µW/cm² @ 1 Meter

Expected Lifespan: 8,000+ Hours

UV Wavelength: UV-C, 200nm - 280nm (254 nm)

Lamp Type: T8

Lamp Base: G13 (Medium Bi-pin)

Ratings/Features

UV Oven

Short-wave Germicidal Light

Kills 99% of Viruses and Other Germs

Made in USA - Manufactured in Texas

EPA Reg. No 98409-1

EPA Est. No. 98409-TX-1

Replacement Lamp: FRL-18-1X-T8-15W-UV-C
Beam Angle: 360º
Light Configuration: Flood
Sanitation Duration: 60 Seconds
Conveyor Belt Speed: Single
Activation: On/Off Switch for Lamps and Motor
Safety: Adjustable UV Shields
Amps: 2.91 A @ 120 V
Ambient Operating Temp Range: -
Materials: 304 Stainless Steel
Lens Material: -
Mounting: Rubber Feet
Wiring: 25' Cord w/ Cord Cap
Cord Cap Options: 5-15 Straight, L5-15 Twist, or Pigtail

PLEASE NOTE: UV-C light can cause temporary or permanent loss of vision, and temporary acute redness or ulceration (mild to severe sunburn) to exposed skin. To prevent exposure, do not operate the device in any application that allows UV-C light to be visible during operation. NEVER LOOK DIRECTLY AT THE BULB OR DISINFECTING TARGET ZONE. DO NOT touch bulb with bare hands. The oils in your skin will damage the lamp. Fingerprints will result in reduced performance and significantly reduce the lifespan of the lamp unless they are removed with alcohol. Please read instruction manual for UV safety requirements before operating.

Special Orders - Special Requirements
Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

This unit is Made In USA - Manufactured in Texas

The IND-CBE-UVC-36-18X6-R4-120V-25C from Larson Electronics is a UV Disinfection Conveyor Oven that sanitizes components that measure as small as 1cm by 1cm. The specially designed conveyor belt features a small hole chain design that can accommodate small components down to 1cm by 1cm in size while still allowing the UV light to pass through and clean both sides of the components. Equipped with eight UV lamps, the unit offers UV-C output at a range of 200nm - 280nm (254nm). This system sanitizes components in 60 seconds. Protected by a 304 stainless steel housing, the UV oven operates on single-phase 120 V and comes with a 25` cord.

Please note: This product produces UV light. Make sure to follow all safety guidelines and protocols found in the user manual. UVC light in the proper setting kills up to 99.9% of viruses, mold, spores, and bacteria. Click here to learn more about UVC and the coronavirus*

The IND-CBE-UVC-36-18X6-R4-120V-25C is a powerful sanitation solution for handling components that measure as small as 1cm by 1cm in size. Equipped with eight UVC fluorescent lamps, this system offers UV output within the 200nm - 280nm UV-C range (254 nm). The lights have an expected lifespan of 8,000+ hours and emit a flood beam pattern with 360 degrees of coverage. Inside the UV oven, the lamps take on the following configuration: (4) 18" UV bulbs on the top and (4) 18" UV bulbs on the bottom. Models with side lamps are available (at an additional cost) for cleaning large packages.

Adjustable UV shields located at both ends are available for UV protection. The components are designed to reduce stray UV light during treatment. We offer bolt-on plastic strip door curtains for variable height processing at an additional cost. The single-speed system is protected by a 304 stainless steel housing.

Operation: Start the UV sanitation system by pressing the on/off button for the lamps and motors. Next, load "dirty" components in size into the entrance of the unit (the UV oven accepts components as small as 1cm by 1cm in size - we offer longer and wider units with larger size capacities at an additional cost). The "dirty" components are cleaned by the UV lamps, which take 60 seconds to complete. Sanitized components exit through an opening after UV treatment. To ease processing, we offer different types of end caps for catching into a collection box and an optional automatic grabber from a hopper (not included) at additional costs. We can also integrate this UV disinfection unit with existing processing equipment at an additional cost.

Voltage: The IND-CBE-UVC-36-18X6-R4-120V-25C operates on single-phase 120

V AC, 60Hz. We offer this unit in other voltages at an additional cost. Single-phase voltage options include: 120V, 208V, 277V or 347V. For three-phase voltages, we offer 208V, 220V, 240V, 480V or 600V.

Click Photos to Enlarge



5-15 Straight Blade Plug
15 Amp / 125V Rated



L5-15 Twist Lock Plug
15 Amp / 125V Rated



Flying Leads / Pigtail Wires

Wiring/Plug: This unit is equipped with 25 feet of 16/3 chemical and abrasion resistant SOOW cord that is fitted with an industrial grade cord cap for easy connection to common wall outlets. Plug options include standard 5-15 15 amp straight blade plug for 110V wall outlets with ground or NEMA L5-15 15 amp twist lock plug for 125V twist lock outlets. Alternatively, we can provide flying leads with no plug for hard wire applications or for operators who prefer to wire in user provided cord caps. Please choose pigtail option below for flying leads with no plug.
Mount: This UV sanitation system is a stand alone unit that can be deployed in work sites. Rubber feet at the bottom ensures stability and prevents scratching surfaces during use.
Note on Environment: Sunlight and visible light fixtures do not impact the effectiveness of the disinfecting on this UVC sanitation product. Metal halide, high pressure sodium, fluorescent, and LED light fixtures can be left on. The UV radiation emitted from this product is not disrupted by any type of lighting in the environment. Put simply, NO it DOES NOT need to be dark in the area you plan to disinfect. The UV radiation is harmful to the eyes and skin, and that is why you should not be in the area while it is in operation. Please see user manual for additional safety information.
Suggested Applications: Sanitation, disinfection, warehouses, mail, package processing, ballots, letters, envelopes and more; kills 99% of viruses, bacteria, mold, and spores.
At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)






DANGER

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

IND-CBE-UVC-36-18X6-R4-120V-25C

Product ID: 273124

Export Control Classification Number (ECCN): EAR99

Options:

IND-CBE-UVC-36-18X6-R4-120V-25C-Cord Cap

Example: IND-CBE-UVC-36-18X6-R4-120V-25C-5.15

Cord Cap	
5-15 STRAIGHT	-5.15
L5-15 TWIST	-L5.15
PIGTAIL	-Pigtail

Links (Click on the below items to view):

- **Dimensional Drawing 2D**
- **Eye Safety Information/Certificate**
- **HigResPic1**
- **HigResPic2**
- **HigResPic3**
- **HigResPic4**
- **HigResPic5**
- **HigResPic6**
- **HigResPic7**
- **HigResPic8**
- **HigResPic9**
- **Video1**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**