

IND-CS-RLY.TMD-CL.6S-OP.6S-6X-120V-30A-SPST-2XC

Programmed Relay Timer - Weatherproof - Corrosion Resistant Plastic Moulding - NEMA 6P

Product ID: 273648

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

IND-CS-RLY.TMD-CL.6S-OP.6S-6X-120V-30A-SPST-2XC Weatherproof Programmed Relay Timer

Unit Type: Programmed Relay Timer

Internal Dimensions: 8"-H x 8"-W x 4"-D

Weight: 2 lbs

Closed Circuit Duration: 6 Seconds

Open Circuit Duration: 6 Seconds

Cycles: 6

Contacts: (2) N/O, (2) N/C

Materials: Plastic Moulding Compound

Mounting: Surface Mount

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Features/Ratings

Weatherproof

Highly Corrosion Resistant

NEMA 6P & 4/4

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

Made in the USA

The IND-CS-RLY.TMD-CL.6S-OP.6S-6X-120V-30A-SPST-2XC from Larson Electronics is a Programmed Relay Timer for industrial sites. The weatherproof device provides timing functions in circuits. This NEMA 6P and corrosion resistant unit is constructed from a plastic moulding compound that will not rust or corrode along with a foam gasketed lid sealed with stainless steel screws.

The IND-CS-RLY.TMD-CL.6S-OP.6S-6X-120V-30A-SPST-2XC is a programmed

relay timer for reliable switching or controlling functions. When triggered, this weatherproof unit closes the circuit and activates connected equipment located downstream. During operation, the device holds the circuit closed for 6 seconds and opens the circuit for two seconds. The cycle is repeated six times in a row. Ideal for both indoor and outdoor use, the IND-CS-RLY.TMD-CL.6S-OP.6S-6X-120V-30A-SPST-2XC offers superior corrosion resistance and ample protection for direct burial applications.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Frequently Asked Questions (FAQ)











IND-CS-RLY.TMD-CL.6S-OP.6S-6X-120V-30A-SPST-2XC

Product ID: 273648

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [HigResPic7](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)