Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

LM-10-5-3S-FM-EW-CSB-208V

10' Light Mast w/ Electric Winch - 5' to 10' - 208V - Fixed Mount, Base Plate - Cable Guides

Product ID: 273855

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

LM-10-5-3S-FM-EW-CSB-208V Fixed-Mount Light Tower

Length: 5 feet - 10 feet
Weight: +-400 lb
Capacity: -
Materials: Steel
Finish: Powder Coated (Gloss Blue) or Hot Dip Galvanized
Operation: (1) 1,000 lb Electric Winch, Manual Optional
Cable: 3/16" Aircraft Cable
Cable (Wire) Management: External Wire Channels Mounted to Each Stage
Winch Voltage: 208 V
Mounting: 13" x 15" x 1/4" Thick Standard Base Plate w/ (6) Mounting Holes
Anchor Bolts: (6) 9/16" Anchor Bolts (Not Included)
Shipping: Common Freight
Shipping Dimensions: 16.5'-L x 4'-W x 5'-H
Shipping Weight: +-1075 lb
Options: Length - Mounting - Fixtures / Call Us for Special Requirements

Summary

5 to 10 Foot Light Mast
Steel Construction
Powder Coated or Galvanized Finish
Removable Mast Head
125 mph Wind Resistance
Manual or Optional Electric Operation

Special Orders - Special Requirements

Contact us for special requirements


Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

The LM-10-5-3S-FM-EW-CSB-208V from Larson Electronics is a 3-Stage Light Mast with Electric Winch that provides a safe and effective way for operators to quickly deploy lights, security cameras, and other equipment to elevations of up to 10 feet. This light tower features a rotating boom that allows for 360°

of rotation, one electric winch that operates on 208 V and a removable mast head for storing mounted equipment when not in use. The LM-10-5-3S-FM-EW-CSB-208V is equipped with a cable support eyelet on every stage.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO LIGHT MASTS, LIGHT TOWERS, OR TRIPODS

This telescoping three stage steel light mast from Larson Electronics is designed to allow operators to quickly and safely deploy lighting, cameras, and other electrical equipment in locations where this equipment must be elevated to heights up to 10` for effective coverage. This light boom can be extended to 10` for maximum area coverage and collapsed to 5` for applications where a smaller footprint is required. The tower is constructed of square steel tubing with a lower section 3.86` in length and 4" by 4" by 1/8" thick, middle section 4.15` in length and 3" by 3" by 1/8" thick, and an upper section 4.56` in length and 2 1/2" by 2 1/2" by 1/8" thick. Each section has a 1 foot overlap. The mast is elevated using one 1,000 lb electric winch with 3/16" cable. The electric winch operates on 208 V.



Locking Pin



Towers Rotated



Control Panel



Raised



Back

The LM series towers are available in two finish options: powder coated with glossy blue finish for corrosion resistance and aesthetics, or hot dip galvanized for superior corrosion resistance. This light mast can be mounted to trailers or other stable surfaces via a 13" x 15" x 1/4" thick mounting base plate which has been drilled to accept six 9/16" anchor bolts (anchor bolts not included). A 44" wide and 2" by 2" by 1/4" thick mounting plate is attached to the upper section of the mast which provides a strong and stable platform for mounting fixtures and equipment.

The LM family of telescoping towers feature a proprietary mast guidance system, which provides increased stability during high winds. When lowered to 5 feet, the mast can withstand winds up to 125 mph. When elevated to its full upright position, the mast can be rotated a full 360°. By loosening the T-Handle, operators can rotate the mast with ease in either direction. The mast can be positioned in one of four different directions, and locked back in place by re-tightening the T-handle. The mast itself spins freely, and can typically be rotated with a single hand.



Mast Hand Control


This light tower weighs approximately 400 lb and can easily support and lift customer-provided fixtures. The entire tower assembly is shipped via common freight carrier and when shipped measures approximately 16.5` long, 4` wide, 5` tall and weighs approximately 1075 lb. Larson Electronics can custom tailor these units to the customer`s requirements with longer sections and larger mounting plates. We also offer a choice of either the electric 1,000 lb hand winch or optional manual winches.
Suggested Applications: Temporary lighting, construction sites, and security camera deployment. We can equip this mast with 1000W or 1500W Metal Halide lights or a wide variety of high powered LED lights with comparable power, including the LED10WSA-160, LEDLB-200X2E, LEDLB-160X2E or LEDLB-80x2E.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364





Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

LM-10-5-3S-FM-EW-CSB-208V

Product ID: 273855

Export Control Classification Number (ECCN): EAR99

Options:

LM-10-5-3S-FM-EW-CSB-208V-Finish

Example: LM-10-5-3S-FM-EW-CSB-208V-PWDC

Finish	
POWDER COAT	-PWDC
GALVANIZED	-GLVD

Links (Click on the below items to view):

- **Operations Manual**
- **Wiring Diagram (Oneline)**
- **HigResPic1**
- **HigResPic2**
- **HigResPic3**
- **HigResPic4**
- **HigResPic5**
- **HigResPic6**
- **HigResPic7**
- **HigResPic8**
- **HigResPic9**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**