Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

**MT-ISX-SS-FP-3P-415Y-225KVA-480D.240-N4X-CU-M1**

# 225 kVA Encapsulated Distribution Transformer - 415V Wye Primary - 480V/240 Delta Secondary - NEMA 4X - Stainless Steel Enclosure - 50/60Hz - Copper Windings

**Product ID: 274159**

**Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).**



**Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.**

**MT-ISX-SS-FP-3P-415Y-225KVA-480D.240-N4X-CU-M1 Encapsulated Distribution Transformer**

**Transformer Type:** Distribution
**Phase:** Three Phase
**Frequency:** 50/60 Hz
**Vector Group:** -
**kVA:** 225
**Primary Voltage:** 415 V Wye
**Taps:** 2 x 2.5% FCAN; 2 x 2.5% FCBN
**Secondary Voltage:** 480V/240 Delta
**Winding Material:** Copper
**Efficiency:** -
**Insulation:** 220°C
**Temperature Rise:** 150°C
**Impedance:** -
**Seismic:** Yes
**Sound Level:** Meets NEMA ST-20 Standards
**Knockouts:** Yes
**Primary Termination:** Lugs large enough to fit one 95 mm2 (#3/0) stranded copper wire
**Secondary Termination:** Double lugs for each phase and neutral; Sufficient for 95 mm2 (#3/0) stranded copper
**Enclosure Material:** NEMA Type 4X Heavy Duty Encapsulated - 304 Stainless Steel
**Finish:** Natural Finish
**Dimensions:** -

**Ratings**

NRTL Listed for United States and Canada
ANN Cooling
IP66 Rated
NRTL Certified to UL 1562
Meets or Exceeds U.S. DOE 10 CFR Part 431
NRTL Certified to C22.2 No. 47

**Special Orders - Special Requirements**

Contact us for special requirements
**Toll Free:** 1-800-369-6671
**Intl:** 1-903-270-1187

**Weight:** -

**Mounting:** Floor Mount

**Fax:** 1-903-498-3364

**E-mail:** sales@larsonelectronics.com

**The MT-ISX-SS-FP-3P-415Y-225KVA-480D.240-N4X-CU-M1 415 V Wye 3 Phase 50/60 Hz Energy Efficient Encapsulated Transformer from Larson Electronics is powerful, reliable and designed with the environment in mind. Suitable for indoor or outdoor applications, the MT-ISX-SS-FP-3P-415Y-225KVA-480D.240-N4X-CU-M1 provides increased reliability and protection against critical equipment failures. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.**

***PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS***

**Transformer Features:** With a transformer rating of 225 kVA, the MT-ISX-SS-FP-3P-415Y-225KVA-480D.240-N4X-CU-M1 distribution transformer is a three phase unit with a primary voltage of 415 V Wye. It also provides a secondary voltage of 480V/240 V Delta. Featuring robust construction, this unit`s cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This 50/60 Hz unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The Standard NEMA Type 4X stainless steel enclosure makes the unit suitable for indoor or outdoor applications and it can be floor mounted. The unit also features 220°C insulation with a 150°C temperature rise and is rated IP66.

**Benefits:** The MT-ISX-SS-FP-3P-415Y-225KVA-480D.240-N4X-CU-M1 encapsulated distribution transformer offers many benefits to the consumer. Precision cut copper transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations. This 50/60 Hz encapsulated distribution transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated mounting brackets make installation fast and easy and the offset outward facing installation holes allow for easy power tool access.

**Safety:** The MT-ISX-SS-FP-3P-415Y-225KVA-480D.240-N4X-CU-M1 is a distribution transformer which means that it provides operators with an increased level of protection against electric shock. A distribution transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-ISX-SS-FP-3P-415Y-225KVA-480D.240-N4X-CU-M1 achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

**Applications:** General purposes.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

# Frequently Asked Questions (FAQ)

**MT-ISX-SS-FP-3P-415Y-225KVA-480D.240-N4X-CU-M1**

**Product ID: 274159**

**Harmonized System (HS) Code:** 85043300

**Export Control Classification Number (ECCN):** EAR99

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Links (Click on the below items to view):

- **HigResPic1**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**