Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

RNT-LM-12-FM-400LB-TLR8

RENT 3 Stage Light Mast on 8' Single Axle Trailer w/ Wheels - Extends up to 12' - 400 lb Capacity

Product ID: 276385

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

RNT-LM-12-FM-400LB-TLR8 Trailer Mounted 3-Stage Light Tower

Light Mast Specs

Tower Length: 6.5` (6.69` Above Trailer Deck with Mast Head Removed) to 12`
Mast Head Length: 44"
Capacity: 400 lbs
Materials: Steel
Finish: Powder Coated - Gloss Blue
Operation: (2) 1,000lbs Hand Winches, Electric Optional
Cable:3/16" Galvanized Aircraft Cable

Trailer Specs

Materials: Steel
Trailer Bed Dimensions: 8-L` x 6.5`-W trailer bed
Trailer Footprint (Towing): 12`L x 8.1`W trailer bed
Trailer Footprint (Deployed): 12`L x 11.25`W trailer bed
Hitch: 2" Ball Coupler
Wiring: 4-Pin Flat
Axle: 3,500lb
Suspension: 5,400 Lb 4-Leaf Double Eye Springs
Outriggers: (4) 1,000 Manual Crack Leveling Jacks - Retractable
Wheels: (2) 15" 5x4.5 Steel Rims
Tires: ST205/75/D15 H188

Quick Summary

6.5` to 12` Light Mast
Steel Construction
Powder Coated Finish
Removable Mast Head
(4) 1,000lb Retractable Outriggers
125 mph Wind Resistance
Manual or Optional Electric Operation

Special Orders - Special Requirements

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Weight: +-1200 lbs

Shipping: Common Freight

Shipping Dimensions:~16.5`-L x 4`-W x 5`-H

Shipping Weight: +-1700 lbs

Options: Length- Mounting-Fixtures/ Call Us for Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

This unit is for rentals

This unit is Made In USA - Manufactured in Texas

The Larson Electronics RNT-LM-12-FM-400LB-TLR8 trailer mounted 3-stage light mast provides a safe and effective way for operators to quickly deploy lights, security cameras and other equipment to elevations up to thirty feet. This light tower folds over for easy transportation, features a rotating boom that allows for 360° of rotation, and a removable mast head for storing mounted equipment when not in use. The entire assembly is mounted onto a 8` single axle trailer, allowing operators to transport this fold over boom from location to location.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO LIGHT MASTS OR LIGHT TOWERS

This telescoping three stage steel light mast from Larson Electronics is designed to allow operators to quickly and safely deploy lighting, cameras, and other electrical equipment in locations where this equipment must be elevated to heights up to 12` for effective coverage. This light boom can be extended to 12` for maximum area coverage and collapsed to 6.5` for applications where a smaller footprint is required. The tower is constructed of square steel tubing with a lower section 5.3` in length and 4" by 4" by 1/8" thick, middle section 5.4` in length and 3" by 3" by 1/8" thick, and an upper section 5.9` and 2" by 2" by 1/8" thick. Each section has a 2` minimum overlap. The mast is elevated by pressing down on the end of base stage, elevating the mast into the upright position. The mast is extended to its full height using an included 1,000 lbs hand winch with 3/16" galvanized cable. The mast collapses to 6.69` above trailer deck height when the mast head is removed.



44" Mast Head for mounting lights and equipment

Click Image to Enlarge



Click Image to Enlarge



13" by 15" by 1/4" thick mounting base

Click Image to Enlarge



Click Image to Enlarge



Click Image to Enlarge



Click Image to Enlarge

A 44" wide and 2" by 2" by 1/4" thick mounting plate is attached to the upper section of the mast which provides a strong and stable platform for standard payloads up to 150 lbs. When elevated to its full upright position, the mast can be rotated a full 360°. By loosening the T-Handle, operators can rotate the mast with easy in either direction. The mast can be positioned in one of four different positions, and locked back in place by re-tightening the T-handle. The mast itself

spins freely with easy, and can typically be rotated with a single hand.
The LM series of towers are powder coated with glossy blue finish for corrosion resistances and aesthetics. This light mast is mounted to a 8` by 8.5`, single axle trailer via six 1/2" anchor bolts. The two wheel trailer is equipped with 3,500 lbs axle and leaf springs with 15" trailer tires. The trailer can support and haul an additional 3,500 lbs of equipment. A standard 2" ball coupling, two standard safety chains, and 4-pin flat trailer plug allow for easy hookup and towing.
The LM family of telescoping towers feature a proprietary mast guidance system, which provide increased stability during high winds. Four 1,000 lbs hand crank leveling jacks are used for leveling. The jacks can be leveled by hand crank or attachment provided for power drills. These outriggers can be extended 2` out from the side of the trailer for added stability. When lowered to 6.5`, the mast can withstand winds up to 125 mph. Custom builds can be provided for higher wind speed resistance when fully raised.



Retractable outriggers with 1,000 lb manual crank jacks and tail lights.

Click Image to Enlarge



Manual 1,000 lb hand crank winch for elevating and folding over the light mast on the LM-30-3S-TLR.
Click Image to Enlarge



Mast support bracket for securing the mast boom in the fold-over position during transportation.
Click Image to Enlarge



The LM-30-3S-TLR fitted with four HID-22-SL-REM 1000 Watt Metal Halide Light Fixtures

Click Image to Enlarge



Ready to Ship

Click Image to Enlarge



Click Image to Enlarge

This light tower assembly weighs approximately 1200 lbs, can easily support and lift 400 lbs fixtures. The entire tower assembly is shipped via common freight carrier or flatbed. Larson Electronics can custom tailor these units to the customer`s requirements with longer sections and larger mounting plates. For example, the LM-40-4S is another model that reaches to a length of 40`, with base section 11.25` in length, lower section 11.25` in length, an upper section 11.25` in length, and a top section 11.75` in length. Larson Electronics can custom build these towers to meet your overall and collapsed height requirements.
We also offer a choice of either the manual or electric winches, finishing, and equipped light heads. Winch options include 1,000 lbs hand winches (included standard) or optional electric winches for standard light towers, and heavy duty winches and hoists for high payload units. Powder coating color can be customized (the standard mast is gloss blue). Mast location on the trailer bed can be tongue

mounted, front of the trailer bed, or center of the trailer bed. These towers can be fitted with Larson Electronics line of high output light heads, or customize the mast head to meet the mounting requirements for your equipment.



Click Image to Enlarge



Click Image to Enlarge



Click Image to Enlarge



Click Image to Enlarge

Click Image to Enlarge

Click Image to Enlarge

Suggested Applications: Temporary lighting, construction sites, and security camera deployment. We can equip this mast with 1000W HID-22-SL-REM or 1500W HID-22-15M-SL-REM Metal Halide lights or a wide variety of high powered LED lights with comparable power, including the LED10WSA-160, LED10WSA-320, LEDP5W-30, LEDP5W-60, and GAU-HB-160LED.
At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364





Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

RNT-LM-12-FM-400LB-TLR8

Product ID: 276385

Export Control Classification Number (ECCN): EAR99

Options:

RNT-LM-12-FM-400LB-TLR8-Rental Length

Example: RNT-LM-12-FM-400LB-TLR8-MR

Rental Length	
MONTHLY	-MR
WEEKLY	-WR
DAILY	-DR

Links (Click on the below items to view):

- HigResPic1
- HigResPic2
- HigResPic3
- HigResPic4
- HigResPic5
- HigResPic6
- HigResPic7
- HigResPic8
- HigResPic9
- HigResPic10
- ISO 9001 Certification
- Business Certificate
- Shipping Time Map