

EPL-MJ-15W-LED-C-R-1227-CM

15W Explosion Proof Colored LED Indicator Light, C1D1, 120-277V, 2,250 lms, Ceiling Mount, Mason Jar / Jelly Jar, Red Housing

Product ID: 277244

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: EPL-MJ-15W-LED-C-R-1227-CM

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPL-MJ-15W-LED-C-R-1227-CM - Explosion Proof LED Indicator Warning Light

Listing: NRTL Listed to United States, Canada

Lamp Technology: LED

Dimensions: 6.22"-OD x 13.5"-H

Weight: 10 lb

Voltage: 120-277V AC, 50/60Hz

Total Watts: 15W

Total Lumens: 2,250 lms

Luminous Efficacy: 150 Lm/w

Lamp Life: 75,000+ Hours

LED Color: Red, Green, Blue, Amber, Purple, White 5000K, White 4500K, White 4000K, White 3500K or White 3000K

Color Rendering Index: >80 CRI

Lamp Type: Integrated LED

Lamp Base: N/A

Replacement Lamp: -

Beam Angle: 360°

Lighting Configuration: Flood Pattern

NEMA Type (Lighting): 7H x 7V

IES Classification: Type VS

Ratings/Approvals

Class I, Division 1, Groups C and D

Class I, Division 2, Groups A, B, C, D

Class II, Divisions 1 & 2, Groups E, F and G

Class III, Divisions 1 & 2

NRTL Certified to UL 844 Ed. 13

NRTL Certified to UL 1598

NRTL Certified to C22.2 No. 137 Rev 2009

NRTL Certified to C22.2 No. 250.0

NRTL Certified to C22.2 No. 30-M-1986 Rev 2012

IEC 60529 Tested

IP67 Rated Waterproof

LEL Approved

Replacement for Metal Halide, HPS, Mercury Vapor, Halogen, CFL and Incandescent Lamps

Pyramid Light Distribution

Field Serviceable

Warning System Indicator Light

Longitudinal Classification: Very Short

Cutoff Classification: Non-Cutoff

CIE Type: Semi-Direct

BUG Rating: B1-U4-G2

Power Efficiency: >95%

Power Factor: 0.959

Amps: 0.125 A @ 120 V, 0.073 A @ 208 V, 0.068 A @ 220 V, 0.063 A @ 240 V, 0.055 A @ 277 V

Ambient Operating Temp Range: -50°C to +65°C

Operating Temp Rating: T5

Housing Material: Copper Free Cast Aluminum (Non-Sparking)

Housing Finish: Epoxy Powder Coated - Red

Lens Material: Hardened Borosilicate Glass

Gasket Material: Silicone

Mounting: Ceiling Mount - Other Mounts Available

Wiring: Internal Wiring Junction Box

Wiring Hub: (1) 3/4" NPT

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-765-7664

E-mail: sales@larsonelectronics.com

The EPL-MJ-15W-LED-C-R-1227-CM from Larson Electronics is an Explosion Proof LED Indicator Light that provides operators with a powerful alternative to traditional hazardous location luminaries, including metal halide, high pressure sodium, mercury vapor, halogen, CFL and incandescent lamps. This 15-watt, steady burn LED unit offers 2,250 lumens, carries an IP67 waterproof rating, features a red colored housing, and is available in a variety of lamp colors. Compatible with ceiling mounting installations, the mason jar style fixture is field serviceable and features pyramid light distribution that closely resembles traditional bulbs. The EPL-MJ-15W-LED-C-R-1227-CM are designed for use in warning systems and can be used with emergency battery backups.

The EPL-MJ-15W-LED-C-R-1227-CM is a Class I, Division 1 & 2 and Class II, Division 1 & 2 explosion proof light fixture that is designed for energy efficient and superior illumination in combustible environments. This 15-watt mason jar style fixture offers 2,250 lumens of high quality light. Color options for the LED light includes: red, green, blue, amber, purple, white 5000K, white 4500K, white 4000K, white 3500K or white 3000K. This compact fixture is a suitable replacement for metal halide, high pressure sodium, mercury vapor, halogen, CFL and incandescent lights. The LED unit features a pyramid configuration to ensure complete light distribution that closely represents light output of traditional bulbs (unlike other LED lights that utilize a flat board causing light to be pushed directly downwards). This solution promotes vertical lighting and reduces the limitations associated with directional lighting. We can add a metal reflector at an additional cost.

This lighting solution for explosive sites is IP67 rated, dust-proof and protected against high pressure jets and temporary submersion. The non-sparking housing is red in color and is specially designed to dissipate heat which increases the efficiency and lifespan of the LEDs and electronic components.

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.

LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

LED Drivers: Even in LED fixtures, heat is the single largest factor in premature light failure and color shifting. As a result, many manufacturers reduce the output of their LEDs in order to reduce the amount of heat produced. Rather than lower light output or quality, Larson Electronics addresses this problem with the addition of an electronic LED driver. This internal driver provides the ability to automatically monitor and adjust input current to maintain the correct LED voltage levels regardless of input levels across a specific range. This not only reduces the energy dissipation, effectively lowering the operating temperature of the fixture, but also prevents AC over-voltage and short circuit loading making this fixture virtually maintenance free. Because the electronic driver allows the EPL-MJ-15W-LED-C-R-1227-CM to run at a cooler internal temperature and regulates the electrical current, energy efficiency and LED service hours are maximized while at the same time reducing operating costs and downtime incurred from the frequent servicing intervals required with other hotter running lights.

Field Serviceability: This explosion proof LED light fixture is field serviceable. All major internal components can be purchased from Larson Electronics and installed by a licensed electrician with basic tools. With most explosion proof fixtures, the fixture must be returned to the manufacturer for repair work, which presents downtime and long turn around times for repair work. Larson Electronics addresses this issue with the EPL-MJ series with field serviceability, allowing operators to perform service work without having to return the fixture to the manufacturer in the event of damage or failure.

Function: The EPL-MJ-15W-LED-C-R-1227-CM is an indicator light intended for use with warning systems as opposed to standard illumination applications. In other words, when this light comes on in the field, it means that something is wrong or needs attention. This unit's red housing helps it to stand out as a warning light amongst other standard illumination fixtures. This indicator light is compatible with emergency battery backup systems (not included).

Voltage: The light is universal voltage capable and can be operated with 120-277 V AC, 50/60 Hz.

Mount: This explosion proof mason jar style LED light fixture comes standard with ceiling mounting features, which cater to installations that hang from the ceiling. Several mounting options including wall, ceiling, angled wall, angled stanchion, and top hat/pan adapter mounts for replacing existing light fixtures can be ordered separately.

Suggested Applications: Hazardous locations, aircraft maintenance, oil drilling rigs, refineries, solvent and cleaning areas, chemical manufacturing, waste treatment plants, gas processing plants and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide



replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.



Frequently Asked Questions (FAQ)

There are no Fags



Image: EPL-MJ-15W-LED-C-R-1227-CM



Image: EPL-MJ-15W-LED-C-R-1227-CM



Image: EPL-MJ-15W-LED-C-R-1227-CM



Image: EPL-MJ-15W-LED-C-R-1227-CM

EPL-MJ-15W-LED-C-R-1227-CM

Product ID: 277244

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

EPL-MJ-15W-LED-C-R-1227-CM-Color

Example: EPL-MJ-15W-LED-C-R-1227-CM-RED

Color	
RED	-RED
GREEN	-GRN
BLUE	-BLU
AMBER	-AMB
PURPLE	-PRPL
WHITE 5000K	-50K
WHITE 4500K	-45K
WHITE 4000K	-40K
WHITE 3500K	-35K
WHITE 3000K	-30K

Links (Click on the below items to view):

- **Canadian CEC Certificate (Commonly referred to as CSA Certificate)**(<https://www.larsonelectronics.com/images/product/CECCert/277244.PDF>)
- **Catalog Page - Product Series**(<https://www.larsonelectronics.com/images/product/CatalogPage/277244.PDF>)
- **CE Certificate**(<https://www.larsonelectronics.com/images/product/CECert/277244.PDF>)
- **IES (Photometric File)**(<https://www.larsonelectronics.com/images/product/ies/277244.ZIP>)
- **LM80**(<https://www.larsonelectronics.com/images/product/LM80/277244.PDF>)
- **MSDS (Material Safety Data Sheet)**(<https://www.larsonelectronics.com/images/product/Msds/277244.PDF>)
- **Operations Manual**(<https://www.larsonelectronics.com/images/product/Manual/277244.PDF>)
- **Photometric DarkSky Report**(<https://www.larsonelectronics.com/images/product/DarkSkyReport/277244.PDF>)
- **Photometric Flood Report**(<https://www.larsonelectronics.com/images/product/FloodReport/277244.PDF>)
- **Photometric Indoor Report**(<https://www.larsonelectronics.com/images/product/IndoorReport/277244.PDF>)
- **Photometric Polar Graph**(<https://www.larsonelectronics.com/images/product/PolarGraph/277244.PDF>)
- **Photometric Road Report**(<https://www.larsonelectronics.com/images/product/RoadReport/277244.PDF>)
- **RoHS Certificate (Restriction of Hazardous Substances)**(<https://www.larsonelectronics.com/images/product/RoHSCert/277244.PDF>)
- **Spectrum Curve (Wavelength Graph)**(<https://www.larsonelectronics.com/images/product/SpectrumChart/277244.PDF>)
- **STEP File (3D CAD Model)**(<https://www.larsonelectronics.com/images/product/Step/277244.ZIP>)
- **TM21**(<https://www.larsonelectronics.com/images/product/TM21/277244.PDF>)
- **USA NEC Certificate (Commonly referred to as UL Certificate)**(<https://www.larsonelectronics.com/images/product/NECCert/277244.PDF>)
- **Wiring Diagram**(<https://www.larsonelectronics.com/images/product/WiringDiagram/277244.PDF>)
- **HigResPic1**(<https://www.larsonelectronics.com/images/product/HigResPic1/277244.JPG>)
- **HigResPic2**(<https://www.larsonelectronics.com/images/product/HigResPic2/277244.JPG>)
- **HigResPic3**(<https://www.larsonelectronics.com/images/product/HigResPic3/277244.JPG>)
- **HigResPic4**(<https://www.larsonelectronics.com/images/product/HigResPic4/277244.JPG>)
- **HigResPic5**(<https://www.larsonelectronics.com/images/product/HigResPic5/277244.JPG>)
- **Video1**(<https://www.youtube.com/watch?v=s4-63tz-Kco>)
- **ISO 9001 Certification**(<http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF>)
- **Business Certificate**(<https://www.larsonelectronics.com/images/pdfdocs/w9.PDF>)
- **Shipping Time Map**(<https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf>)