

HAL-LC-24-LED-R2-1227-APM

75W Hazardous Location Integrated LED Linear Fixture - C1D2, C2D1 - 120-277V - 11,550

Im/pipe Mount Brackets - IP66/Field Serviceable

Product ID: 277407

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

HAL-LC-24-LED-R2-1227-APM - Hazardous Location LED Fixture

Listing: NRTL Listed to United States, Canada

Lamp Technology: LED

Dimensions: 23.7"-L x 6.26-W x 6"-H

Weight: 30 lbs

Voltage: 120-277V AC, 50/60Hz

Total Watts: 75W

Total Lumens: 11,550 lms

Luminous Efficacy: 153 Lm/w

Lamp Life: 75,000+ Hours

LED Color Temperature: 5000K, 4500K, 4000K, 3500K or 3000K

Color Rendering Index: >80 CRI

Lamp Type: Integrated LED

Lamp Base: -

Replacement Lamp: -

Beam Angle: 80° x 120°

Lighting Configuration: Flood

Power Efficiency: >95%

Power Factor: 0.992

Amps: 0.63A @ 120V, 0.36A @ 208V, 0.34A @ 220V, 0.32A @ 240V, 0.27A @ 277V

Ambient Operating Temp Range: -50°C to +65°C

Operating Temp Rating: T5

Ratings/Approvals

Class I, Division 2 Groups A, B, C and D

Class II, Division 1 Groups E, F and G

Class II, Division 2 Groups F and G

Class III, Divisions 1 & 2

NRTL Certified to UL 844 Ed. 13

NRTL Certified to UL 1598

NRTL Certified to C22.2 No. 137 Rev 2009

NRTL Certified to C22.2 No. 250.0

NRTL Certified to C22.2 No. 30-M-1986 Rev 2012

IEC 60529 Tested

IP66 Rated Waterproof

Replacement for Fluorescent Linear Fixtures

Field Serviceable

Housing Material: Copper Free Cast Aluminum (non sparking)
Housing Finish: Epoxy Powder Coated - Gray
Lens Material: Hardened Polycarbonate
Gasket Material: Silicone
Mounting: (2) Pipe Mount Brackets - Other Mounts Available
Wiring Hub: (1) 3/4" NPT

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The Larson Electronics HAL-LC-24-LED-R2-1227-APM Hazardous Location Integrated LED Linear Fixture offers powerful lighting with heavy-duty and energy efficient benefits in combustible sites. This 75-watt LED unit delivers 11,550 lumens and is field serviceable. Compatible with pipe mount bracket installations (such as under large pipes, poles, pipe racks, industrial catwalks and more), the IP66 rated fixture operates on universal 120-277V AC, 50/60Hz and features a 3/4" NPT wiring hub.

The HAL-LC-24-LED-R2-1227-APM is a Class I, Division 2 and Class II, Division 1 & 2 linear fixture that is designed for reliable illumination in facilities that contain hazardous gases/vapors. This 75-watt fixture offers 11,550 lumens of high quality light. An 80° x 120° flood beam angle promotes wide light distribution in the surrounding area. Color temperature options for the LED light includes: 5000K, 4500K, 4000K, 3500K or 3000K. This unit is a suitable replacement for fluorescent linear fixtures. Equipped with field serviceable features, the LED assembly is sealed from the driver box, allowing the driver to be changed without impacting the LEDs.

This hazardous location light is protected by a copper-free cast aluminum housing, with an epoxy powder coated gray finish for durability in rugged environments. The non-sparking housing is specially designed to dissipate heat, which increases the efficiency and lifespan of the LEDs and electronic components. Equipped with a hardened polycarbonate lens, the T5-rated LED fixture carries an IP66 waterproof rating.

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.

LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

Field Serviceability: This LED light fixture is field serviceable. All major internal components can be purchased from Larson Electronics and installed by a licensed electrician with basic tools. With most explosion proof fixtures, the fixture must be returned to the manufacturer for repair work, which presents downtime and long turn around times for repair work. Larson Electronics addresses this issue with products that cater to field serviceability, allowing operators to perform service work without having to return the fixture to the manufacturer in the event of damage or failure.

Voltage: The hazardous location light is universal voltage capable and can be operated with 120-277V AC, 50/60Hz.

Wiring: A 3/4" NPT hub at the back of the unit is available for completing wiring connections.

Mount: This linear LED light fixture comes standard with two pipe mount brackets at both ends of the unit. Several mounting options including pendant, ceiling and wall mounts for replacing existing light fixtures can be ordered separately.


Suggested Applications: Hazardous locations, oil drilling rigs, refineries, solvent and cleaning areas, chemical manufacturing, waste treatment plants, gas processing plants, aircraft maintenance and more.


At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.



Frequently Asked Questions (FAQ)









HAL-LC-24-LED-R2-1227-APM

Product ID: 277407

Warranty: 60 Months.

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

HAL-LC-24-LED-R2-1227-APM-Color Temp

Example: HAL-LC-24-LED-R2-1227-APM-50K

Color Temp	
5000K	-50K
4500K	-45K
4000K	-40K
3500K	-35K
3000K	-30K

Links (Click on the below items to view):

- [IES \(Photometric File\)](#)
- [Operations Manual](#)
- [Wiring Diagram](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [Video1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)