

EHL-LED-ITG-120XLVAC-C1D1-100

15W Explosion Proof LED Handlamp - 120-277V AC to LV AC - EXP Inline Xfr - 100' Cord w/ EXP Cord Cap

Product ID: 278395

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EHL-LED-ITG-120XLVAC-C1D1-100 Explosion Proof LED Handlamp

Unit Type: Explosion Proof LED Handlamp

Dimensions: L-20.8" Dia-5"

Lamp Weight: 4.5 lbs

Input Voltage: 120-277V AC

Output Voltage: 12V or 24V AC

Total Watts: 15

Total Lumens: 2,400

Luminous Efficacy: 160 Lm/W

Lamp Life: 50,000+ Hours

Color Temp: 5,000K

Color Rendering Index: 70

Ambient Operating Temperature: -20°C to +50°C

Housing Material: Aluminum Alloy with Nylon Zytel Handle

Mounting: Handheld with Annealed Aluminum Wire Swivel Hook

Lens Material: Tempered Soda Lime Glass; Frosted

EXP Transformer: 120-277V AC to LV - Inline

Wiring: 100' 12/3 SOOW Cable, inline xfmr, 10' 16/3 SOOW

Cord Cap Options: 5-15P or 5-20P

YOU CAN RENT THIS UNIT. CONTACT 1-800-369-6671

Ratings/Approvals

Listed for United States and Canada

Class I, Division 1 & 2 Groups C, D

Class II, Division 1 & 2 Groups F, G

NEMA 4X

T4 Temperature Rating

EXP Inline Stepdown Transformer

360° Illumination

Special Orders - Special Requirements

Contact us for special requirements

Intl: 1-903-270-1187

Toll Free: 1-800-369-6671

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com



Frequently Asked Questions (FAQ)









EHL-LED-ITG-120XLVAC-C1D1-100

Product ID: 278395

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

EHL-LED-ITG-120XLVAC-C1D1-100-Cord Cap-Output Voltage

Example: EHL-LED-ITG-120XLVAC-C1D1-100-1523-12V

Cord Cap	
5-15P	-1523
5-20P	-2023-125V
6-20P	-2023-250V

Output Voltage	
12V DC	-12V
24V DC	-24V

Links (Click on the below items to view):

- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [Video1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)