Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671


www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

HAL-EMG-48-2L-LED-BMSW-D-V2

0-10V Dimmable C1D2 Emergency LED Pivoting Light - 4 Foot 2 Lamp - Offshore LED Rig Light - Meets USCG Specs

Product ID: 278761

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

HAL-EMG-48-2L-LED-BMSW-D-V2 Hazardous Location LED Fixture

Listing: NRTL Listed for United States and Canada
Lamp Technology: LED
Lamp Qty: (2) 4'
Dimensions: 51.1"-L x 7.09"-W x 8.65"-H
Weight: 22.2 Lbs
Voltage: 120V or 277V
Total Watts: 56W
Single-lamp Watts: 28W
Total Lumens: 7,000 lms
Single-lamp Lumens: 3,500 lms
Luminous Efficacy: 120 Lumens per Watt
Lamp Life: 50,000+ Hours
Color Temp: 5600K, 4500K or 3000K
Color Rendering Index: >80
Lamp Type: -
Lamp Base: -
Replacement Lamp: -
Beam Angle: 150°
Lighting Configuration: Flood
Power Efficiency: 90%

Ratings/Approvals

Class I Division 2, Groups A, B, C & D
NRTL Certified to UL 844
NRTL Certified to UL 1598A Marine Type
T4 Temperature Rating
Meets USCG Specs
California Title 24 Compliant
0-10V Dimmable

Power Factor: >0.95
Emergency Runtime: 90 Minutes
Emergency Battery Charging Duration: 24 Hours
Emergency Lumens: (1) Lamp - Output Depends on Dim Setting
Amps: -
Ambient Operating Temp Range: -40°C to +65°C
Operating Temp Rating: T4
Materials: Sheet Aluminum Housing, Acrylic Lens
Mounting: Back Mount Swivel Bracket
Wiring Hub: 1/2" or 3/4" Threaded

Special Orders - Special Requirements
Contact us for special requirements

Intl: 1-903-270-1187
Toll Free: 1-800-369-6671
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

Made in the USA

The Larson Electronics HAL-EMG-48-2L-LED-BMSW-D-V2 Hazardous Area 0-10V Dimmable LED Emergency Light Fixture is NRTL Listed for United States and Canada Class I Division 2 Groups A, B, C and D - NRTL Certified to UL 1598A listed, has a T4A temperature rating and ideal for hazardous locations where flammable chemical/petrochemical vapors may be occasionally encountered. This emergency hazardous location LED light carries a United States Coast Guard approval, making it recommended for applications such as oil rigs, ships, offshore applications, petrochemical, manufacturing, chemical storage, and water treatment centers.

This four foot long, two lamp, 0-10V dimmable emergency LED fixture is ideal for operators seeking a top quality hazardous location light that will reduce operating costs, improve lighting quality and reduce downtime incurred from frequent servicing intervals. The HAL-EMG-48-2L-LED-BMSW-D-V2 fixture is a 4 foot long, 2 lamp, Class I Division 2 Groups A, B, C and D hazardous area LED light that takes the reliability and efficiency of a fluorescent fixture and adds even longer lamp life and efficiency with high output LEDs. This fixture is T4A temperature rated and comes standard with our high power 28 watt LED lamps. The emergency lamps are protected by a powder coated aluminum frame and shatter and heat resistant clear acrylic lens secured with ten zinc coated steel draw latches.

We now offer our second generation dimmable LED tube lamps with this fixture which have increased this hazardous location light`s performance. This two lamp HAZLOC LED linear fixture is lighter in weight and produces more light than hazardous location fluorescent fixtures. The four foot long LED tube design bulbs included with this unit are rated at 50,000+ hours of service life, which is over twice as long as standard T8 bulbs.

Dimming: This LED light fixture features 0-10V dimming capabilities. This gives operators the ability to manually adjust the brightness of the LED lamp quickly and easily. The 0-10V dimming allows for adjustments to fit the brightness needs of any lighting situation. A 0-10V dimmable light works through the use of a DC control signal that ranges between zero and ten volts. The basic idea is that at 10 volts of input the light is at its brightest level with 0 volts being the lowest possible dimness setting. The smooth, continuous and flicker-free dimming of a 0-10V dimmable LED light is ideal for a wide range of different lighting applications.

Emergency Operation: The LED light features an emergency backup battery that will run one lamp for 90 minutes following power outage or any loss of power. Emergency lamp output depends on the dim setting. The emergency backup battery takes 24 hours to recharge.

This fixture carries a T4A temperature rating and is NRTL Certified to U.L. 595 and UL 1598A Marine Type approved for use marine environments. The fixture is constructed of copper free sheet aluminum and powder coated. The lamp reflector is corrosion resistant heavy gauge aluminum and coated with a high gloss reflective finish. The HAL-48-2L-LED-G2 is weatherproof and provides operators in hazardous locations with a highly efficient, reliable and affordable lighting solution for open areas where flammable chemicals and vapors may occasionally be present. Click here to read the NEC description for explosion proof and hazardous locations.

Click here to see the new HAL-48-2L-ITG-LED-BMSW Class I Division 2 integrated LED fixture producing 19,200 lumens.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Click Photo to Enlarge



Click Photo to Enlarge



Click Photo to Enlarge

We have eliminated the ballast normally associated with fluorescent fixtures which reduces overall weight and overall complexity of installation. There is no ballast in this unit and the included LEDT8-28W-V1 LED lamps have a 50,000+ hour service life, both of which result in extreme efficiency and greatly reduced maintenance costs. The solid state design of the LED lamps give this fixture superior resistance to damage from vibration, extremes in temperature and a lamp service life over twice that of standard fluorescent bulbs. This second generation lamp is offered in 5600K cool white, 4500K natural white, and 3000K warm white. Our standard unit ships with 5600K unless different color temperature is specified.
Unlike the glass tube design of traditional fluorescent lamps, these LED T-Style lamps have no filaments or fragile housings to break during operation. Instead of using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current applied and emitting light. The LED assembly is mounted to the "tube" constructed from extruded aluminum, with a polycarbonate lens protecting the LEDs. With LED lights, there is no warm up time or cool down time before re-striking and provide instant illumination when powered on, adding to the reliability of LED technology. By nature, LED light sources run significantly cooler than fluorescent lamps, reducing the chance of accidental burns and increased temperatures due to heat emissions. This solid state design of light emitting diodes provides a more reliable, stable, durable, and energy efficient light source over traditional fluorescent lighting.
The 28 watt LED lamps produce 30% more illumination than standard T8 bulbs while offering lower amp draw and increased reliability. Each lamp produces 3,500 lumens at 125 lumens per watt, for a combined 7,000 total lumen light output. Standard 0-10V dimming switches (mounted outside the hazardous location) are compatible with these hazardous location fixtures. Larson Electronics offers an explosion proof dimmer switch for mounting within the hazardous location.
Voltage: The HAL-EMG-48-2L-LED-BMSW-D-V2 operates on 120V or 277V.

Energy Consumption Comparison

	T5HO	T8	LED
Wattage	108 watts	64 watts	56 watts
Amp Draw @ 120V AC	0.90 amps	0.54 amps	0.47 amps
Amp Draw @ 220V AC	0.49 amps	0.29 amps	0.25 amps
Amp Draw @ 240V AC	0.45 amps	0.27 amps	0.23 amps
Amp Draw @ 277V AC	0.39 amps	0.24 amps	0.20 amps
Lamp Life Expectancy	20,000 hours	24,000 hours	50,000 hours
Color Temperature	5000K / 4100K	4100K	5600K
Operation cost per year (12hs/day @ 12c/kWh)	$56.77	$33.64	$29.43

Mounting Options: Unless otherwise specified, our standard, most popular configuration is the bracket end mounting shown enlarged below. We also offer a pendant mount for those needing to suspend the fixture away from the ceiling surface (i.e. suspend from pipe or conduit). Additional mounting configurations can be customized to meet the requirements on the application. Please contact us for special mounting configurations.
Standard Surface Mount Brackets: Each L bracket is cinched to the bracket

mounting peg on each side of the light. The angle of the bracket is set by tightening two bolts on either side of the bracket. The bolts act as a set screw. The bracket itself is mounted via a single bolt hole at the top the bracket. There are two brackets. Once the brackets are mounted to a surface (ceiling, floor or wall), the light fixture can be pivoted by loosening the that hold the bracket to the mounting peg. This fixture allows 45° of pivot from the 90° point.

Suggested Applications: Aircraft maintenance, oil drilling rigs, refineries, marine and salt water environments, ships, tankers, offshore, solvent and cleaning areas, chemical manufacturing, waste treatment plants, gas processing plants.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.


Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)









Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

HAL-EMG-48-2L-LED-BMSW-D-V2

Product ID: 278761

Warranty: 60 Months.

Harmonized System (HS) Code: 9405.41.84.10
Export Control Classification Number (ECCN): EAR99

Options:

HAL-EMG-48-2L-LED-BMSW-D-V2-Color Temp-Hub Config-Voltage

Example: HAL-EMG-48-2L-LED-BMSW-D-V2-56K-0.5IN-120V

Color Temp	
5600K	-56K
4500K	-45K
3000K	-30K

Hub Config	
1/2IN	-0.5IN
3/4IN	-0.75IN

Voltage	
120V	-120V
277V	-277V

Links (Click on the below items to view):

- **Operations Manual**
- **Wiring Diagram**
- **HigResPic1**
- **HigResPic2**
- **HigResPic3**
- **HigResPic4**
- **HigResPic5**
- **HigResPic6**
- **HigResPic7**
- **HigResPic8**
- **Video1**
- **Video2**
- **Video3**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**