Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MT-ISX-3P.1P-480D-10KVA-220V.EU-N3R-2X10C-M1

10 kVA Isolation Transformer - 480V Delta 3-Phase Primary - 220V Euro 1-Phase Secondary - NEMA 3R - Three Phase to Single Phase - 25A Fused Disconnect

Product ID: 280721

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-ISX-3P.1P-480D-10KVA-220V.EU-N3R-2X10C-M1 3-Phase to 1-Phase Isolation Transformer

Phase: Three Phase to Single Phase
Frequency: 60 Hz
kVA: 10
Primary Voltage: 480 V Delta 3P
Taps: 2 x 2.5% FCAN; 4 x 2.5% FCBN
Secondary Voltage: 220 V Euro (L-N 220V) 1P
Secondary Amps: 45 Amps Max Output
Winding Material: Aluminum
Insulation: 220°C
Temperature Rise: 150°C
Impedance (Std): -
Seismic: Yes
Sound Level: Meets NEMA ST-20 Standards
Primary Wiring: 10' 10/4 SOOW Cord w/ Blunt Cut End
Secondary Wiring: 10' 8/3 SOOW Cord w/ Blunt Cut End
Disconnect: Fused Disconnect - Fused at 25 Amps
Enclosure Material: NEMA Type 3R Heavy Duty Ventilated
Finish: ANSI 61 Grey Finish
Dimensions: 27.00"-H x 20.00"-W x 22.00"-D
Weight: 132 lb
Mounting: Floor Mount

Ratings

NRTL Listed for United States and Canada
ANN Cooling
IP14 Rated
Isolation Transformer

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

The MT-ISX-3P.1P-480D-10KVA-220V.EU-N3R-2X10C-M1 480 V Delta Three Phase to Single Phase Energy Efficient Isolation Transformer from Larson Electronics is powerful, reliable, and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-ISX-3P.1P-480D-10KVA-220V.EU-N3R-2X10C-M1 provides increased reliability and protection against critical equipment failures. The lower operating costs, lower heat emissions, and lower cost of ownership make this transformer ideal for a wide range of applications and businesses. The MT-ISX-3P.1P-480D-10KVA-220V.EU-N3R-2X10C-M1 is equipped with a disconnect fused at 25 amps.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

Transformer Features: With a transformer rating of 10 kVA, the MT-ISX-3P.1P-480D-10KVA-220V.EU-N3R-2X10C-M1 isolation transformer is a three phase to single phase unit with a primary voltage of three phase 480 V Delta. It also provides a secondary voltage of single phase 220 V Euro (L-N 220V). Featuring robust construction, this unit`s cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The Standard NEMA Type 3R enclosure makes the unit suitable for both indoor and outdoor applications and it can be floor mounted. The unit also features 220°C insulation with a 150°C temperature rise and is rated IP14.

Benefits: The MT-ISX-3P.1P-480D-10KVA-220V.EU-N3R-2X10C-M1 isolation transformer offers many benefits to the consumer. Precision cut aluminum transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations.

This isolation transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated floor brackets make installation fast and easy and the offset outward facing floor installation holes allow for easy power tool access.

Safety: The MT-ISX-3P.1P-480D-10KVA-220V.EU-N3R-2X10C-M1 is an isolation transformer which means that it provides operators with an increased level of protection against electric shock. An isolation transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-ISX-3P.1P-480D-10KVA-220V.EU-N3R-2X10C-M1 achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

Wiring: The MT-ISX-3P.1P-480D-10KVA-220V.EU-N3R-2X10C-M1 is equipped with both input and output cords for completing wiring connections. The primary side is outfitted with 10` of 10/4 SOOW cord terminated in a blunt cut end. The secondary side is outfitted with 10` of 8/3 SOOW cord terminated in a blunt cut end.

Applications: General purposes.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364


Frequently Asked Questions (FAQ)


Larson Electronics
1-800-369-6671

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364





MT-ISX-3P.1P-480D-10KVA-220V.EU-N3R-2X10C-M1

Product ID: 280721

Harmonized System (HS) Code: 85043300

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **Operations Manual**
- **Wiring Diagram (Oneline)**
- **HigResPic1**
- **HigResPic2**
- **HigResPic3**
- **HigResPic4**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**