

HID-2215M-SL-REM-108-X6

(6) 1500W Enclosed Remote Ballasts for HID-22-SL Series Metal Halide Fixtures - NEMA 3R Enclosure

Product ID: 281094

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

HID-2215M-SL-REM-108-X6 Enclosed Remote Ballasts

Equipment Type: Enclosed Remote Ballast System

Dimensions: -

Weight: -

Voltage Configurations: 120 V, 208 V, 240 V, or 277 V

Number of Ballasts: 6

Ballast Watts (Per Ballast): 1500 W

Ballast Watts (Total): 9000 W

Line-In Wiring: 10' Line-In Cord

Line-In Wiring Type: 120 V - 4/3 Type W; 208 V / 240 V - 2/3 SOOW; 277 V - 6/3 SOOW

Line-Out Wiring: (6) 20' 12/2 SOOW Cord w/ Quick Disconnects

Quick Disconnect Whip Length: 6"

Enclosure Rating: NEMA 3R / IP14

Mounting: Surface Mounting Holes for Flat Surface Mounting

Ratings/Approvals

(6) Ballasts

Quick Disconnects on Line-Out Wiring

NEMA 3R Rated Enclosure

Surface Mount

Can Power Up To (6) Light Fixtures

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

The HID-2215M-SL-REM-108-X6 from Larson Electronics is an Enclosed Remote Ballast System that contains six 1500 watt ballasts for HID-22-SL series metal halide fixtures. The ballasts are enclosed in a NEMA 3R enclosure.

This enclosed remote ballast system contains six 1500 watt remote ballasts that can be used to power six HID-22-SL series metal halide fixtures. The HID-2215M-SL-REM-108-X6 is available in 120 V, 208 V, 240 V, or 277 V configurations. Please make your selection when ordering.

Wiring: The HID-2215M-SL-REM-108-X6 is equipped with a 10' line-in cord. The type of line-in cord depends on the selected voltage configuration as follows: 4/3 Type W for 120 V, 2/3 SOOW for 208 V & 240 V, and 6/3 SOOW for 277 V. It is also equipped with six 20' 12/2 SOOW line-out cords for connection to each light fixture. Each line-out whip features a quick disconnect to allow for quick and easy connection to and disconnection from the light fixtures. There is a six inch whip after the disconnect.

Please note that this is for the remote ballasts, wiring, and enclosure ONLY. Light fixtures are sold separately.

Enclosure: The HID-2215M-SL-REM-108-X6 utilizes a NEMA 3R rated enclosure to house the six remote ballasts. The enclosure is outfitted with surface mount holes for mounting to flat surfaces.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.



Frequently Asked Questions (FAQ)

HID-2215M-SL-REM-108-X6

Product ID: 281094

Export Control Classification Number (ECCN): EAR99

Options:

HID-2215M-SL-REM-108-X6-Voltage

Example: HID-2215M-SL-REM-108-X6-120V

Voltage	
120	-120V
208	-208V
240	-240V
277	-277V

Links (Click on the below items to view):

- [HigResPic1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)