Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

RNT-SPLT-.53K-LM25-1XN3B-PW-NB-TLR7

RENT Portable Solar Light Tower - 25' Mast - 7.5' Trailer - (1) Junction Box - No Batteries

Product ID: 281328

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

RNT-SPLT-.53K-LM25-1XN3B-PW-NB-TLR7 Trailer Mounted Solar Generator Light Mast

Light Mast Specs

Tower Length: 13.5` to 25`
Mast Head Length: 44"
Materials: Steel
Finish: Powder Coated - Gloss Blue
Operation: (1) 1,000lbs Hand Winch
Mast Cable: 3/16" Galvanized Aircraft Cable
Cable Sheath: Sealtight Coiled Tubing

Solar Specs

Panels: (2) 265 Watt panels
Method of Deployment: Fixed Mount
System Voltage: 12V or 24V
Battery Bank: Customer Provided - Accepts up to (2) 8D Batteries
Battery capacity: -

Trailer Specs

Materials: Steel
Trailer Dimensions: 7.5`L` x 7`W trailer bed- 10.75` total length
Hitch: 2" Ball Coupler
Wiring: 7-Pin Flat
Axle: 3,500lb
Suspension: 3,500 Lb 4-Leaf Double Eye Springs

Quick Summary

13.5` to 25` Light Mast
Steel Construction
Powder Coated Finish
Removable Mast Head
(4) 1,000lb Outriggers
125 mph Wind Resistance
Manual or Optional Electric Operation
A-Frame for mounted (2) 265 Watt Solar Panels
Fully Solar, No Fuel Needed

Outriggers: (4) 1,000 Manual Crack Leveling Jacks

Wheels: (2) 15" 5x4.5 Steel Rims

Tires: ST205/75/D15 H188

Weight: +-600 lbs

Shipping: Common Freight

Shipping Dimensions: 8`-L x 8`-W x 12`-H

Shipping Weight: +-600 lbs

Options: Length- Mounting-Fixtures/ Call Us for Special Requirements

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

This unit is for rentals

Made in the USA

The Larson Electronics RNT-SPLT-.53K-LM25-1XN3B-PW-NB-TLR7 solar powered LED light tower provides a safe and effective way for operators to quickly deploy cameras, security devices, and other equipment to elevations up to twenty-five feet. This solar light plant features a telescoping light tower that folds over for easy transportation, features a rotating boom that allows for 360° of rotation, and a removable mast head for storage when not in use. This unit features two 265 watt solar panels.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO LIGHT MASTS OR LIGHT TOWERS

This trailer mounted light mast with solar generator has a 12" x 12" x 6" junction box mounted at the top of the mast for connecting cameras and other devices. This junction box is ideal for mounting security cameras for a 360° field of view along with other electrical devices for each operator`s specific needs. The top mounted junction box is mounted to the mast head via a half-moon shaped mounting plate. External sealtite coiled tubing runs around the mast to allow operators to run Ethernet cable to the junction box at the top of the mast. The tubing connects the junction box and base solar component box together. The entire assembly is mounted onto a 7.5` single axle trailer, allowing operators to transport this portable solar light tower from location to location.



Click Photo to Enlarge



Click Photo to Enlarge



Click Photo to Enlarge







Solar Powered Light Tower: This solar light tower includes two 265 watt solar panels, solar charging system, battery bank and manual crank up mast mounted on trailer with outriggers. This 0.53KW solar generator system replenishes amp hours of usable battery capacity per day, assuming 5.5 hours of peak charging sunlight. This system delivers 12 volts or 24 volts for equipment mounted atop the 25` telescoping light mast.

Light Mast: This telescoping five stage steel light mast from Larson Electronics is designed to allow operators to quickly and safely deploy a variety of equipment in locations where it must be elevated to heights up to 25` for effective coverage. This light mast can be extended to 25` above the trailer floor for maximum area coverage, and collapsed to 13.5` for applications where a footprint smaller is required. TThe

tower is constructed of square steel tubing with a base section 6.6` in length and 6" by 6" by 3/16" thick, lower section 6.78` in length and 5" by 5" by 3/16" thick, middle section 6.93` in length and 4" by 4" by 1/8" thick, upper section 7.08` in length and 3" by 3" by 1/8" thick, and top section 7.58` in length and 2" by 2" by 1/8" thick. Each section has a 1`+ overlap. The mast is extended to its full height using an included 1,000lb rated hand winch with 3/16" galvanized steel cable. Junction boxes are mounted at the top of the first stage and at the very top of the mast for equipment setup, connection, and deployment.

A 44" wide and 2" by 2" by 1/4" thick mounting plate is attached to the upper section of the mast which provides a strong and stable platform for the equipped LED light fixtures. A half-moon shaped mounting plate on the top of the mast head provides a secure mounting platform for the NEMA 3R 12" x 12" x 6" junction box, where operatores can mount cameras, indicator lights, and route electrical cabling. When elevated to its full upright position, the mast can be rotated a full 360°. By loosening the T-Handle, operators can rotate the mast with easy in either direction. The mast can be positioned in one of four different positions, and locked back in place by re-tightening the T-handle. The mast itself spins freely with easy, and can typically be rotated with a single hand. The LM series of towers are powder coated with glossy blue finish for corrosion resistances and aesthetics.

The LM family of telescoping towers feature a proprietary mast guidance system, which provide increased stability during high winds. Four 1,000 lbs hand crank leveling jacks are used for leveling. The jacks can be leveled by hand crank or attachment provided for power drills. These outriggers can be extended 2` out from the side of the trailer for added stability. When lowered to 13.5`, the mast can withstand winds up to 125 mph. Custom builds can be provided for higher wind speed resistance when fully raised.



Click Photo to Enlarge



Click Photo to Enlarge



Click Photo to Enlarge

Solar Panel Assembly: This unit is comprised of two 265-watt solar panels, generating a total maximum output of 0.53 KW. The panels are mounted to a stationary assembly. The panels are wired to the solar charger control box which manages the charging system. The two solar panels are mounted to a frame angled at 45° to capture the intensity of the sun for optimized light intake.

Component Control Center: All the electrical components are encapsulated in a NEMA 3R job box that is bolted to the trailer. Since most of these components are not rated for high heat, our component cooling system circulates air within the job box at 1400 CFM when the ambient temperature exceeds 90 degrees Fahrenheit. The job box that contains the component control system includes locks for security purposes. A 12" by 12" plate allows operators to mount user provided equipment within the job box. This control center houses the operator provided battery bank, which is designed to hold up to two 8D batteries.

Trailer Assembly: The entire assembly is mounted to a 7.5` by 7`, single axle trailer via six 1/2" anchor bolts. The two wheel trailer is equipped with 3,500 lbs axle and leaf springs with 15" trailer tires. A standard 2" ball coupling, two standard safety chains, and 7-pin flat trailer plug allow for easy hookup and towing. The trailer tongue can be removed for long term deployment. A rugged and waterproof job box is included, safely secured to the trailer. Four outriggers mounted to the corners of the trailer allow operators to level the trailer, and provide stabilization during deployment. All trailer lighting complies with DOT/FMVSS regulations.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)







Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

RNT-SPLT-.53K-LM25-1XN3B-PW-NB-TLR7

Product ID: 281328

Export Control Classification Number (ECCN): EAR99

Options:

RNT-SPLT-.53K-LM25-1XN3B-PW-NB-TLR7-Rental Length-Voltage

Example: RNT-SPLT-.53K-LM25-1XN3B-PW-NB-TLR7-MR-12V

Rental Length	
MONTHLY	-MR
WEEKLY	-WR
DAILY	-DR

Voltage	
12V	-12V
24V	-24V

Links (Click on the below items to view):

- HigResPic1
- HigResPic2
- HigResPic3
- HigResPic4
- HigResPic5
- HigResPic6
- HigResPic7
- HigResPic8
- HigResPic9
- HigResPic10
- Video1
- Video2
- ISO 9001 Certification
- Business Certificate
- Shipping Time Map