

EPEXC-4X-12.3-300

Explosion Proof 4 Outlet Extension Cord - (4) Outlets - 20A Continual Service - 300' SOOW Cable

Product ID: 281346

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPEXC-4X-12.3-300 Explosion Proof Extension Cord

Amp Rating: 20 amp Continuous Service

Dimensions: Cord-300 Feet Plug-2.78"-L 1.75"-W

Configuration: 2 Pole 3 Wire

Suitable Plug Cable Diameter: .538" to .639"

Wiring: 300' 12/3 SOOW Cable Terminated w/ (1) Explosion Proof Straight Blade Plug and

(4) 20 Amp Receptacles

Cord Cap: 20 Amp 5-20P (125V) or 20 Amp 6-20P (250V) EXP Plug

Voltage: 125 Volts or 250 Volts

Plug / Outlet Certifications

Class 1 Div 1 Groups C and D

Class 2 Div 1 Groups F and G

Receptacle Specs: 4 Inline Receptacles

Configuration: 2 Pole 3 Wire

Materials: Copper Free Aluminum

Dims:- Single Receptacle- 3"-W X 5.69"-D X6.13"-H

Mating Plugs: ****[EPP-15A](#), [EPP-20-A](#)****

Finish: Epoxy Powder Coat

[U.L. Certification](#)

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Made in the USA

The Larson Electronics EPEXC-4X-12.3-300 300' Explosion Proof extension cord allows operators to safely extend the range of their explosion proof light or equipment cords beyond the boundaries of the hazardous work area.

These units are constructed of 300 feet of 12/3 SOOW explosion proof cord and are rated at 20 amps of continuous service. The cord is chemical and abrasion resistant and

comes with four inline, 20 amp, explosion proof receptacles installed on one end and a standard explosion proof plug installed on the other end. This unit enables multiple connections from a single cord.

The plugs on these units are of a twist lock design. In order for a secure and working connection to take place, the operator must insert the plug and twist until it locks into place. This ensures a safe seal is made before any sparks from electrical contact can take place. To ensure the highest safety, operators should make connections outside of the hazardous area.

We offer this unit in a 125V or 250V configuration. Each receptacle's contacts are deep recessed to avoid accidental contact and will accept standard non explosion proof plugs that are NEMA 5-20R, or 6-20R compatible although explosion proof plugs must be used to preserve explosion proof approval in hazardous environments. Ordinary location plugs will NOT activate this cord's explosion proof receptacles.

[Click Photos to Enlarge](#)



125V 5-20P Explosion Proof
Straight Blade Plug

These explosion proof extension cords are preconfigured in 125V (left) or 250V (right). Each unit is equipped with a 20 amp explosion proof cord cap and rated for 20 amps of continual service. The outlets are a twistlock design. The deep recessed contacts in the receptacle housing prevents ordinary and wet location plugs from activating the explosion proof outlets.



250V 6-20P Explosion Proof Straight
Blade Plug



125V 15/20 Explosion Proof
Outlet



Outlet accepts 15A and 20A Explosion
Proof Plugs




Outlet accepts 6-15P and 6-20P
Explosion Proof Plugs


Inter-Compatibility: These cords use T style plugs and will work with non-explosion proof standard receptacles and plugs (NEMA 5-15R, 5-20R, or 6-20R) but will not work with standard 120V wall outlets. The included plugs and receptacles are cross-interchangeable with Crouse Hind™ part# ENP5201 plugs and receptacles and Hubble-Killiark part# UGP-20231 ACCEPTOR® plugs and receptacles. Any equipment requiring these C-H or H-B plugs should work with these cords. Due to possible manufacturer changes we cannot guarantee interchangeability although we have made every effort to ensure cross compatibility correctness.


Suggested Applications: Manufacturing, Industrial, Warehouse, Lighting, Explosion Proof Light Fixtures, Grinders, Wet areas or Locations Where Combustible Dust is Present.

Frequently Asked Questions (FAQ)









EPEXC-4X-12.3-300

Product ID: 281346

Export Control Classification Number (ECCN): EAR99

Options:

EPEXC-4X-12.3-300-Voltage

Example: EPEXC-4X-12.3-300-2023-125V

Voltage	
125V	-2023-125V
250V	-2023-250V

Links (Click on the below items to view):

- [Canadian CEC Certificate \(Commonly referred to as CSA Certificate\)](#)
- [CE Certificate](#)
- [Certificate 1, Misc](#)
- [Certificate 2, Misc](#)
- [Certificate 3, Misc](#)
- [MSDS \(Material Safety Data Sheet\)](#)
- [Operations Manual](#)
- [RoHS Certificate \(Restriction of Hazardous Substances\)](#)
- [USA NEC Certificate \(Commonly referred to as UL Certificate\)](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [Video1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)