Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

HAL-PRM-LED-R2-125VDC-WP-TRN

100W Hazardous Location Integrated Wall Pack LED Fixture - C1D2, C2D1 - 125V DC - 16,300 lms/Trunnion Mount - IP66/Field Serviceable

Product ID: 282292

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: HAL-PRM-LED-R2-125VDC-WP-TRN

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

HAL-PRM-LED-R2-125VDC-WP-TRN - Hazardous Location LED Fixture

Listing: NRTL Listed to United States, Canada
Lamp Technology: LED
Dimensions: 12.6'"-L x 9.8"-W x 5.95"-H
Weight: -
Voltage: 125V DC
Total Watts: 100W
Total Lumens: 16,300 lms
Luminous Efficacy: 152 Lm/w
Lamp Life: 75,000+ Hours
LED Color Temperature: 5000K, 4500K, 4000K, 3500K, or 3000K
Color Rendering Index: -
Lamp Type: Integrated LED
Lamp Base: -
Replacement Lamp: -
Beam Angle: 24°, 60°, or 90°
Lighting Configuration: Spot or Flood
Power Efficiency: >95%
Power Factor: 0.992
Amps: 0.8 A @ 125 V DC
Ambient Operating Temp Range: -50°C to +65°C

Ratings/Approvals

Class I, Division 2 Groups A, B, C and D
Class II, Division 1 Groups E, F and G
Class II, Division 2 Groups F and G
Class III, Divisions 1 & 2
NRTL Certified to UL 844 Ed. 13
NRTL Certified to UL 1598
NRTL Certified to C22.2 No. 137 Rev 2009
NRTL Certified to C22.2 No. 250.0
NRTL Certified to C22.2 No. 30-M-1986 Rev 2012
IEC 60529 Tested
IP66 Rated Waterproof
Replacement for Fluorescent Wall Pack Fixtures
Field Serviceable

Operating Temp Rating: T5
Housing Material: Copper Free Cast Aluminum (Non-Sparking)
Housing Finish: Epoxy Powder Coated - Gray
Lens Material: Hardened Borosilicate Glass
Gasket Material: Silicone
Mounting: Trunnion Mount - Other Mounts Available
Wiring Hub: (1) 3/4" NPT

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

The HAL-PRM-LED-R2-125VDC-WP-TRN from Larson Electronics is a Hazardous Location Integrated Wall Pack LED Fixture that offers powerful lighting with heavy-duty and energy efficient benefits in Class I, Division 2 rated hazardous locations that contain combustible gases/vapors. This 100-watt LED unit delivers 16,300 lumens and is field serviceable. Compatible with trunnion mount installations, the IP66 rated fixture operates on universal 125V DC and features a 3/4" NPT wiring hub. The LED unit is recommended for illuminating busy, outdoor ground areas for vehicles and pedestrians.

The HAL-PRM-LED-R2-125VDC-WP-TRN is a Class I, Division 2 and Class II, Division 1 & 2 wall pack fixture that is designed for reliable illumination in facilities with hazardous gases/vapors. This 100-watt fixture offers 16,300 lumens of high quality light along the outdoor, exterior areas of buildings. The LED fixture is offered in a 24-degree spot, 60-degree flood or 90-degree wide flood beam configuration. Color temperature options for the LED light includes: 5000K, 4500K, 4000K, 3500K, or 3000K. This unit is a suitable replacement for fluorescent wall pack fixtures. Equipped with field serviceable features, the LED assembly is sealed from the driver box, allowing the driver to be changed without impacting the LEDs.

This hazardous location light is protected by a copper-free cast aluminum housing, with an epoxy powder coated gray finish for durability in rugged environments. The non-sparking housing is specially designed to dissipate heat, which increases the efficiency and lifespan of the LEDs and electronic components. Equipped with a hardened borosilicate glass lens, the T5-rated LED fixture carries an IP66 waterproof rating. We can add a downward glare shield to reduce light spillage and for dark sky compliance at an additional cost.

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.

LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

Field Serviceability: This LED light fixture is field serviceable. All major internal components can be purchased from Larson Electronics and installed by a licensed electrician with basic

tools. With most explosion proof fixtures, the fixture must be returned to the manufacturer for repair work, which presents downtime and long turn around times for repair work. Larson Electronics addresses this issue with products that cater to field serviceability, allowing operators to perform service work without having to return the fixture to the manufacturer in the event of damage or failure.

Voltage: The hazardous location light is universal voltage capable and can be operated with 125V DC.

Wiring: A 3/4" NPT hub at the back of the unit is available for completing wiring connections.

Mount: This LED light fixture comes standard with trunnion mounting features. Several mounting options including ceiling, wall and pendant mounts for replacing existing light fixtures can be ordered separately.

Suggested Applications: Hazardous locations, outdoor areas, buildings, exterior walls, oil drilling rigs, refineries, solvent and cleaning areas, chemical manufacturing, waste treatment plants, gas processing plants, aircraft maintenance and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs



Image: HAL-PRM-LED-R2-125VDC-WP-TRN

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: HAL-PRM-LED-R2-125VDC-WP-TRN



Image: HAL-PRM-LED-R2-125VDC-WP-TRN




Image: HAL-PRM-LED-R2-125VDC-WP-TRN

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

HAL-PRM-LED-R2-125VDC-WP-TRN

Product ID: 282292

Warranty: 60 Months.

Harmonized System (HS) Code: 9405.41.84.10
Export Control Classification Number (ECCN): EAR99

Options:

HAL-PRM-LED-R2-125VDC-WP-TRN-Beam Angle-Color Temp
Example: HAL-PRM-LED-R2-125VDC-WP-TRN-24B-50K

Beam Angle	
24-DEGREE SPOT	-24B
60-DEGREE FLOOD	-60B
90-DEGREE WIDE FLOOD	-90B

Color Temp	
5000K	-50K
4500K	-45K
4000K	-40K
3500K	-35K
3000K	-30K

Links (Click on the below items to view):

- **Canadian CEC Certificate (Commonly referred to as CSA Certificate)**(https://www.larsonelectronics.com/images/product/CECCert/282292.PDF)
- **CE Certificate**(https://www.larsonelectronics.com/images/product/CECert/282292.PDF)
- **FCC Certificate (Federal Communications Commission, USA)**(https://www.larsonelectronics.com/images/product/FCCCert/282292.PDF)
- **MSDS (Material Safety Data Sheet**(https://www.larsonelectronics.com/images/product/Msds/282292.PDF)
- **Operations Manual**(https://www.larsonelectronics.com/images/product/Manual/282292.PDF)
- **RoHS Certificate (Restriction of Hazardous Substances)**(https://www.larsonelectronics.com/images/product/RoHSCert/282292.PDF)
- **USA NEC Certificate (Commonly referred to as UL Certificate)**(https://www.larsonelectronics.com/images/product/NECCert/282292.PDF)
- **Wiring Diagram**(https://www.larsonelectronics.com/images/product/WiringDiagram/282292.PDF)
- **HigResPic1**(https://www.larsonelectronics.com/images/product/HigResPic1/282292.JPG)
- **HigResPic2**(https://www.larsonelectronics.com/images/product/HigResPic2/282292.JPG)
- **HigResPic3**(https://www.larsonelectronics.com/images/product/HigResPic3/282292.JPG)
- **HigResPic4**(https://www.larsonelectronics.com/images/product/HigResPic4/282292.JPG)
- **HigResPic5**(https://www.larsonelectronics.com/images/product/HigResPic5/282292.JPG)
- **HigResPic6**(https://www.larsonelectronics.com/images/product/HigResPic6/282292.JPG)
- **HigResPic7**(https://www.larsonelectronics.com/images/product/HigResPic7/282292.JPG)
- **HigResPic8**(https://www.larsonelectronics.com/images/product/HigResPic8/282292.JPG)
- **HigResPic9**(https://www.larsonelectronics.com/images/product/HigResPic9/282292.JPG)
- **HigResPic10**(https://www.larsonelectronics.com/images/product/HigResPic10/282292.JPG)
- **Video1**(https://www.youtube.com/watch?v=aOzETLXcJMU)
- **Video2**(https://www.youtube.com/watch?v=AQ5sXJ2wZt8)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)