

MT-DOE16-SS-FP-1P-240.480V-7.5KVA-120V-N4X

7.5 KVA Isolation Transformer - 240/480V Primary - 120V Secondary - NEMA 4X - Stainless Steel - Fully Potted

Product ID: 283652

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: MT-DOE16-SS-FP-1P-240.480V-7.5KVA-120V-N4X

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-DOE16-SS-FP-1P-240.480V-7.5KVA-120V-N4XX Fully Potted Isolation Transformer Ratings

Phase: Single Phase

Frequency: 60 Hz

kVA: 7.5

Primary Voltage: 240/480V

Primary FCAN: None

Primary FCBN: None

Secondary Voltage: 120 V

Winding Material: Aluminum

Insulation: 180°C

Temperature Rise: 115°C

Impedance (Std): -

Seismic Zone: Zone 4

Sound Level: Meets NEMA ST-20 Standards

Primary Termination: Front Accessible Terminals

Secondary Termination: Front Accessible Terminals

Enclosure Material: NEMA Type 4X Heavy Duty Stainless Steel - Resin Encapsulated

Finish: Natural

Dimensions: TBD

Weight: TBD

Shipping Dimensions: 14.13"H x 48"W x 48"D

Shipping Weight: 103 lb

NRTL Listed for United States and Canada

ANN Cooling

IP66 Rated

Fully Potted / Encapsulated

DOE 2016 / NRCAN 2019 (Also Meets ON Reg. 404/12)

NRTL Certified to C22.2 No. 47

NRTL Certified to UL 506

Isolation Transformer

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Mounting: Wall Mount

E-mail: sales@larsonelectronics.com

The MT-DOE16-SS-FP-1P-240.480V-7.5KVA-120V-N4X 480 V 1 Phase Energy Efficient Fully Potted Isolation Transformer from Larson Electronics is powerful, reliable and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-DOE16-SS-FP-1P-240.480V-7.5KVA-120V-N4X provides increased reliability and protection against critical equipment failures. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

Transformer Features: With a transformer rating of 7.5 KVA, the MT-DOE16-SS-FP-1P-240.480V-7.5KVA-120V-N4X transformer is a single phase unit with a primary voltage of 480 V. It also provides a secondary voltage of 120 V. Featuring robust construction, this unit's cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This fully potted unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The Standard NEMA Type 4X stainless steel enclosure makes the unit suitable for both indoor and outdoor applications and it can be wall mounted. The unit also features 180°C insulation with a 115°C temperature rise and is rated IP66. These units are also available in NEMA 2, NEMA 3R, and NEMA 4 configurations. Please email Larson Electronics at sales@larsonelectronics.com for more information.

Benefits: The MT-DOE16-SS-FP-1P-240.480V-7.5KVA-120V-N4X general purpose transformer offers many benefits to the consumer. Precision cut aluminum transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations.

This fully potted transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated wall mounting brackets make installation fast and easy and the offset outward facing wall installation holes allow for easy power tool access.

Safety: The MT-DOE16-SS-FP-1P-240.480V-7.5KVA-120V-N4X is an encapsulated isolation transformer which means that it provides operators with an increased level of protection against electric shock. An isolation transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-DOE16-SS-FP-1P-240.480V-7.5KVA-120V-N4X achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

Applications: General purposes.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power



distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.



Frequently Asked Questions (FAQ)

There are no Faqs



Image: MT-DOE16-SS-FP-1P-240.480V-7.5KVA-120V-N4X



Image: MT-DOE16-SS-FP-1P-240.480V-7.5KVA-120V-N4X



Image: MT-DOE16-SS-FP-1P-240.480V-7.5KVA-120V-N4X



Image: MT-DOE16-SS-FP-1P-240.480V-7.5KVA-120V-N4X



Harmonized System (HS) Code: 85043300

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **Operations Manual**(<https://www.larsonelectronics.com/images/product/Manual/283652.PDF>)
- **Wiring Diagram**(<https://www.larsonelectronics.com/images/product/WiringDiagram/283652.PDF>)
- **HigResPic1**(<https://www.larsonelectronics.com/images/product/HigResPic1/283652.JPG>)
- **HigResPic2**(<https://www.larsonelectronics.com/images/product/HigResPic2/283652.JPG>)
- **HigResPic3**(<https://www.larsonelectronics.com/images/product/HigResPic3/283652.JPG>)
- **HigResPic4**(<https://www.larsonelectronics.com/images/product/HigResPic4/283652.JPG>)
- **HigResPic5**(<https://www.larsonelectronics.com/images/product/HigResPic5/283652.JPG>)
- **ISO 9001 Certification**(<http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF>)
- **Business Certificate**(<https://www.larsonelectronics.com/images/pdfdocs/w9.PDF>)
- **Shipping Time Map**(<https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf>)