

MPD-CD1-CLP6.400AB-YT0-ZZ-5.L35-20.N10-M1

400A Portable Panel Distribution System - 208V AC Wye 3-Phase - Camlock Inputs - MCB Circuit Breakers

Product ID: 284157

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MPD-CD1-CLP6.400AB-YT0-ZZ-5.L35-20.N10-M1 Temporary Power Distribution System

Line-in Cord: -

Line-in Cord Cap: 400A Single-Pole 16-Series Male Camlock Receptacles (1) Green, White, Black, Red, Blue [600V] w/ Covers

Primary Voltage (V): 208 V AC Wye

Primary Phase (PH): 3-Phase (3PH)

Primary Frequency (HZ): 60 Hz (60-cycles)

Primary Panel: 208Y/120V 3PH 400A MCCB Hinged N3R

Primary Breaker(s): (5) 30A 3P MCB [250V]; (10) 20A 1P MCB [125V]

Primary Outlet(s): (5) L14-30R NEMA Twist-Lock [208Y/120V]; (10) 5-20R NEMA GFCI-DPLX [125V]

Primary Protection: MCB Circuit Breakers; GFCI's

Transformer (kVA): -

Secondary Voltage (V): -

Secondary Phase (PH): -

Secondary Frequency -

Secondary Panel: -

Secondary Breakers: -

Secondary Outlets: -

Secondary Protection: -

Form Factor: Blue Powder Coated MGL Dolly Cart w/ No Flat Tires

Run Flat Tires: (2) Black

Frame Material: Steel

Frame Finish: High-Strength TGIC Polyester Powder Coated Blue

Cart Handle Orientation: -

Ratings

Max Primary OCP: 400 A @ 208 V

Max Secondary Output: -

NEMA 3R Indoor or Outdoor Use

Made in the USA

NRTL Certified to UL 1640

NRTL Certified to CSA C22.2 No. 14

Powder Coat Finish Standards:

Complies with ASTM D-523

Complies with ASTM D-3359

Complies with ASTM D-522

Complies with ASTM D-3363

Complies with ASTM D-2794

Special Orders - Special Requirements

Contact us for special requirements

Lifting Eyelet: (1) Center Point

Skid Pockets: -

Dimensions: -

Weight: -

Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

Intl: 1-903-270-1187

Toll Free: 1-800-369-6671

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Made in Texas

The MPD-CD1-CLP6.400AB-YT0-ZZ-5.L35-20.N10-M1 from Larson Electronics is a Portable Power Distribution System that is compatible with three-phase 208V AC Wye power. This fully enclosed power distribution unit provides operators the ability to safely tap into and distribute 208 V Wye AC power from a variety of sources including generators and direct grid power.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

The MPD-CD1-CLP6.400AB-YT0-ZZ-5.L35-20.N10-M1 temporary power distribution system gives operators the ability to power their 208 volt equipment from a single system.

Operation:

- Primary Voltage: 3-phase 208V AC Wye
- Primary Panel: 208Y/120V 3PH 400A MCCB Hinged N3R
- Primary Breaker(s): (5) 30A 3P MCB [250V]; (10) 20A 1P MCB [125V]
- Primary Outlet(s): (5) L14-30R NEMA Twist-Lock [208Y/120V]; (10) 5-20R NEMA GFCI-DPLX [125V]
- Transformer: N/A
- Secondary Voltage: N/A
- Secondary Receptacles: N/A

*See specification table at the top of the page for more information about the power distribution system.

Input Power Camlock Location: The camlock inputs for this unit are located on the narrow (26") side or end of the enclosure offering a convenient location for connecting input power.

Protective Construction: This temporary power distribution unit is fully enclosed and is ruggedly constructed to withstand demanding conditions and industrial applications. The system is accessible via two doors at each end for access to breakers on the panels and a center-located door for access to receptacles. The model is equipped with bottom-located forklift skid pockets and four top-located lifting eyelets, which allows easy lifting with cable or chain hooks.

The power distribution system is constructed of steel with a polyester powder coated blue finish for durability against dirt, moisture and mild corrosion. This special coating creates a high-strength barrier for protection from accidental bumps and scratches. The TGIC polyester powder coat finish offers reliable resistance against chemicals, UV light (sun light) and degrading elements in outdoor locations. Our powder coating solution ensures robust color retention for many years without fading. Custom colors, such as black, grey, desert tan or forest green, and galvanized finishes are available upon request. Non-standard powder coat colors or galvanized finishes may increase price and lead times.

Certification: All units are built in accordance to NFPA 70 (National Electric Code) and NRTL certified to UL 1640. All equipment is NEMA 3R rated for indoor and outdoor use and provide a degree of protection against dirt, water, and ice. NEMA 4 and NEMA 4X equipment can be equipped upon request.

Grounding: Transformer is grounded to the frame and we provide a grounding lug on the frame for the earth ground.

~Please check all motor loads for dual rated motors that will work 208 or 240.~

Applications: This power distribution system is ideal for indoor or outdoor use and applications including but not limited to, construction sites, plant maintenance, plant turnarounds, shows, exhibits, and shipyard operations. These

power distribution systems are popularly used in applications where external power sources are often necessary. We also offer class rated transformers for use within explosion proof and hazardous location environments.

Custom Built Systems Available: Larson Electronics is a manufacturer and we can build portable power distribution systems to your specifications. Although we carry several models of portable power distribution systems in stock, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.



Frequently Asked Questions (FAQ)





MPD-CD1-CLP6.400AB-YT0-ZZ-5.L35-20.N10-M1

Product ID: 284157

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [Operations Manual](#)
- [Single Line Diagram \(One-Line Diagram\)](#)
- [Wiring Diagram \(Online\)](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)