Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

EPP-250-2P-3X-20FT-15A

Explosion Proof Plug w/ Tri-Tap Receptacle - Pin Sleeve Cord Cap - 20' 12/3 SOOW - Hot Work Permit

Product ID: 284170

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: EPP-250-2P-3X-20FT-15A

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPP-250-2P-3X-20FT-15A - 20' Explosion Proof Plug w/ Tri-Tap Receptacle
Male Cord Cap: 2P3W Pin Sleeve - Explosion Proof
Female Receptacles: Tri-Tap 5-15R Receptacle
Voltage Rating: 125V 60Hz
Max Amp Rating: 15A
Cable Type: 12/3 SOOW
Cable Length: 20'
Weight: 1.5 lbs

Approvals/Ratings
C1D1 15A Male Cord Cap
Hot Work Permit

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

The EPP-250-2P-3X-20FT-15A from Larson Electronics is an Explosion Proof Plug with Tri-Tap Receptacle that is designed for heavy duty and outdoor applications. This rugged extension cord is constructed of six inches of 12-gauge 3-conductor wire, equipped with a 15-amp rated explosion proof 2-pole 3-wire pin sleeve male cord cap and features a tri-tap receptacle for powering a variety of general use devices.

The EPP-250-2P-3X-20FT-15A linecord provides a safe and effective way for operators to

power a variety of general use devices within a hazardous location with a hot permit. The EPP-250-2P-3X-20FT-15A consists of 20` of chemical and abrasion resistant flexible 12/3 SOOW cord that is terminated in a 2-pole 3-wire pin sleeve, 15 amp rated, explosion proof cord cap. A tri-tap receptable allows operators to connect up to three devices.

Hot Work Permit: This line cord is approved for hot work permit applications and allows operators to use their non-explosion proof equipment within an explosion proof environment. The alternative to this line cord is to convert non-explosion proof equipment to explosion proof plugs which can quickly become prohibitively expensive. Having the ability to use non-explosion proof equipment within hazardous areas when a job requires it makes this line cord able to greatly increase the versatility of non-explosion proof equipment. These industrial line cords are popularly used in hazardous locations when hot work permits have been acquired. We also offer class rated extension cords for use within explosion proof and hazardous location environments without hot work permits.

Suggested Applications: This GFCI protected linecord system is ideal for indoor or outdoor use and applications including but not limited to aircraft maintenance, alcohol processing, aerospace, chemical manufacturing, coke processing, cold storage, compressed natural gas (CNG) facilities, cranes, cryogenics, distilleries, food processing, fuel storage, gas processing plants, grain processing, laboratories, liquefied natural gas (LNG) facilities, liquid propane gas (LPG), manufacturing, marine vessels, methane production, mining, offshore, oil drilling rigs, oil refineries, paint spray booths, paper processing, petrochemical, pharmaceuticals, power plants, production refineries, sand blast cabinets, sewage and septic tanks, shipyards, solvent and cleaning areas, storage facilities, tank farms, tankers, textile, washdown areas, waste treatment plants, and woodworking. These industrial extensor cords are popularly used in hazardous locations when hot work permits have been acquired. We also offer class rated extension cords for use within explosion proof and hazardous location environments without hot work permits.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: EPP-250-2P-3X-20FT-15A

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: EPP-250-2P-3X-20FT-15A



Image: EPP-250-2P-3X-20FT-15A

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: EPP-250-2P-3X-20FT-15A

Export Control Classification Number (ECCN): EAR99

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Links (Click on the below items to view):

- **Operations Manual**(https://www.larsonelectronics.com/images/product/Manual/284170.PDF)
- **Wiring Diagram**(https://www.larsonelectronics.com/images/product/WiringDiagram/284170.PDF)
- **HigResPic1**(https://www.larsonelectronics.com/images/product/HigResPic1/284170.JPG)
- **HigResPic2**(https://www.larsonelectronics.com/images/product/HigResPic2/284170.JPG)
- **HigResPic3**(https://www.larsonelectronics.com/images/product/HigResPic3/284170.JPG)
- **HigResPic4**(https://www.larsonelectronics.com/images/product/HigResPic4/284170.JPG)
- **HigResPic5**(https://www.larsonelectronics.com/images/product/HigResPic5/284170.JPG)
- **HigResPic6**(https://www.larsonelectronics.com/images/product/HigResPic6/284170.JPG)
- **HigResPic7**(https://www.larsonelectronics.com/images/product/HigResPic7/284170.JPG)
- **HigResPic8**(https://www.larsonelectronics.com/images/product/HigResPic8/284170.JPG)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)