

MPD-MTS2-EP100A-TL.B-YT0-Z-5.CLR5-M1

100A Camlock Connection Transfer Switch, Manual Service Disconnect Switch, Lug Inputs & Camlock Outputs

Product ID: 284667

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: MPD-MTS2-EP100A-TL.B-YT0-Z-5.CLR5-M1

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MPD-MTS2-EP100A-TL.B-YT0-Z-5.CLR5-M1 Manual Service Disconnect Switch

Line-in Cord: -
Line-in Cord Cap: 100A Terminal Lugs [600V]
Primary Voltage (V): 208V AC Wye
Primary Phase (PH): 3-Phase (3PH)
Primary Frequency (Hz): 60 Hz (60-cycles)
Primary Panel: MTS 208Y/120V 3PH 100A Non-Fused Single-throw N3R
Primary Breakers: N/A
Primary Outlets: 100A Single-pole 15-Series Female Camlocks (1) grn, wht, blk, red, blu [600V]
Primary Protection: Flip Covers
Transformer (KVA): -
Secondary Voltage (V): -
Secondary Phase (PH): -
Secondary Frequency (Hz): -
Secondary Panel: -
Secondary Breakers: -
Secondary Outlets: -
Secondary Protection: -
Operating Temperature: 40°C

Ratings

Max Primary OCP: 100A @ 208V
Max Secondary Output: -
NRTL Listed for UL508A
NEMA 3R Indoor or Outdoor Use
Made in USA

Materials: Steel, Copper

Bus Material: Copper

Ground Bar Material: -

Form Factor: Powder Coated Enclosure N3R

Input Wire Size: -

Dimensions: -

Weight: -

Shipping Weight: -

Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

Special Orders - Special Requirements

Contact us for special requirements

Intl: 1-903-270-1187

Toll Free: 1-800-369-6671

Fax: 1-903-765-7664

E-mail: sales@larsonelectronics.com

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

The Larson Electronics MPD-MTS2-EP100A-TL.B-YT0-Z-5.CLR5-M1 Camlock Connection Transfer Switch is designed for reliable, safe and convenient power distribution at industrial work sites. This 100-amp unit provides three-phase 208V AC Wye power and features one set of 15 series female camlocks. The power distribution panel provides operators the ability to safely tap into and distribute 208V AC Wye power from a variety of sources including generators and direct grid power.

****PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS****

The MPD-MTS2-EP100A-TL.B-YT0-Z-5.CLR5-M1 camlock connection transfer switch provides a safe and reliable way for operators in industrial settings to tap into and utilize power sources independently of the work area. 100-amp, 600V rated terminal lugs are available for input connections on the primary side. The primary side also contains one set of 15 series female camlocks for 208V AC equipment.

Operators bring three-phase 208V AC Wye line-in power to the primary side of the system using 100-amp 600V rated terminal lugs. The primary side of the NEMA 3R non-fused single-throw, 100-amp three-phase 208Y/120V manual transfer switch contains one set of 100-amp 600V rated single-pole 15 series female camlocks (green, white, black, red and blue).

Enclosure Design: This power distribution assembly is housed in a space-saving NEMA 3R enclosure for protection against dust, dirt and moisture in indoor and outdoor locations. Constructed of steel, the unit's slim, rectangular profile is compatible with panel mounting configurations. A lockable opening deters the possibility of tampering. We also offer similar power distribution panels on dolly carts with wheels, powder coated cube frames with lifting eyelets/skid pockets or stand-alone with handles for faster turnarounds and completion of temporary tasks.

Certification: This unit is NRTL listed for UL508A. All equipment is NEMA 3R rated for indoor and outdoor use and provide a degree of protection against dirt, water, and ice. NEMA 4 and NEMA 4X equipment can be equipped upon request.

Grounding: Transformer is grounded to the frame and we provide a grounding lug on the frame for the earth ground.

~Please check all motor loads for dual rated motors that will work 208 or 240.~

Applications: This power distribution system is NEMA 3R rated and ideal for indoor/outdoor



use and applications including but not limited to; construction sites, plant maintenance, plant turnarounds, hazardous location operations, shows, exhibits, and shipyard operations.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.



Frequently Asked Questions (FAQ)

There are no Fags



Image: MPD-MTS2-EP100A-TL.B-YT0-Z-5.CLR5-M1



Image: MPD-MTS2-EP100A-TL.B-YT0-Z-5.CLR5-M1




Image: MPD-MTS2-EP100A-TL.B-YT0-Z-5.CLR5-M1



Image: MPD-MTS2-EP100A-TL.B-YT0-Z-5.CLR5-M1



Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **Single Line Diagram (One-Line Diagram)**(<https://www.larsonelectronics.com/images/product/Online/284667.PDF>)
- **Wiring Diagram**(<https://www.larsonelectronics.com/images/product/WiringDiagram/284667.PDF>)
- **HigResPic1**(<https://www.larsonelectronics.com/images/product/HigResPic1/284667.JPG>)
- **HigResPic2**(<https://www.larsonelectronics.com/images/product/HigResPic2/284667.JPG>)
- **HigResPic3**(<https://www.larsonelectronics.com/images/product/HigResPic3/284667.JPG>)
- **HigResPic4**(<https://www.larsonelectronics.com/images/product/HigResPic4/284667.JPG>)
- **HigResPic5**(<https://www.larsonelectronics.com/images/product/HigResPic5/284667.JPG>)
- **ISO 9001 Certification**(<http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF>)
- **Business Certificate**(<https://www.larsonelectronics.com/images/pdfdocs/w9.PDF>)
- **Shipping Time Map**(<https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf>)