Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MT-DOE16-1P-208V-5KVA-230V-N3R-CU-M1

5 kVA Prewired Distribution Transformer - 208V AC Primary - 230V AC Secondary - NEMA 3R - 1 Phase - Copper Windings - Fused

Product ID: 285935

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-DOE16-1P-208V-5KVA-230V-N3R-CU-M1 Prewired Distribution Transformer
Transformer Type: Distribution
Phase: Single Phase
Frequency: 60 Hz
kVA: 5
Primary Voltage: 208 V
Taps: TBD
Secondary Voltage: 230 V
Winding Material: Copper
Wiring: 3 Meters 16/3 SOOW w/ Cable Gland & Blunt Cut End for Line-In; 2 Meters 16/3 SOOW w/ Cable Gland & 2P3W 16A Connector For Line-Out
Insulation: 220°C
Temperature Rise: 150°C
Impedance (Std): -
Seismic: Yes
Sound Level: Meets NEMA ST-20 Standards
Primary Termination: -
Secondary Termination: -
Enclosure Material: NEMA Type 3R Heavy Duty Ventilated
Finish: ANSI 61 Grey Finish
Dimensions: -
Weight: -
Mounting: Floor or Wall Mount

Ratings
NRTL Listed for United States and Canada
ANN Cooling
IP14 Rated
Distribution Transformer

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

The MT-DOE16-1P-208V-5KVA-230V-N3R-CU-M1 208 V 1 Phase Energy Efficient Prewired Distribution Transformer from Larson Electronics is powerful, reliable, and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-DOE16-1P-208V-5KVA-230V-N3R-CU-M1 fused transformer provides increased reliablity and protection against critical equipment failures. The lower operating costs, lower heat emissions, and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

Transformer Features: With a transformer rating of 5 kVA, the MT-DOE16-1P-208V-5KVA-230V-N3R-CU-M1 distribution transformer is a single phase unit with a primary voltage of 208 V. It also provides a secondary voltage of 230 V. Featuring robust construction, this unit`s cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This prewired and fused unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The Standard NEMA Type 3R enclosure makes the unit suitable for both indoor and outdoor applications and it can be floor or wall mounted. The unit also features 220°C insulation with a 150°C temperature rise and is rated IP14.

Benefits: The MT-DOE16-1P-208V-5KVA-230V-N3R-CU-M1 distribution transformer offers many benefits to the consumer. Precision cut copper transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations.

This distribution transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated mounting brackets make installation fast and easy and the offset outward facing installation holes allow for easy power tool access.

Wiring: The MT-DOE16-1P-208V-5KVA-230V-N3R-CU-M1 is equipped with line-in and line-out wiring. On the input side, there is three meters of 16/3 SOOW cable with cable gland that is terminated in a blunt cut end. On the output side, there is two meters of 16/3 SOOW cable with cable gland that is terminated in a XLE-PA-IP67-309.INTL-1PH-16A-220V-2P3W-C 2P3W 16A connector.

Safety: The MT-DOE16-1P-208V-5KVA-230V-N3R-CU-M1 is a distribution transformer which means that it provides operators with an increased level of protection against electric shock. A distribution transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-DOE16-1P-208V-5KVA-230V-N3R-CU-M1 achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

Applications: General purposes.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MT-DOE16-1P-208V-5KVA-230V-N3R-CU-M1

Product ID: 285935

Harmonized System (HS) Code: 85043300

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **HigResPic1**
- **HigResPic2**
- **HigResPic3**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**