

MT-DOE16-SS-FP-1P-208V-1KVA-240V-N4X-CU

1 kVA Isolation Transformer - 208V Primary - 240V Secondary - NEMA 4X - Stainless Steel - Fully Potted - -

Product ID: 286480

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-DOE16-SS-FP-1P-208V-1KVA-240V-N4X-CU Fully Potted Distribution Transformer Ratings

Transformer Type: Fully Potted / Encapsulated Distribution

Phase: Single Phase

Frequency: 60 Hz

kVA: 1

Primary Voltage: 208 V

Taps: -

Secondary Voltage: 240 V

Winding Material: copper

Efficiency: DOE 2016 / NRCAN 2019 (Also Meets ON Reg. 404/12)

Insulation: 180°C

Temperature Rise: 115°C

Impedance (Std): -

Seismic: Yes

Sound Level: Meets NEMA ST-20 Standards

Primary Termination: -

Secondary Termination: -

Enclosure Material: NEMA Type 4X Heavy Duty Resin Encapsulated - Stainless Steel

Finish: Natural Finish

Dimensions: 11.62"H x 5.50"W x 5.13"D

Weight: 30 lb

Mounting: Wall Mount

NRTL Listed for United States and Canada

ANN Cooling

IP66 Rated

Fully Potted / Encapsulated

Distribution Transformer

NRTL Certified to C22.2 No. 47

NRTL Certified to UL 506

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The MT-DOE16-SS-FP-1P-208V-1KVA-240V-N4X-CU 208 V 1 Phase Energy Efficient Fully Potted Distribution Transformer from Larson Electronics is powerful, reliable and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-DOE16-SS-FP-1P-208V-1KVA-240V-N4X-CU provides increased reliability and protection against critical equipment failures. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

Transformer Features: With a transformer rating of 1 kVA, the MT-DOE16-SS-FP-1P-208V-1KVA-240V-N4X-CU fully potted distribution transformer is a single phase unit with a primary voltage of 208 V. It also provides a secondary voltage of 240 V. Featuring robust construction, this unit's cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology. This unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The Standard NEMA Type 4X stainless steel enclosure makes the unit suitable for both indoor and outdoor applications and it can be wall mounted. The unit also features 180°C insulation with a 115°C temperature rise and is rated IP66.

Benefits: The MT-DOE16-SS-FP-1P-208V-1KVA-240V-N4X-CU fully potted distribution transformer offers many benefits to the consumer. Precision cut copper transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations. This encapsulated distribution transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated mounting brackets make installation fast and easy and the offset outward facing installation holes allow for easy power tool access.

Safety: The MT-DOE16-SS-FP-1P-208V-1KVA-240V-N4X-CU is a distribution transformer which means that it provides operators with an increased level of protection against electric shock. A distribution transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-DOE16-SS-FP-1P-208V-1KVA-240V-N4X-CU achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

Applications: General purposes.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.



Frequently Asked Questions (FAQ)









MT-DOE16-SS-FP-1P-208V-1KVA-240V-N4X-CU

Product ID: 286480

Harmonized System (HS) Code: 85043300

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [HigResPic7](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)