

ATEX-EPsLED-80-SOL-20C-C1D2-WR.GA

Solar Powered Explosion Proof LED Strobe Light - Wireless Remote, 20' Cord - C1D2 Panel - ATEX Zone 1, 21

Product ID: 287946

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

ATEX-EPsLED-80-SOL-20C-C1D2-WR.GA Explosion Proof Solar Powered LED Strobe Lamp

Listing: NRTL Listed for EU and International

Lamp Type: Solar LED

Lamp Dimensions: 15.4"-L x 9.29"-D

Solar Panel Dimensions: 11-3/8"L x 15-3/4"D

Weight: -

Voltage: 12V DC

Battery: (4) 18aH Sealed Lead Acid Batteries

Runtime: -

Charging Time: 5 Hours

Total Watts: 7W

Candela: 1,235

LED Lamp Life Expectancy: 50,000+ Hours

Light Color Options: Red, Green, Blue, Amber or White

Beam Angle: 360°

Lighting Configuration: Strobing Flash

Strobe Count: 4 per Second

Operation: Wireless Remote - Not Rated for Hazardous Location Use

Housing Material: Aluminum Alloy

Lens Material: Temperature-resistant Pressed Glass

Mounting: Wall, Pendant or Trunnion Mount

Wiring: 20' 12/2 SOOW Cord

Ratings/Approvals

IECEX PTB 06.0049X

Ex de IIC T3, T4, T5, T6 1

PTB 03 ATEX 1096 (Zone 1)

Ex II 2 G EEx de IIC T. (Zone 1)

E II 2 D IP66 TO max. (Zone 21)

20' Cord Between Light/Panel

Saltwater Resistant Enclosure

Outdoor Rated and Waterproof Wireless Remote

Wireless Remote is Not Rated for Hazardous Locations

Special Orders - Special Requirements

Contact us for special requirements

Intl: 1-903-270-1187

Toll Free: 1-800-369-6671

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

ATEX-EPSLED-80-SOL-20C-C1D2-WR.GA

Product ID: 287946

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

ATEX-EPSLED-80-SOL-20C-C1D2-WR.GA-Color-Mount

Example: ATEX-EPSLED-80-SOL-20C-C1D2-WR.GA-RED-WLM

Color	
RED	-RED
GREEN	-GRN
BLUE	-BLU
AMBER	-AMB
WHITE	-WHT

Mount	
WALL	-WLM
PENDANT	-PND
TRUNNION	-TRN

Links (Click on the below items to view):

- [HigResPic1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)