

Product ID: 289184

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image:

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

**This unit is Made In USA - Manufactured in Texas**

**MPD-PB-LB-MB-DZ-G-L-6-BF-N4X-Z - Electrical Panel, Lighting Panelboard**

**Item Type:** Deadfront Lighting Panelboard

**Panel Type:** Main Breaker Panel (MCB)

**System Voltage (V):** 240V/120 AC Delta w/ Center Tap

**Phase (PH):** 3-Phase (3PH)

**Frequency (HZ):** 60 Hz (60-cycles)

**System Amperage:** 150A

**Line-In Connection:** (3) Terminal Lugs

**Line-In Orientation:** Bottom Feed

**Mains Capacity:** 150 Amps

**Main Breaker Size:** 150AF

**Main Breaker Type:** Molded Case Circuit Breaker (MCCB)

**Main Breaker Short Circuit Current Rating (SCCR) :** 35 kAIC

**Circuit Count:** (6 Ckt Total - (6) Circuit MCB

**Branch Breakers:** (0) Breakers Included

**Branch Breaker Size:** 35mm Din Rail Mount Breakers; (Not compatible with Ground Fault Indicator Breakers)

**Branch Breaker Type:** Miniature Circuit Breaker (MCB), UL 1077, Not Compatible w/ GFCI Din Rail Breakers

**Branch Breaker Short Circuit Current Rating (SCCR):** 10 kAIC

**Neutral Connection:** Insulated Neutral Bar Kit Included

**Ratings**

**Max Primary OCP:** 150A @ 480V

Made in the USA

NRTL Certified to UL 508A

NRTL Certified to UL 1640

NEMA 3R Rated Indoor/Outdoor Use

**Ground Connection:** Ground Bar Kit Included  
**Line-In Connection:** Breaker Outputs  
**Line-In Orientation:** Bottom, Side Knockouts  
**Feed Thru Capacity:** Not Capable of Feed Thru Line-Outs  
**Mount:** Wall Mounted  
**Enclosure Door:** (1) Left Hinged Door w/ Handle  
**Enclosure Rating:** NEMA 4X  
**Enclosure Material:** CNC formed 304 stainless sheet steel  
**Bus Material:** Tin Plated Copper  
**Finish Color:** Natural Finish  
**Finish Type:** No External Finish  
**Dimensions:** -  
**Weight:** -

Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

**Special Orders - Special Requirements**

Contact us for special requirements

**Intl:** 1-903-270-1187

**Toll Free:** 1-800-369-6671

**Fax:** 1-903-765-7664

**E-mail:** [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com)

\*All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250\*

**This unit is Made In USA - Manufactured in Texas**

**The Larson Electronics MPD-PB-LB-MB-DZ-G-L-6-BF-N4X-Z Power Distribution Main Breaker Lighting Panelboard facilitates electrical and power connections in industrial sites. This unit provides operators the ability to safely tap into and distribute three phase 240V/120 AC power from a variety of sources including generators and direct grid power.**

**Operation:**

- Voltage: 3-Phase 240V/120 AC 3PH Delta w/ Center Tap
- Panel: 150A MB Hinged 6 Circuit Count
- Branch Breaker(s): (0) Breakers Included; Compatible with Larson Electronics Din Rail Mount Breakers. Not compatible with GFCI Style Breakers.
- Enclosure: NEMA 4X for Indoor and Outdoor applications with regular exposure to chemicals, heavy water, or salt water., Bottom Feed

**Panelboard:** The MPD-PB-LB-MB-DZ-G-L-6-BF-N4X-Z power distribution Lighting panelboard unit gives operators the ability to power and protect their MPD-PB-LB-MB-DZ-G-L-6-BF-N4X-Z volt equipment. On the primary side, operators connect three-phase 480Y/277 volt line-in power using a customer-provided cord or line-in conduit. This panelboard distributes power from an electrical feed to various branch circuits. Breaker poles, breaker amperage, circuit count, mains protection, and branch breaker layout can be customized upon request.

**Main Breaker Panel vs Main Lug Only Panel:** Panelboards are available with a main circuit breaker or as main lug only (MLO). A main circuit breaker provides overcurrent protection and serves as the primary unit serving all branch circuits and controls within the panel. This type of panel offers a single disconnection method for connected loads. A MLO panel typically serves as an add-on or sub panel, which is connected to a main breaker panel. A MLO panel does not have overcurrent protection or devices.

**Enclosure:** The MPD-PB-LB-MB-DZ-G-L-6-BF-N4X-Z is constructed from CNC formed 304 stainless sheet steel and has No External Finish coating in Natural Finish finish. This panelboard features a Bottom feed for running input conduit and Side Knockouts. This panelboard is for main panel or sub panel configurations. This panelboard does not provide bus output connections for subpanels. .

\*See specification table at the top of the page for more information about the the panel system.

**Protective Construction:** The power distribution panel is protected from the elements in harsh environments via a 304 stainless steel and weatherproof enclosure with drip shield. Equipped with a gasketed hinged locking door, the panelboard carries a NEMA 4X rating for use in indoor or outdoor locations and protection from water, debris, corrosion, chemicals, and external ice formation. This enclosure provides protection against falling dirt, rain, sleet, snow, windblown dust, splashing water, salt water, chemical wash down, and hose-directed water. The NEMA 4X rated enclosure provides protection from harsh element exposure including ice formation, salt spray, sulfates, and chlorine from interfering with the successful operation of the apparatus or result in wetting of live parts and wiring within the enclosure under specified conditions. This unit is compatible with wall mounting installations.

This power distribution panel can be modified to meet the needs of job-site breaker requirements. Portable units are available upon request and can be equipped with receptacles, carts, skids or trailer mount.

**Certification:** All units are built in accordance to NFPA 70 (National Electric Code), NEMA PB1 and NRTL certified to UL 1640.

**Grounding:** The panel is grounded to the frame and we provide a grounding lug on the frame for the earth ground.

~Please check all motor loads for dual rated motors that will work 208 or 240.~

**Applications:** This power distribution system is ideal for indoor or outdoor use and applications including but not limited to, construction sites, plant maintenance, plant turnarounds, shows, exhibits, and shipyard operations. These power distribution systems are popularly used in applications where external power sources are often necessary. We also offer class rated transformers for use within explosion proof and hazardous location environments.

**Custom Built Systems Available:** Larson Electronics is a manufacturer and we can build portable power distribution systems to your specifications. Although we carry several models of portable power distribution systems in stock, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com) to discuss your specific requirements.



---

## Frequently Asked Questions (FAQ)

There are no Faqs



Image:



**Product ID: 289184**

**Harmonized System (HS) Code: 85371010**

**Export Control Classification Number (ECCN): EAR99**



Links (Click on the below items to view):

- **ASTM Certificate 1** ( <https://www.larsonelectronics.com/images/product/ASTMCert1/289184.PDF> )
- **Canadian CEC Certificate (Commonly referred to as CSA Certificate)** ( <https://www.larsonelectronics.com/images/product/CECCert/289184.PDF> )
- **CE Certificate** ( <https://www.larsonelectronics.com/images/product/CECert/289184.PDF> )
- **Certificate 1, Misc** ( <https://www.larsonelectronics.com/images/product/Cert1/289184.PDF> )
- **FCC Certificate (Federal Communications Commission, USA)** ( <https://www.larsonelectronics.com/images/product/FCCCert/289184.PDF> )
- **MSDS (Material Safety Data Sheet)** ( <https://www.larsonelectronics.com/images/product/Msds/289184.PDF> )
- **RoHS Certificate (Restriction of Hazardous Substances)** ( <https://www.larsonelectronics.com/images/product/RoHSCert/289184.PDF> )
- **USA NEC Certificate (Commonly referred to as UL Certificate)** ( <https://www.larsonelectronics.com/images/product/NECCert/289184.PDF> )
- **HigResPic1** ( <https://www.larsonelectronics.com/images/product/HigResPic1/289184.JPG> )
- **HigResPic2** ( <https://www.larsonelectronics.com/images/product/HigResPic2/289184.JPG> )
- **ISO 9001 Certification** ( <http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF> )
- **Business Certificate** ( <https://www.larsonelectronics.com/images/pdfdocs/w9.PDF> )
- **Shipping Time Map** ( <https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf> )