Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MT-ISX-FP-SS-3P-600D-25KVA-240D.120CT-N4X

25 kVA Isolation Transformer - 600V Delta Primary - 240V/120 Delta Secondary - 50/60Hz - Fully Potted/Encapsulated - Stainless Steel Enclosure

Product ID: 295834

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-ISX-FP-SS-3P-600D-25KVA-240D.120CT-N4X Isolation Transformer
Transformer Type: Isolation Transformer
Phase: Three Phase
Frequency: 50/60 Hz
Primary Voltage: 600 V Delta
kVA: 25 kVA
Secondary Voltage: 240V/120 Delta
Taps: 2 x 2.5% FCAN; 4 x 2.5% FCBN
Winding Material: Aluminum
Knockouts: Side and Rear
Primary Termination: Front Access Copper Tabs or Lead Wires
Secondary Termination: Front Access Copper Tabs or Lead Wires
Cooling: Air / Dry Type
Insulation: 180°C
Temperature Rise: 115°C
Enclosure Rating: NEMA 4X
Encapsulation: Silica Sand, Resin Compounds
Enclosure Material: Stainless Steel
Finish: Stainless Steel
Mounting: Floor Mount
Dimensions: 21.89"H x 15.75"W x 14.13"D
Weight: 385 lbs

Ratings
UL listed for United States
NEMA 3R Indoor/Outdoor Stainless Steel Enclosure
Meets or Exceeds NEMA ST-20 Standards
Isolation Transformer
Fully Potted/Encapsulated
CSA certified for Canada

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

The MT-ISX-FP-SS-3P-600D-25KVA-240D.120CT-N4X 600 V Delta Three

Phase Fully Potted Isolation Transformer from Larson Electronics is powerful, reliable,and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-ISX-FP-SS-3P-600D-25KVA-240D.120CT-N4X provides increased reliability, higher efficiency, protection against critical equipment failures and an extra level of protection by isolating the power source from the connected device. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of applications and businesses. The MT-ISX-FP-SS-3P-600D-25KVA-240D.120CT-N4X features a stainless steel enclosure for corrosion resistance.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

Transformer Features: The MT-ISX-FP-SS-3P-600D-25KVA-240D.120CT-N4X fully potted isolation transformer is a three phase unit with a 25 kVA rating and a primary voltage of 600 V Delta on the primary side. This transformer has a secondary voltage of 240V/120 Delta on the secondary side. Featuring robust construction, this unit`s cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This encapsulated unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The NEMA 4X stainless steel enclosure makes the unit suitable for both indoor and outdoor applications, and this fully potted transformer can be floor mounted. The MT-ISX-FP-SS-3P-600D-25KVA-240D.120CT-N4X features a 180°C insulation with a 115°C temperature rise.

Construction: The aluminum windings in the MT-ISX-FP-SS-3P-600D-25KVA-240D.120CT-N4X are formed from high quality aluminum wire that help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations. Isolation transformers are designed to maximize the performance and life of electrical equipment. The MT-ISX-FP-SS-3P-600D-25KVA-240D.120CT-N4X is encapsulated in silica sand and resin, and cased in a NEMA 3R stainless steel enclosure.

Benefits: The MT-ISX-FP-SS-3P-600D-25KVA-240D.120CT-N4X fully potted isolation transformer offers many benefits to the consumer. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Installation and maintenance costs are reduced due to the smaller form factor, and less overall space requirements are decreased. In addition, these transformers operate quieter than a standard autotransformer of the same capacity.

Mounting: Integrated floor mounting brackets make installation fast and easy.

Applications: Air conditioners, lighting systems, heating elements, motor applications and other applications that that require the ability to power loads that differ from the available line voltage.

Limitations: While there are many benefits to an isolation transformer and there are some limitations to consider. This transformer will only transform voltage, it will not convert phases and does not allow use of the neutral. If any of these limitations apply to you, you will need a standard transformer. Please see below link for our standard line of industrial transformers or our line of phase converters.

Note on Phases: For three phase transformers, click on the following links:
Three Phase Delta Buck/Boost Transformers
Three Phase Wye Buck/Boost Transformers

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)


LARSON
ELECTRONICS
MT-BBT-SS-208V-240V-62.5A
DRY TYPE ISOLATION/BUCK-BOOST TRANSFORMER
Input Voltage: 208
Output Voltage: 240
kVA: 25.0
Cooling: ANC
Temp. Rise: 115°C
Temp. Class: 180°C
Frequency: 50/60Hz
Encl. Type: 3R
1
LARSONELECTRONICS.COM
1-800-369-6671
sales@larsonelectronics.com


LARSON
ELECTRONICS
MT-BBT-SS-208V-240V-62.5A
LARSONELECTRONICS.COM
1-800-369-6671
sales@larsonelectronics.com

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



MT-ISX-FP-SS-3P-600D-25KVA-240D.120CT-N4X

Product ID: 295834

Harmonized System (HS) Code: 85043300

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **HigResPic1**
- **HigResPic2**
- **HigResPic3**
- **HigResPic4**
- **HigResPic5**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**