Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

MPD-CW15-CLP6.1200AB-DT400DE-ZZ-5.CLR6-M1

400 KVA Mobile Power Distribution - 208V Delta to 480V Delta 3-Phase - Camlock Input/Outputs - N4X

Product ID: 295868

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: MPD-CW15-CLP6.1200AB-DT400DE-ZZ-5.CLR6-M1

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

This unit is Made In USA - Manufactured in Texas

MPD-CW15-CLP6.1200AB-DT400DE-ZZ-5.CLR6-M1 Power Distribution

Line-In Cord: -
Line-In Cord Cap: (3 Sets) 400A Single-pole 16-Ser. Male Camlock Receptacles [green, black, red, blue] [600V]
Primary Voltage (V): 208V AC Delta
Primary Phase (PH): 3-Phase (3PH)
Primary Frequency (HZ): 60 Hz (60-cycles)
Primary Panel: N/A
Primary Breaker(s): Not Included - Requires Maximum 1200A Rated MCCB [250V] (**Customer Provided**)
Primary Outlet(s): N/A
Primary Protection: Flip Covers
Transformer (KVA): 400KVA 208V to 480V 3PH N4X
Secondary Voltage (V): 480V AC Delta
Secondary Phase (PH): 3-Phase (3PH)
Secondary Frequency (HZ): 60 Hz (60-cycles)
Secondary Panel: N/A
Secondary Breaker(s): Not Included - Requires Maximum 400A Rated MCCB [480V]

Ratings/Features

Max OCP Primary: 1200A @ 208V

Max OCP Secondary: 400A @ 480V

NEMA 4X Indoor or Outdoor Use
Made in the USA
NRTL Certified to UL 1640

Powder Coat Finish Standards:

Complies with ASTM D-523
Complies with ASTM D-3359
Complies with ASTM D-522
Complies with ASTM D-3363
Complies with ASTM D-2794

(**Customer Provided**)
Secondary Outlets: (1 Set) 400A Single-pole 16-Ser. Female Camlock Receptacles [green, brown, orange, yellow] [600V]
Secondary Protection: Flip Covers
Form Factor: Blue Powder Coated Open Cart w/ Casters
Frame Materials: Steel
Frame Finish: High-Strength TGIC Polyester Powder Coated Blue
Dimensions: (*Please note that dimensions are approximate and subject to change*) 60"-L x 48"-W x 72"-H
Weight: (*Please note that weight is approximate and subject to change*) 3250 lb

Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

Special Orders - Special Requirements
Contact us for special requirements
Intl: 1-903-270-1187
Toll Free: 1-800-369-6671
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

This unit is Made In USA - Manufactured in Texas

The MPD-CW15-CLP6.1200AB-DT400DE-ZZ-5.CLR6-M1 from Larson Electronics is a Mobile Power Distribution converts three-phase 208V AC Delta electrical current into three-phase 480V AC Delta. This unit provides operators the ability to safely tap into and distribute 208V AC power from a variety of sources including generators and direct grid power.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

Operation:

• Primary Voltage: 208V AC Delta 3PH

• Primary Panel: N/A

• Primary Breaker(s): Not Included - Requires Maximum 1200A Rated MCCB [250V] (**Customer Provided**)

• Primary Outlet(s): N/A

• Transformer: 400KVA 208V to 480V 3PH N4X

• Secondary Voltage: 480V AC Delta 3PH

• Secondary Panel: N/A

• Secondary Breaker(s): Not Included - Requires Maximum 400A Rated MCCB [480V] (**Customer Provided**)

• Secondary Outlet(s): (1 Set) 400A Single-pole 16-Ser. Female Camlock Receptacles [green, brown, orange, yellow] [600V]

*See specification table at the top of the page for more information about the power distribution system.

Portable Power Distribution Purpose and Use: The MPD-CW15-CLP6.1200AB-DT400DE-ZZ-5.CLR6-M1 portable power distribution system gives operators the ability to power their three-phase 480 volt equipment from a single system. On the primary side, operators connect three-phase 208V line-in power to three sets of 400A Single-pole 16-Ser. Male [green, black, red, blue] Camlock Receptacles [600V]. On the secondary side, operators are provided access to one set of 400A Single-pole 16-Ser. Female Camlock Receptacles [green, brown, orange, yellow] [600V] for powering 480V equipment. The input and output camlocks are protected by NEMA 3R weatherproof flip covers.

Operation: Three sets of 400A Single-pole 16-Ser. Male [green, black, red, blue] Camlock Receptacles [600V] bring three-phase 208V AC to the primary side of the system and passes power to the transformer. The NEMA 4X 400 KVA transformer converts three-phase 208V AC Delta to three-phase 480V AC Delta, 60 Hz. The secondary side of the transformer contains one set of 400A Single-pole 16-Ser. Female Camlock Receptacles [green, brown, orange, yellow] [600V].

Click Photo to Enlarge



Click Photo to Enlarge



Protective Construction: Unlike many portable power distribution boxes made of plastic and utilizing thin gauge, low grade metals in their construction, this unit is designed for serious use and is ruggedly constructed to withstand demanding conditions and heavy duty industrial applications. The transformer and load assembly is mounted on a carbon steel mounting platform and the load center/distribution assembly is mounted to a square carbon steel tubing frame, resulting in an extremely stable, durable, and well protected power distribution platform.

This model is equipped with forklift skid pockets, locking casters, and a top located lifting eyelet which allows easy lifting with cable or chain hooks. This can be replaced for an additional cost with stainless steel, hot dip galvanized steel, or aluminum depending on the customer's needs. Larger units are available upon request and can be equipped with skids or trailer mounted.

The power distribution unit cannot be pushed by hand. For pulling by cart, a hitch attachment is included with the system. The pivoting hitch tongue has a pintle hitch attachment (not road legal for towing on roads).

Grounding: Transformer is grounded to the frame and we provide a grounding lug on the frame for the earth ground.
~Please check all motor loads for dual rated motors that will work 208 or 240.~

Applications: This power distribution system is ideal for indoor or outdoor use and applications including but not limited to, construction sites, plant maintenance, plant turnarounds, shows, exhibits, and shipyard operations. These power distribution systems are popularly used in applications where external power sources are often necessary. We also

offer class rated transformers for use within explosion proof and hazardous location environments.

Custom Built Systems Available: Larson Electronics is a manufacturer and we can build portable power distribution systems to your specifications. Although we carry several models of portable power distribution systems in stock, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MPD-CW15-CLP6.1200AB-DT400DE-ZZ-5.CLR6-M1

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MPD-CW15-CLP6.1200AB-DT400DE-ZZ-5.CLR6-M1

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MPD-CW15-CLP6.1200AB-DT400DE-ZZ-5.CLR6-M1

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MPD-CW15-CLP6.1200AB-DT400DE-ZZ-5.CLR6-M1

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **ANSI Certificate 1**(https://www.larsonelectronics.com/images/product/ANSICert1/295868.PDF)
- **Canadian CEC Certificate (Commonly referred to as CSA Certificate)**(https://www.larsonelectronics.com/images/product/CECCert/295868.PDF)
- **Catalog Page - Product Series**(https://www.larsonelectronics.com/images/product/CatalogPage/295868.PDF)
- **CE Certificate**(https://www.larsonelectronics.com/images/product/CECert/295868.PDF)
- **Certificate 1, Misc**(https://www.larsonelectronics.com/images/product/Cert1/295868.PDF)
- **Certificate 2, Misc**(https://www.larsonelectronics.com/images/product/Cert2/295868.PDF)
- **Certificate 5, Misc**(https://www.larsonelectronics.com/images/product/Cert5/295868.PDF)
- **MSDS (Material Safety Data Sheet**(https://www.larsonelectronics.com/images/product/Msds/295868.PDF)
- **Operations Manual**(https://www.larsonelectronics.com/images/product/Manual/295868.PDF)
- **RoHS Certificate (Restriction of Hazardous Substances)**(https://www.larsonelectronics.com/images/product/RoHSCert/295868.PDF)
- **Single Line Diagram (One-Line Diagram)**(https://www.larsonelectronics.com/images/product/Oneline/295868.PDF)
- **USA NEC Certificate (Commonly referred to as UL Certificate)**(https://www.larsonelectronics.com/images/product/NECCert/295868.PDF)
- **Wiring Diagram**(https://www.larsonelectronics.com/images/product/WiringDiagram/295868.PDF)
- **HigResPic1**(https://www.larsonelectronics.com/images/product/HigResPic1/295868.JPG)
- **HigResPic2**(https://www.larsonelectronics.com/images/product/HigResPic2/295868.JPG)
- **HigResPic3**(https://www.larsonelectronics.com/images/product/HigResPic3/295868.JPG)
- **HigResPic4**(https://www.larsonelectronics.com/images/product/HigResPic4/295868.JPG)
- **HigResPic5**(https://www.larsonelectronics.com/images/product/HigResPic5/295868.JPG)
- **HigResPic6**(https://www.larsonelectronics.com/images/product/HigResPic6/295868.JPG)
- **HigResPic7**(https://www.larsonelectronics.com/images/product/HigResPic7/295868.JPG)
- **HigResPic8**(https://www.larsonelectronics.com/images/product/HigResPic8/295868.JPG)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)