

MT-HAL-ISX-3P-690D-300KVA-480Y.277-N3R-50HZ

300 KVA Hazardous Location Transformer - 480V Delta Primary - 480Y/277 V Wye-N Secondary

Product ID: 301223

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-HAL-ISX-3P-690D-300KVA-480Y.277-N3R-50HZ Isolation Transformer

Phase: Three Phase
Frequency: 50/60 Hz
kVA: 300
Primary Voltage: 690 V Delta
Primary Connection: Delta
Primary FCAN: 2 x 2.5%
Primary FCBN: 2 x 2.5%
Secondary Voltage: 480Y/277 V Wye-N
Secondary Connection: Wye-N
Winding Material: Copper
Efficiency: No Efficiency Specification
Insulation: 180°C
Temperature Rise: 115°C
Temperature Class: T3A
Ambient Temp Rating: 40°C
Secondary Phase Angle: 0°C
Impedance (Std): -
Seismic Zone: -
Sound Level: 55 dBA (ST-20)
Primary Termination: Mounting Pads
Secondary Termination: Mounting Pads
Enclosure Material: NEMA Type 3R Heavy Duty Ventilated
Finish: ANSI 61 Grey
Dimensions: -

Ratings

NRTL Listed for United States and Canada
ANC Cooling
IP24 Rated
Class I, Zone 2, Group IIC, T3
Class I, Division 2, Groups A, B, C, D
Isolation Transformer

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Weight : -

Intl: 1-903-270-1187

Mounting: Floor

E-mail: sales@larsonelectronics.com

The MT-HAL-ISX-3P-690D-300KVA-480Y.277-N3R-50HZ 690 V Delta 3 Phase Energy Efficient Hazardous Location Isolation Transformer from Larson Electronics is powerful, reliable and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-HAL-ISX-3P-690D-300KVA-480Y.277-N3R-50HZ provides increased reliability and protection against critical equipment failures. The lower operating costs, lower heat emissions and lower cost of ownership make this transformer ideal for a wide range of applications and businesses. The MT-HAL-ISX-3P-690D-300KVA-480Y.277-N3R-50HZ is rated for use in Class I, Division 2, Groups A, B, C, D and Class I, Zone 2, Group IIC, T3 hazardous areas.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

Transformer Features: With a transformer rating of 300 KVA, the MT-HAL-ISX-3P-690D-300KVA-480Y.277-N3R-50HZ isolation transformer is a three phase unit with a primary voltage of 690 V Delta. It also provides a secondary voltage of 480Y/277 V Wye-N. Featuring robust construction, this unit's cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The Standard NEMA Type 3R enclosure makes the unit suitable for both indoor and outdoor applications and it can be floor mounted. The unit also features 180°C insulation with a 115°C temperature rise and is rated IP24.

Benefits: The MT-HAL-ISX-3P-690D-300KVA-480Y.277-N3R-50HZ hazardous location isolation transformer offers many benefits to the consumer. Precision cut copper transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations. This isolation transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated floor and wall mounting brackets make installation fast and easy and the offset outward facing floor installation holes allow for easy power tool access.

Safety: The MT-HAL-ISX-3P-690D-300KVA-480Y.277-N3R-50HZ is an isolation transformer which means that it provides operators with an increased level of protection against electric shock. An isolation transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-HAL-ISX-3P-690D-300KVA-480Y.277-N3R-50HZ achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

Applications: General purposes.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Frequently Asked Questions (FAQ)



MT-HAL-ISX-3P-690D-300KVA-480Y.277-N3R-50HZ

Product ID: 301223

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [HigResPic1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)