

**MT-PSTH-R7-3P-DNC-750KVA-YT-HS-LT-A6-AM-CZ-Z-M1**

**750 KVA Hermetically Sealed Substation - 7200V Delta Primary, 208Y/120 Secondary - ONAN, Grey**

**Product ID: 302283**

**Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).**



**Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.**

**MT-PSTH-R7-3P-DNC-750KVA-YT-HS-LT-A6-AM-CZ-Z-M1 Hermetically Sealed Transformer**

**Transformer Type: Substation Power Transformer, Hermetically Sealed**

**Transformer Configuration: Liquid Filled Pad Mounted**

**Transformer Feed Type: Radial Feed**

**Operation: Approved for Step-Up and Step-Down Operations**

**Phase: Three Phase**

**Capacity: 750 KVA**

**Vector Group: DYN11**

**Primary Voltage: 7200V**

**Primary Voltage Switch: N/A**

**Primary Voltage Class: 15 kV Class**

**Primary Phasor: Delta**

**Primary BIL: 95 kV**

**Secondary Voltage: 208Y/120**

**Secondary Voltage Class: 1.2 kV Class**

**Secondary Phasor: Wye-N**

**Secondary BIL: 30 kV**

**Frequency: 60 Hz**

**Temperature Rise: 55°C**

**Insulation Rating: Class E Insulation - 120°C, 248°F**

**Cooling Class: ONAN; Self-Cooled**

**Forced Air (Fans): None**

**Tap Changer: 5-Position Off-Load Tap Changer**

**Tap Qty: (2) FCAN Above Taps, (2) FCBN Below Taps**

**Tap %: 2.5% Taps**

**Ratings**

Meets/Exceeds DOE 2016 Efficiency Ratings

Meets/Exceeds CSA Efficiency Ratings

Complies with ANSI / IEEE C57.12.00

Complies with ANSI / IEEE C57 12.28

Complies with ANSI / IEEE C57 12.29

Complies with ANSI / IEEE C57 12.34

Complies with ANSI / IEEE C57 12.35

Complies with ANSI / IEEE C57.12.70

Complies with ANSI / IEEE C57.12.110

Complies with ANSI / IEEE C57.12.131

Complies with ANSI / IEEE C62.11

Complies with ANSI / IEEE C62.22

Complies with ANSI / IEEE 386

Complies with ANSI / IEEE C2

Complies with ANSI / IEEE C37.47

Complies with ANSI Z535.4

Complies with ASTM D3487

Complies with ASTM D6871

Complies with NEMA 260-1996

Complies with 10 CFR Part 431

Complies with CSA C2.1-06

Complies with CSA C50

Complies with CSA C88

Complies with CSA C88.1

Tap Changer Switch Rating: 15 kV, On-Load Rated  
Tap Changer Switch Location: High Voltage (HV) [Left Side]  
Impedance (Typical): 1.2% - 6.0%  
Primary Connection Type: Live Front  
Primary Termination Arrangement: Top Mounted Terminals  
Primary Termination: Porcelain Bushings  
Primary Connection Qty: (3) Primary Connections  
Primary Bushing Rating: 15 kV Class, 95 kV BIL  
Primary Neutral Connection: N/A  
Primary Surge Arrestors: N/A  
Primary Surge Arrestor Voltage Rating: N/A  
Primary Surge Arrestor MCOV Rating: N/A  
Primary Over Current Protection (OCP): N/A  
Primary Over Current Protection Method: N/A  
Primary Over Current Protection Holder: N/A  
Primary Grounding Provisions: N/A  
Secondary Connection Type: Live Front  
Secondary Termination Arrangement: Top Mounted Porcelain Bushings  
Secondary Connections: (4) Externally Clamped One-Piece Epoxy Bushings Copper Threaded Studs w/ NEMA Spade Terminals  
Secondary Connection Qty: (4)  
Secondary Connection Supports: N/A  
Secondary Over Current Protection (OCP): N/A  
Secondary Neutral Connection: N/A  
Secondary Grounding Provisions: (1) NEMA Ground Bar Attached to Tank via (2) Welded Ground Bungs  
Metering Current Transformer (CT): N/A  
Metering Panel: N/A  
Auxiliary Control Panel : N/A  
Load Break Switch: N/A  
Load Break Switch Qty: N/A  
Load Break Switch Rating: N/A  
Load Break Switch Location: N/A  
Efficiency Standard(s): Meets ANSI/IEEE Standards  
K-Factor Rating (Harmonic Mitigation): K-1 (Standard)  
Pulse Drive Rating: Appropriate For Use With 6-Pulse Drive Equipment On Secondary Side  
Insulation Fluid: Mineral Oil  
Fluid (Oil) Capacity\*: TBD  
Fluid (Oil) Weight\*: TBD  
Oil Level Indicator: Analog Dial Gauge  
Oil Temperature Indicator: Analog Dial Gauge  
Pressure/Vacuum Indicator: Analog Dial Gauge  
Pressure Relief Device: Included, Automatic Action  
Fault Indicator: N/A  
Gas Sampler Valve: N/A  
Fill Valve: N/A  
Fill Valve Location: N/A  
Oil Drain Valve: 1" NPT Port w/ 5/8" NPT Sampler Valve  
Drain Valve Location: Front Compartment  
Winding Material: Copper  
Ambient Temperature Rating: 40°C  
Ambient Operating Temperature Range: -40°C to +40°C (-50°F to +104°F)  
Sound Level: 67 dBA  
Elevation (Altitude): 3300ft (1000 meters) Above Sea Level  
Core Material: Grain Oriented Steel  
Tank Material: Coated Steel  
Cabinet Material: Coated Steel  
Base Platform Material: Coated Steel  
Portability: Lifting Lugs, Provisions for Jacking Under Base, w/ Base Construction Suitable for Using Rollers or Skidding  
Housing Type: Metal Casing Liquid Filled Transformer  
Enclosure Rating: NEMA 3R Weatherproof Wiring Cabinet, Sealed Tank  
Seismic Rating: Yes  
Paint Type: Weatherproof and UV Resistant Epoxy Coating and Undercoating  
Finish Color: ANSI 61 Grey  
Mounting: Skid Type Base w/ Lifting Lugs  
Conduit Opening: N/A  
Tank Cover Access Handhole: N/A

Complies with CSA C88-16  
Complies with CSA C227.4 & C227.5  
Complies with CSA C802.1  
Complies with CSA C802-3

#### **Features**

Hot Stick Included, HV Door Mount  
Pentahead Bolt Entry Assembly  
High-Fire Point Insulating Fluid  
Non-PCB Insulating Fluid  
Tamper Proof Housing  
Hinged Front Compartment Doors, Pad Lockable  
NEMA 3R Wiring Compartment

#### **Efficiency %: 98.00%**

*Based on transformer operating at 50% of nameplate base kVA.*

#### **Load Losses Based on 85°C Reference Temp.**

No Load Loss (in watts): TBD

Full Load Loss (in watts) at 100%: TBD

Total Load Loss (in watts) at 100%: TBD

#### **Total Losses at 55°C LL Temp. & 20°C NL Temp.**

Total Load Loss (in watts) at 50%: TBD

***Note: Losses offered are typical only, not guaranteed***

#### **Labeling:**

Externally Stencilled (Painted) KVA Rating  
Externally Stencilled (Painted) Voltage Rating  
External Non-PCB Label  
External Warning & Danger Label  
External Barcode Label  
Internal Busing & Accessory Labeling  
Stainless Steel Riveted Nameplate

#### **Factory Tests:**

Winding Resistance Test  
Insulation Resistance Test  
Voltage Ratio Error Test  
Short-circuit Impedance Test  
No-load Loss (Wattage) Test  
Load Loss (Wattage) Test  
Induced Voltage Withstand Test  
Separate Source Voltage Withstand Test  
Pressure Integrity Test Test

#### **Shipping:**

Shipped on pallet on open flatbed  
Palletized on Wooden Pallet w/ Skid Pockets  
Pallet Skid Facing Outward Sides of Truck  
***Note: Crated shipping in lieu of palletizing can be done upon request for an additional fee***

#### **Special Orders - Special Requirements**

Contact us for special requirements

Dimensions\*: 57.08"-H x 57.08"-W x 37.40"-D

Dry Weight (w/o Oil)\*: 2211 lb

Total Weight (Liquid Filled)\*: 3417 lb

\*Please note that numbers are approximate and subject to change

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com)

**The MT-PSTH-R7-3P-DNC-750KVA-YT-HS-LT-A6-AM-CZ-Z-M1 Hermetically Sealed Transformer from Larson Electronics offers powerful, reliable, and efficient power distribution in indoor or outdoor locations. The low operating costs, low heat emissions, and low cost of ownership makes this transformer ideal for a wide range of applications and businesses. This air tight transformer does not have doors and must be installed in a contained or protected area away from public access.**

***\*PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS\****

**Transformer Features:** The industrial transformer features a primary voltage of three-phase 7200V Delta and a secondary voltage of three-phase 208Y/120 Wye-N. This system carries the following ratings: 750 KVA. The unit has a primary radial feed and live front primary connections. We also offer systems with loop feed and dead front primary connections. This transformer features a 5-position tap changer with two, +/- 2.5% taps above and two, +/- 2.5% taps below to allow small changes for voltage. There are no load break switches, rapid rise relays, or protection fuses present on the system.

The system features aluminum windings for high strength and thermal/electrical conductivity. This transformer consists of rectangular coil and five-legged wound core design with three coils and four core loops (this is for three-phase transformers only; single-phase units have one coil and two core loops).

The MT-PSTH-R7-3P-DNC-750KVA-YT-HS-LT-A6-AM-CZ-Z-M1 is completely sealed and features air tight construction. Designed for long-term performance, the transformer is maintenance free.

**Temperature Rise:** This unit features a 55°C ambient temperature rating and a 55°C temperature rise for reduced heat waste, increased reliability, and longer life. At 55°C temperature rise, the transformer offers 750 KVA. The transformer meets standard efficiency requirements. The combination of low temperature rise and high efficiency makes this unit suitable for use in electrical rooms, air conditioned spaces in buildings, underground vaults and similar locations, in addition to outdoor areas.

**Insulation Fluid:** The MT-PSTH-R7-3P-DNC-750KVA-YT-HS-LT-A6-AM-CZ-Z-M1 features mineral oil (ONAN).

**Gauges:** The following gauges are included with the system: oil level indicator, oil thermometer, and pressure/vacuum gauge. Standard oil level indicator, oil thermometer, and pressure/vacuum gauges are analog, manual reading types. These gauges do not have alarm contacts.

**Fault Pressure Devices:** There are no fault pressure devices on the unit. Fault pressure devices are used to detect high rates of pressure rise within the tank.

**Rapid Rise Relay:** There are no rapid rise relays on the unit. This safety component is designed for protection when a rapid increase in tank pressure occurs. The relay is suitable for detecting sudden pressure fluctuations above predetermined safe limits.

**Surge arresters:** This system comes with surge arresters on the primary and secondary side. Designed for over-voltage and transient voltage protection, the components prevent damage caused by lightning, internal switching or voltage surges. We can offer models without high elbow surge arresters that have mounting provisions for customer-provided surge arresters.

**Load Breaker Switch:** The transformer is not equipped with a load breaker switch.

**Valves:** The MT-PSTH-R7-3P-DNC-750KVA-YT-HS-LT-A6-AM-CZ-Z-M1 is equipped with an oil drain valve, an oil sampling valve, and a pressure relief valve.

**Protection Fuses:** This transformer does not have bayonet protection fuses on the primary side. For units without protection fuses, up stream protection is provided. We recommend provisions for protection fuses when possible, as blown

fuses may require more frequent oil changes.

**Terminal Connections:** The primary and secondary terminal connections are located on the top of the transformer. We can configure the location to be top located or side located for both the high voltage and low voltage sides.

**Mount:** This hermetically sealed transformer is equipped with a skid type base with lifting lugs.

**Benefits:** The MT-PSTH-R7-3P-DNC-750KVA-YT-HS-LT-A6-AM-CZ-Z-M1 transformer offers many benefits to consumers. This transformer provides owners with significant energy savings, as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turns into cost savings for owners in the form of lower energy bills and decreased cost of ownership.

**Applications:** General purposes, industrial sites, electrical rooms, underground vaults, manufacturing facilities, steel plants, offshore, commercial, military, processing plants, electric power distribution, utilities, and more.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com) to discuss your specific requirements.

---

## Frequently Asked Questions (FAQ)

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [HigResPic1](#)
- [Video1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)