Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

MT-ISX-FP-1P-120V-750VA-12.13.14.15V-N4X

750 VA Isolation Transformer - 120V Primary - 12/13/14/15V AC Secondary - 50/60Hz - Fully Potted/Encapsulated - Stainless Steel - NEMA 4X

Product ID: 305686

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: MT-ISX-FP-1P-120V-750VA-12.13.14.15V-N4X

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-ISX-FP-1P-120V-600VA-12.13.14.15V-N4X Isolation Transformer

Transformer Type: Isolation Transformer
Transformer Configuration: Buck
Phase: Single Phase
Frequency: 50/60 Hz
Primary Voltage: 120 V AC
kVA:750 VA (0.75 kVA)
Secondary Voltage: 12V, 13V, 14V, 15V AC
Secondary Overload Protection: 25 Amp Magnetic Circuit Breaker
Secondary Terminal Blocks: 125 Amp Rated, Extra Large
Winding Material: Aluminum
Knockouts: Side and Rear
Switch: Hi-Low Switch
Primary Wiring: 6' Heavy-Duty #16/3 Awg Power Cord w/ 3-Prong Grounded Wall Plug
Cooling: Air / Dry Type
Insulation: 130°C
Temperature Rise: 80°C
Temp Rating: 30°C
Enclosure Rating: NEMA 4X
Encapsulation: Silica Sand, Resin Compounds
Enclosure Material: Stainless Steel

Ratings

NRTL Listed for United States
CSA Certified for Canada
NEMA 4X Indoor/Outdoor Enclosure
Meets or Exceeds NEMA ST-20 Standards
Isolation Transformer
Fully Potted/Encapsulated

Special Orders - Special Requirements

Finish: Natural
Mounting: Wall Mount via Mounting Tabs
Dimensions: (*Please note that dimensions are approximate and subject to change*) 7.19"-H x 4.31"-W x 5.56"-D
Weight: (*Please note that weight is approximate and subject to change*) 11 lb

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

The MT-ISX-FP-1P-120V-200VA-12.13.14.15V-N4X from Larson Electronics is a Single Phase Isolation Transformer that is powerful, reliable, and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-ISX-FP-1P-120V-200VA-12.13.14.15V-N4X provides increased reliability, higher efficiency, protection against critical equipment failures and an extra level of protection by isolating the power source from the connected device. The lower operating costs, lower heat emissions, and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

Transformer Features: The MT-ISX-FP-1P-120V-200VA-12.13.14.15V-N4X isolation transformer is a single phase unit with a 600 VA (0.60 kVA) rating and a primary voltage of 120 V AC on the primary side. This transformer has secondary voltages of 12V, 13V, 14V, and 15V AC on the secondary side. Featuring robust construction, this unit's cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This unit's primary and secondary windings are separated, allowing operators to connect the primary and secondary components to form an autotransformer. When the primary and secondary windings are connected, the unit is no longer an isolated transformer and becomes a buck-boost transformer (autotransformer).

This unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The NEMA 4X stainless steel enclosure makes the unit suitable for both indoor and outdoor applications, and this step-down transformer can be either floor or wall mounted. The MT-ISX-FP-1P-120V-200VA-12.13.14.15V-N4X features a 130°C insulation with a 80°C temperature rise.

Construction: The aluminum winding in the MT-ISX-FP-1P-120V-200VA-12.13.14.15V-N4X are formed from high quality aluminum wire help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations. Isolation transformers are designed to maximize the performance and life of electrical equipment. The MT-ISX-FP-1P-120V-200VA-12.13.14.15V-N4X is encapsulated in silica sand and resin, and cased in a NEMA 4X stainless steel enclosure. NEMA 3R, NEMA 4, and NEMA 12 enclosures are available upon request.

Benefits: The MT-ISX-FP-1P-120V-200VA-12.13.14.15V-N4X isolation transformer offers many benefits to the consumer. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Installation and maintenance costs are reduced due to the smaller form factor, and less overall space requirements are decreased. In addition, these transformers operate quieter than a standard autotransformer of the same capacity.

Wiring: The MT-ISX-FP-1P-120V-200VA-12.13.14.15V-N4X is equipped with a 6' heavy-duty #16/3 AWG power cord with 3-prong grounded wall plug.

Mounting: Integrated wall mounting brackets make installation fast and easy. Because of the smaller overall footprint, heavy machinery is rarely needed for mounting and installation.

Applications: Air conditioners, lighting systems, heating elements, motor applications and other applications that that require the ability to power loads that differ from the available line voltage.

Limitations: While there are many benefits to an isolation transformer and there are some limitations to consider. This transformer will only transform voltage, it will not convert phases and does not allow use of the neutral. If any of these limitations apply to you, you will need a standard transformer. Please see below link for our standard line of industrial transformers or our line of phase converters.

Note on Phases: For three phase transformers, click on the following links:
Three Phase Delta Buck/Boost Transformers
Three Phase Wye Buck/Boost Transformers

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MT-ISX-FP-1P-120V-750VA-12.13.14.15V-N4X

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **Operations Manual**(https://www.larsonelectronics.com/images/product/Manual/305686.PDF)
- **HigResPic1**(https://www.larsonelectronics.com/images/product/HigResPic1/305686.JPG)
- **HigResPic2**(https://www.larsonelectronics.com/images/product/HigResPic2/305686.JPG)
- **HigResPic3**(https://www.larsonelectronics.com/images/product/HigResPic3/305686.JPG)
- **HigResPic4**(https://www.larsonelectronics.com/images/product/HigResPic4/305686.JPG)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)