Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MPD-CM1-NTL.20AB-SE5SW-CZ-2.L05-8.N10-M1

5 KVA Mini Portable Power Distro, 480V-120V 1PH, L22-20P Inlet, (2) L5-30R & (8) 5-20R Outlets - N3R

Product ID: 306609

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

This unit is Made In USA - Manufactured in Texas

MPD-CM1-NTL.20AB-SE5SW-CZ-2.L05-8.N10-M1 - Portable Spider Box

Line-in Cord: 20' #12 3/C AWG TYPE SOOW Cord [600V]
Line-in Cord Cap: L22-20P NEMA Twist Lock Plug [480Y/277V]
Primary Voltage (V): 480V AC
Primary Phase (PH): 1-Phase (1PH)
Primary Frequency (HZ): 60 Hz (60-cycles)
Primary Panel: N/A
Primary Breaker(s): (1) 20A 2P MCCB [480V]
Primary Outlet(s): N/A
Primary Protection: MCCB Circuit Breaker
Transformer (KVA): 5 KVA 480V to 120V 1PH N3R
Secondary Voltage (V): 120V AC
Secondary Phase (PH): 1-Phase (1PH)
Secondary Frequency (HZ): 60 Hz (60-cycles)
Secondary Panel: N/A
Secondary Breaker(s): (2) 30A 1P MCB [125]; (8) 20A 1P MCB [125]
Secondary Outlet(s): (2) L5-30R 30A Twist Lock Receptacle [125V]; (8) 5-20R NEMA GFCI DPLX [125]
Secondary Protection: MCB Circuit Breakers; GFCI's
Form Factor: Blue Powder Coated Portable w/ Base Stand
Frame Finish: High- strength TGIC Polyester Powder Coated Blue
Dimensions: -
Weight: -

Ratings

Max Primary OCP: 20A @ 480V
Max Secondary Output: 41.67A @ 120V
NEMA 3R Indoor or Outdoor Use
Made in the USA
NRTL Certified to UL 1640

Powder Coat Finish Standards:

Complies with ASTM D-523
Complies with ASTM D-3359
Complies with ASTM D-522
Complies with ASTM D-3363
Complies with ASTM D-2794

Special Orders - Special Requirements

Contact us for special requirements

Intl: 1-903-270-1187
Toll Free: 1-800-369-6671
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

This unit is Made In USA - Manufactured in Texas

The MPD-CM1-NTL.20AB-SE5SW-CZ-2.L05-8.N10-M1 Larson Electronics from is a Portable Power Distribution System that converts single-phase 480V AC input voltage and steps it down to single-phase 120V AC output voltage. All system components are protected by a powder coated steel enclosure with a top located handle for mobility.

The MPD-CM1-NTL.20AB-SE5SW-CZ-2.L05-8.N10-M1 portable wheeled spider box from Larson Electronics is built to provide operators with a reliable source of 120V power. This spider box is designed for portability and convenience as well as durability. Featuring an elevated base platform for protection from standing water and weatherproof construction, the MPD-CM1-NTL.20AB-SE5SW-CZ-2.L05-8.N10-M1 is ideal for powering 120V equipment and lighting in construction, entertainment, job-site, marine and outdoor locations where generators are providing the power.

Operation:

- Primary Voltage: 480V AC 1PH
- Primary Panel: N/A
- Primary Breaker(s): (1) 20A 2P MCCB [480V]
- Primary Outlet(s): N/A
- Transformer: 5 KVA 480V to 120V 1PH N3R
- Secondary Voltage: 120V AC 1PH
- Secondary Panel: N/A
- Secondary Breaker(s): (2) 30A 1P MCB [125]; (8) 20A 1P MCB [125]
- Secondary Outlet(s): (2) L5-30R 30A Twist Lock Receptacle [125V]; (8) 5-20R NEMA GFCI DPLX [125]

*See specification table at the top of the page for more information about the power distribution system.

This portable spider box features two L5-30R NEMA twist-lock outlets and eight 5-20R NEMA duplex outlets that provide sealed and secure connections for eighteen device. The receptacle provides 120V for powering high voltage lighting and equipment without the need for running additional extension cords. The MPD-CM1-NTL.20AB-SE5SW-CZ-2.L05-8.N10-M1 power distribution unit features short circuit and overload protection. In the instance of circuit overload, the unit automatically shuts down to protect the unit from damage and operators manually restart the system.

A 20-amp L22-20P 480Y/277V NEMA twist-lock inlet brings single-phase 480V AC power to the primary side of the system and passes power to the transformer. The NEMA 3R 5 KVA transformer converts single-phase 480V AC to single-phase 120V AC and passes the current to the secondary side of the system. The secondary side contains two 30-amp 1-pole 125V miniature circuit breaker protecting two 30-amp L5-30R NEMA twist-lock outlets and eight 20-amp 1-pole 125 volt miniature circuit breakers protecting eight 20-amp 5-20R NEMA duplex outlets.

Protective Construction: The housing on the MPD-CM1-NTL.20AB-SE5SW-CZ-2.L05-8.N10-M1 is constructed from powder coated steel with a NEMA 3R enclosure rating. The angled base and low center of gravity ensure this low voltage transformer does not tip over when in the field. The entire unit is powder coated with glossy blue finish for corrosion resistance and aesthetics. A top located adjustable push handle allows operators to guide this unit through the workspace.

The power distribution system is constructed of steel with a polyester powder coated blue finish for durability against dirt, moisture, and mild corrosion. This special coating creates a high-strength barrier for protection from accidental bumps and scratches. The TGIC polyester powder coat finish offers reliable resistance against chemicals, UV light (sun light) and degrading elements in outdoor locations. Our powder coating solution ensures robust color retention for many years without fading. Custom colors, such as black, grey, desert tan, or

forest green, and galvanized finishes are available upon request. Non-standard powder coat colors or galvanized finishes may increase price and lead times.
This temporary power distribution solution can be modified to meet the needs of job-site receptacle requirements. Larger units are available upon request and can be equipped with skids or trailer mount.
Certification: All units are built in accordance to NFPA 70 (National Electric Code) and NRTL certified to UL 1640. All equipment is NEMA 3R rated for indoor and outdoor use and provide a degree of protection against dirt, water, and ice. NEMA 4 and NEMA 4X equipment can be equipped upon request.
Grounding: Transformer is grounded to the frame and we provide a grounding lug on the frame for the earth ground.
~Please check all motor loads for dual rated motors that will work 208 or 240.~
Applications: This power distribution system is ideal for indoor or outdoor use and applications including but not limited to, construction sites, plant maintenance, plant turnarounds, shows, exhibits, and shipyard operations. These power distribution systems are popularly used in applications where external power sources are often necessary. We also offer class rated transformers for use within explosion proof and hazardous location environments.
Custom Built Systems Available: Larson Electronics is a manufacturer and we can build portable power distribution systems to your specifications. Although we carry several models of portable power distribution systems in stock, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364









Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- ANSI Certificate 1
- Canadian CEC Certificate (Commonly referred to as CSA Certificate)
- Catalog Page - Product Series
- CE Certificate
- Certificate 1, Misc
- Certificate 2, Misc
- Certificate 5, Misc
- MSDS (Material Safety Data Sheet
- RoHS Certificate (Restriction of Hazardous Substances)
- Single Line Diagram (One-Line Diagram)
- USA NEC Certificate (Commonly referred to as UL Certificate)
- Wiring Diagram (Oneline)
- HigResPic1
- HigResPic2
- HigResPic3
- HigResPic4
- HigResPic5
- HigResPic6
- HigResPic7
- HigResPic8
- HigResPic9
- HigResPic10
- ISO 9001 Certification
- Business Certificate
- Shipping Time Map