Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MT-PMUT-R7-1P-GMP-250KVA-SLR-HT-LT-Z6-AFP-CC-1C3-M1

250 KVA Submersible Distribution Transformer, Vault Mount, 13800Y/7970 Grounded Wye Primary, 277/480V Secondary, Copper, 316L S.S, KNAN/FR-3, Light Grey

Product ID: 307012

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-PMUT-R7-1P-GMP-250KVA-SLR-HT-LT-Z6-AFP-CC-1C3-M1 Submersible Vault Distribution Transformer

Transformer Type: Submersible Vault Distribution Transformer
Transformer Configuration: Underground Vault Installation, Suitable for Temporary Submersion
Transformer Polarity Type: Subtractive
Phase: Single Phase
Capacity: 250 KVA
Duty: Continuous
Primary Voltage: 13800Y/7970
Primary Voltage Switch: N/A
Primary Voltage Class: 15 kV Class
Primary Phasor: Grounded Wye
Primary BIL: 95 kV
Secondary Voltage: 277/480V (L-N-L)
Secondary Voltage Class: 1.2 kV Class
Secondary Phasor: Single Phase, Dual Windings
Secondary BIL: 30 KV
Angular Phase Displacement: 0 degrees
Overload Capabilities: In accordance with ANSI/IEEE C57.91
Short Circuit Capability: In accordance with ANSI Standard C57.12.00
Frequency: 60 Hz
Temperature Rise: 55°C
Insulation Rating: Class E Insulation - 120°C, 248°F
Forced Air (Fans): None

Ratings

Meets/Exceeds DOE 2016 Efficiency Ratings
Complies with ANSI / IEEE #C57.12.00
Complies with ANSI / IEEE #C57.12.23
Complies with ANSI / IEEE #C57.12.31
Complies with ANSI / IEEE #C57.12.32
Complies with ANSI / IEEE C57.12.70
Complies with ANSI / IEEE C57.12.80
Complies with ANSI / IEEE C57.12.90
Complies with ANSI / IEEE C57.19.00
Complies with ANSI / IEEE C57.19.01
Complies with ANSI / IEEE C57.91.00
Complies with ANSI / IEEE C57.105
Complies with ANSI / IEEE 386
Complies with Code of Federal Regulations, Title 10 Chapter II DOE – Part 431 Subpart K
Complies with ASTM D3487
Non-PCB Insulating Fluid
Lifting Lugs Included

Mounting Provision For Fans: Included
Cooling Radiators: Included
Cooling Class: KNAN; Self-Cooled
Tap Changer: N/A
Tap Qty: N/A
Tap %: N/A
Tap Changer Switch Location: N/A
Impedance: 2.0-6.0% Typical

Primary Connection Type: Load Break Bushing

Primary Bushing Rating: H1A and H1B bushings include 200 A, 15 kV bushing wells and inserts for use with load-break elbow connectors with up to 4/0 AWG copper conductor cables rated 200 A loop feed
Primary Termination: Externally Clamped Well Bushings w/ Removable Studs, 200A Load Break Elbows w/ Inserts
Primary Connection Qty: (2) Primary Connections for Use w/ Elbow Connectors
Primary Neutral Connection: Primary H2 Neutral Internally Bonded to Tank
Primary Parking Stand Qty: (1) Per Each Phase, Welded Brackets for Installing Accessory Parking Stand Bushings
Primary Surge Arrestors: N/A
Primary Surge Arrestor Voltage Rating: N/A
Primary Surge Arrestor MCOV Rating: N/A
Primary Over Current Protection (OCP): Bayonet Expulsion Fuse in series w/ Partial-Range Current-Limiting Fuse, MFR: Cooper Industries, Provided (2) spare fuses
Primary Over Current Protection Method: Fused, Oil-Immersed, Draw-out, De-energized, hot stick operated
Primary Over Current Protection Holder: Bayonet Fuse Holder w/ External Drip Shield
Primary Over Current Protection Rating: 7.97 kV, 65 A
Secondary Connection Type: Live Bushing Lug
Secondary Connection Arrangement: Secondary Cable leads are arranged for vertical takeoff and extend 14 inches above the top of the cover. Two cables are utilized per terminal
Secondary Connections: Accommodate either aluminum or copper conductors
Secondary Connection Qty: (3)
Secondary Neutral Connection: Secondary X2 Neutral Grounded to Tank via 1/2"-13 UNC Tapped Hole, 7/16" Deep Bung & Copper Ground Strap
Bushing Wells: Included, Two Each, 200 A rms, 10 kA Short Time Rating, Elastimold, Cooper Industries
Grounding Provisions: (1) Lug w/ Grounding Strap, Tank Grounding Lug
Load Break Switch: 2-Position Load Break Switch, oil immersed loop-feed/load-break sectionalizing type
Load Break Switch Qty: (2)
Load Break Switch Rating: 200 A Cont./Interrupting Current Rating, 15 kV Class, 16 kA Momentary Current, 10 kA Close-And-Latch Rating, 95 kV BIL
Load Break Switch Location: On the load side of the incoming primary bushings
Efficiency Standard(s): Meets DOE 2016 Standards, Meets ANSI/IEEE Standards
K-Factor Rating (Harmonic Mitigation): K-1 (Standard)
Pulse Drive Rating: N/A
Insulation Fluid: Enviro-temp FR-3 type less flammable fluid
Fluid Capacity*: TBD
Fluid Weight*: TBD
Liquid Level Indicator: Internal In-Tank Oil Level Line
Temperature Indicator: N/A
Pressure/Vacuum Indicator: N/A
Pressure Relief Device: Included, Automatic Action, Diaphragm Type, Replaceable, Designed to re-seal after operating
Fault Indicator: N/A
Oil Level Marking: Internal
Fill Valve: N/A (Tank Filled via Removable Lid)
Drain Valve: 1/2" NPT Port w/ Removable Bolt
Winding Material: Copper
Service Condition: Outdoor
Ambient Temperature Rating: 40°C
Sound Level: 55 dBA
Elevation Level: N/A
Core Material: Non-aging, cold-rolled, grain-oriented, stress free, thin silicon steel laminations
Tank Material: 316L Stainless Steel
Housing Material: 316L Stainless Steel Steel w/ Corrosion Resistant Cover Band, Removable Top Cover
Hardware Material: 316L Stainless Steel
Nameplate Material: 316L Stainless Steel

Efficiency: 99.20%
Based on transformer operating at 50% of nameplate base kVA.

Load Losses Based on 85°C Reference Temp.

No Load Loss (in watts): +/- 683W

Full Load Loss (in watts): +/- 2,763W
Total Load Loss (in watts): +/- 3,445W
Note: Losses offered are typical only, not guaranteed

Paint Type: Weatherproof and UV Resistant Epoxy Coating and Undercoating
Finish Color: ANSI 70 Light Grey
Mounting: Floor Mount
Lifting Lugs: Included
Dimensions*: TBD
Overall Tank Height: 51.00"
Tank Diameter: 32.00" OD
Dry Weight*: TBD
Total Weight (Liquid Filled)*: TBD
*Please note that numbers are approximate and subject to change

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail:sales@larsonelectronics.com

The MT-PMUT-R7-1P-GMP-250KVA-SLR-HT-LT-Z6-AFP-CC-1C3-M1 from Larson Electronics is a Submersible Vault Distribution Transformer that offers powerful, reliable, and efficient power distribution in outdoor and public locations. The low operating costs, low heat emissions, and low cost of ownership makes this transformer ideal for a wide range of applications and businesses. This submersible vault power distribution system is designed for underground installation in concrete vaults where flooding may happen and the transformer may be temporarily submerged.
PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*
Transformer Features: With a transformer rating of 250 kVA, this submersible industrial transformer features a primary voltage of 13800Y/7970 Grounded Wye and a secondary voltage of single-phase 277/480V (L-N-L). This transformer connects to a three phase electrical grid system to provide single phase low voltage power for indoor distribution. This submersible transformer features porcelain high-voltage, dual load break bushings on the primary side and three bushings on the secondary side. Equipped with copper windings and a grain oriented steel core, this submersible distribution transformer consists of one coil and two core loops. Tin plated terminals on the primary and secondary side accepts copper or aluminum connections.
The MT-PMUT-R7-1P-GMP-250KVA-SLR-HT-LT-Z6-AFP-CC-1C3-M1 is air cooled and does not have fans or but has a radiator and mounting provision for fans. This unit features a 55°C temperature rise for reduced heat waste, increased reliability and longer life. The submersible design makes this unit suitable for use in concrete vaults where flooding may occur or in other areas where the transformer may be temporarily submerged such as underground.
Insulation Fluid: The MT-PMUT-R7-1P-GMP-250KVA-SLR-HT-LT-Z6-AFP-CC-1C3-M1 features FR-3 insulation fluid. Internal marking is available for proper oil level monitoring. We offer transformers with biodegradable fluid, if needed.
Gauges: There is a liquid level gauge. We can add temperature, and pressure/vacuum gauges at an additional cost. Standard liquid level gauge is analog, manual reading type.
Pressure Relief Device: An automatic pressure relief device is included with this transformer.
Rapid Rise Relay: There are no rapid rise relays on the unit. This safety component is designed for protection when a rapid increase in tank pressure occurs. The relay is suitable for detecting sudden pressure fluctuations above predetermined safe limits.
Surge arresters: This system doesn't contain surge arrestors.
Valves: The MT-PMUT-R7-1P-GMP-250KVA-SLR-HT-LT-Z6-AFP-CC-1C3-M1 is not equipped with fill or drain valves. The transformer can be filled via removing the top lid. A drain port w/ bolt plug is equipped.
Protection Fuses: This transformer contains Bayonet fuses. For units without protection fuses, up stream protection is provided. We recommend provisions for protection fuses when possible, as blown fuses may require more frequent oil changes.
Mount: The heavy-duty enclosure makes the unit suitable for underground applications such as concrete vaults where flooding may occur. This submersible vault distribution transformer can be floor mounted.
Benefits: The MT-PMUT-R7-1P-GMP-250KVA-SLR-HT-LT-Z6-AFP-CC-1C3-M1

heavy-duty transformer offers many benefits to consumers. This transformer provides owners with significant energy savings, as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turns into cost savings for owners in the form of lower energy bills and decreased cost of ownership.


Applications: Underground installation applications, such as concrete vaults, where the transformer may be temporarily submerged due to flooding.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)


#281031

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364





Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **HigResPic1**
- **HigResPic2**
- **HigResPic3**
- **HigResPic4**
- **HigResPic5**
- **Video1**
- **Video2**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**