Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MT-DOE16-1P-125V-15KVA-250V-N3R-2X6FT-BCE

15 kVA Prewired Isolation Transformer - 125V AC Primary - 250V AC Secondary - NEMA 3R - Single Phase - (2) 6' 16/3 SOOW Whips w/ Blunt Cut Ends

Product ID: 307280

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-DOE16-1P-125V-15KVA-250V-N3R-2X6FT-BCE Prewired Isolation Transformer

Phase: Single Phase
Frequency: 60 Hz
kVA: 15
Primary Voltage: 125V
Taps: 2 @ 2.5% FCAN & 4 @ 2.5% FCBN
Secondary Voltage: 250V
Winding Material: Aluminum
Wiring: Prewired with (2) 6' 12/3 SOOW Whips (One on each side) w/ Blunt Cut Ends
Wiring Termination: Blunt Cut End on Primary Side; Blunt Cut End on Secondary Side
Insulation: 220°C
Temperature Rise: 150°C
Impedance (Std): -
Seismic: Yes
Sound Level: Meets NEMA ST-20 Standards
Primary Termination: -
Secondary Termination: -
Enclosure Material: NEMA Type 3R Heavy Duty Ventilated
Finish: ANSI 61 Grey Finish
Dimensions: (*Please note that dimensions are approximate and subject to change*) 33.5"-H x 48"-W x 48"-D
Weight: (*Please note that weight is approximate and subject to change*) 415 lb
Mounting: Floor or Wall Mount

Ratings

NRTL Listed for United States and Canada
ANN Cooling
IP14 Rated
Prewired Isolation Transformer

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-214-616-6180

E-mail: sales@larsonelectronics.com

The MT-DOE16-1P-125V-15KVA-250V-N3R-2X6FT-BCE from Larson Electronics is a 120V 1 Phase Energy Efficient Prewired Isolation Transformer that is powerful, reliable, and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-DOE16-1P-125V-15KVA-250V-N3R-2X6FT-BCE provides increased reliablity and protection against critical equipment failures. The lower operating costs, lower heat emissions, and lower cost of ownership make this transformer ideal for a wide range of applications and businesses. The MT-DOE16-1P-125V-15KVA-250V-N3R-2X6FT-BCE is a prewired transformer for customer installation and is equipped with 6' of 12/3 SOOW cable with blunt cut ends on each side connected to the transformer.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

Transformer Features: With a transformer rating of 15 kVA, the MT-DOE16-1P-125V-15KVA-250V-N3R-2X6FT-BCE isolation transformer is a single phase unit with a primary voltage of 125V. It also provides a secondary voltage of 250V. Featuring robust construction, this unit's cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology.

This prewired unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The Standard NEMA Type 3R enclosure makes the unit suitable for both indoor and outdoor applications and it can be floor or wall mounted. The unit also features 220°C insulation with a 150°C temperature rise and is rated IP14.

Wiring/Installation: The MT-DOE16-1P-125V-15KVA-250V-N3R-2X6FT-BCE is equipped with 6' 12/3 SOOW whips on both the primary and secondary sides. Both whips are terminated in blunt cut ends. This transformer makes installation simple. Operators connect them to the corresponding current. For example, the 250V whip gets connected to 250V current.

Benefits: The MT-DOE16-1P-125V-15KVA-250V-N3R-2X6FT-BCE isolation transformer offers many benefits to the consumer. Precision cut aluminum transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations.

This isolation transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. Integrated floor and wall brackets make installation fast and easy and the offset outward facing floor installation holes allow for easy power tool access.

Safety: The MT-DOE16-1P-125V-15KVA-250V-N3R-2X6FT-BCE is an isolation transformer which means that it provides operators with an increased level of protection against electric shock. An isolation transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-DOE16-1P-125V-15KVA-250V-N3R-2X6FT-BCE achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

Applications: General purposes.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364







Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **Operations Manual**
- **HigResPic1**
- **HigResPic2**
- **HigResPic3**
- **HigResPic4**
- **HigResPic5**
- **HigResPic6**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**