

MT-PDT-VPM-K4-3P-DMP-750KVA-YE-A6-HA-CZ-4Z-ZZ-Z-N3R-M1

**750 KVA Vacuum Pressure Impregnated Transformer, 13800V Delta Primary, 480Y/277 Wye-N
Secondary, FA, Class H, VPI**

Product ID: 308948

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-PDT-VPM-K4-3P-DMP-750KVA-YE-A6-HA-CZ-4Z-ZZ-Z-N3R-M1 Vacuum Pressure Impregnated Transformer

Transformer Type: Vacuum Pressure Impregnated (VPI) Transformer

Transformer Configuration: Dry Type, Ventilated

Phase: Three Phase

Capacity: 750 KVA

Vector Group: Dyn11

Primary Voltage: 13800V AC

Primary Voltage Class: 15 kV Class

Primary Phasor: Delta

Primary BIL: 35 KV

Secondary Voltage: 480Y/277 AC

Secondary Voltage Class: 1.2 kV Class

Secondary Phasor: Wye-N

Secondary BIL: 30 KV

Frequency: 60 Hz

Temperature Rise: 150°C

Cooling Class: FA; Fan-Cooled

Forced Air (Fans): Included

Insulation Class: Class H

Tap Changer: 5-Position Tap Changer

Tap Qty: (2) FCAN Above, (2) FCBN Below

Tap %: 2.5%

Ratings

NRTL Listed for United States and Canada

Complies with ANSI / IEEE C57.12.00

Complies with ANSI / IEEE C57.12.01

Complies with ANSI / IEEE C57.12.35

Complies with ANSI / IEEE C57.12.59

Complies with ANSI / IEEE C57.12.70

Meets/Exceeds 10 CFR 431, Subpart K, Efficiency Ratings

Meets/Exceeds CSA Efficiency Ratings

Meets or Exceeds NEMA ST-20 Standards

NEMA 3R Indoor/Outdoor Steel Enclosure

Seismic Qualified for Earthquake Loads

RoHS Certified

CE Certified

Efficiency %: 99.20%

Based on transformer operating at 50% of nameplate base kVA.

Load Losses at 145°C Reference Temp.

No Load Loss (in watts): +/- 1,500W

Full Load Loss(in watts): +/- 9,300W

Total Load Loss (in watts): +/- 10,800W

Tap Changer Switch Location: HV Compartment

Impedance (at 120°C): 5.75% ± 7.5%

Primary Connection Type: Terminal Lugs

Primary Surge Arrestors: Included, (3) Metal-Oxide, Gapless-Type, Station Class Surge Arrestors

Primary Surge Arrestor Voltage Rating: 15 KV

Primary Surge Arrestor MCOV Rating: 15 KV rms

Primary Over Current Protection (OCP): N/A

Primary Over Current Protection Method: N/A

Primary Grounding Provisions: N/A

Secondary Connection Type: Terminal Lugs

Secondary Surge Arrestors: Included, (3) Metal-Oxide, Gapless-Type, Station Class Surge Arrestors

Secondary Surge Arrestor Voltage Rating: 1 KV

Secondary Surge Arrestor MCOV Rating: 1 KV rms

Secondary Over Current Protection (OCP): N/A

Secondary Grounding Provisions: Lugs

Metering Current Transformer (CT): N/A

Metering Panel: N/A

Auxiliary Control Panel : N/A

Load Break Switch: N/A

Load Break Switch Qty: N/A

Load Break Switch Location: N/A

Efficiency Standard(s): DOE 2016, IEEE, ANSI

K-Factor Rating (Harmonic Mitigation): K-4

Temperature Sensors in Coil: Included, w/ Alarm & Trip Contacts

Temperature Gauge: Included, w/ 3 Contacts

Seismic Bracing: Included

Weather Shield: N/A

Space Heaters: N/A

Winding Material: Copper

Ambient Temperature Rating: 40°C

Sound Level: 58 dBA

Elevation (Altitude) Rating: 3300ft (1000 meters) Above Sea Level

Core Material: Cold Rolled, Non-Aging Silicon Steel

Enclosure Material: Coated Steel

Enclosure Rating: NEMA 3R Weatherproof

Lifting Eyes: Included

Jacking Pads: Included

System Form Factor: N/A

Paint Type: Epoxy Paint

Finish: ANSI 61 Grey

Mount: Pad Mount / Floor Mount

Dimensions: 62.99"L x 55.11"W x 70.86"H

Weight: 4,365 lbs

*Please note that numbers are approximate and subject to change

Note: Losses offered are typical only, not guaranteed

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The MT-PDT-VPM-K4-3P-DMP-750KVA-YE-A6-HA-CZ-4Z-ZZ-Z-N3R-M1 Vacuum Pressure Impregnated Transformer from Larson Electronics converts three-phase 13800V Delta to three-phase 480Y/277 Wye-N. This power distribution unit provides operators the ability to safely tap into and distribute 750KVA AC power from a variety of sources, such as direct grid power. The entire system is secured to a skid mount platform.
PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

Transformer Features: With a transformer rating of 750 KVA, the industrial dry type transformer features a primary voltage of three-phase 13800V AC Delta and a secondary voltage of three-phase 480Y/277 AC Wye-N. This transformer is equipped with a 5-position tap changer with five, +/- 2.5% taps (two FCAN above and two FCBN below) to allow small changes for voltage. The system has copper windings for high strength and electrical conductivity. This VPI transformer features minimized air gaps and voids in the insulation, leading to increased

durability and thermal stability.

The MT-PDT-VPM-K4-3P-DMP-750KVA-YE-A6-HA-CZ-4Z-ZZ-Z-N3R-M1 has fans for forced air cooling.

Transformer Efficiency: The Class H transformer meets standard efficiency requirements. High efficiency makes this unit suitable for use in electrical rooms, air conditioned spaces in buildings, underground vaults and similar locations, in addition to outdoor areas.

Temperature Sensor: The MT-PDT-VPM-K4-3P-DMP-750KVA-YE-A6-HA-CZ-4Z-ZZ-Z-N3R-M1 is equipped with temperature sensors inside the system for controls and monitoring. A monitoring service is not included with the transformer.

Temperature Gauge: This transformer comes with a temperature gauge.

Load Break Switch: This VPI transformer does not include a load break switch. We can add a load break switch at an additional cost.

Surge Arresters: This transformer includes surge arresters on both primary and secondary sides. Designed for over-voltage and transient voltage protection, the components prevent damage caused by lightning, internal switching or voltage surges. We can offer models without surge arresters that have mounting provisions for customer-provided surge arresters.

Control Transformer: This VPI transformer does not include a control transformer. We can add a control transformer for operating equipment at an additional cost.

Seismic Bracing: This system does not include seismic bracing. We can add seismic bracing for added protection in areas prone to earthquakes at an additional cost.

Weather Shield: This transformer does not include a weather shield. We can add a weather shield for protection in outdoor areas, humid environments and rodents at an additional cost.

Space Heaters: This system does not include a space heater. We can add a space heater for preventing condensation during extended shutdown at an additional cost.

Enclosure Design: This VPI transformer is protected by a steel housing. The enclosure carries a NEMA 3R rating for protection from exposure to moisture, rain, dust and debris.

Mount: The power distribution unit is mounted atop a skid plate base that allows this transformer to easily be moved from one location to another using a forklift. The skid platform is designed for serious use and is ruggedly constructed to withstand demanding conditions and heavy duty industrial applications. The industrial grade skid platform can be modified to meet the needs of job-site requirements.

Benefits: The MT-PDT-VPM-K4-3P-DMP-750KVA-YE-A6-HA-CZ-4Z-ZZ-Z-N3R-M1 transformer offers many benefits to consumers. This transformer provides owners with significant energy savings, as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turns into cost savings for owners in the form of lower energy bills and decreased cost of ownership.

Applications: General purposes, industrial sites, electrical rooms, underground vaults, manufacturing facilities, steel plants, offshore, commercial, military, processing plants, electric power distribution, utilities, public locations and more. Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.



Frequently Asked Questions (FAQ)







Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)