

EXP-MTR-3P-415.440V-17HP-1.5K-215T

17 HP Explosion Proof Motor - Class I, II - 415/440V 3PH 50/60 Hz - 1500 RPM - Foot Mount - 215T Frame

Product ID: 309508

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EXP-MTR-3P-415.440V-17HP-1.5K-215T Explosion Proof Motor

Listing: NRTL Listed for United States & Canada

Dimensions: 20.631" x 12.928" x 10.709"

Weight: 228 lbs

Phase: Three Phase

Voltage: 415/440V AC

Frequency: 50/60 Hz

Poles: 4

Output Horsepower: 17 HP

Kilowatt: 13 KW

Rotations per Minute: 1500 RPM - 1440 RPM

Motor Frame: 215T

Rated Current: 23.4A/11.7A

FL Efficiency: 91.7%

Service Factor: 1.15

Insulation: Class F

Noise: 58 dBA

Ambient Temperature Rating: -20°C to 40°C

Materials: Aluminum

Mount: Foot Mount

Wiring: 24" (+2/-0) Leads

Ratings

Class I, Division 1 Groups C,D

Class II, Division 1 Groups F,G

IP55

TEFC Cooling

Aluminum Endshields

Special Orders- Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Color: Blue

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The Larson Electronics EXP-MTR-3P-415.440V-17HP-1.5K-215T Explosion Proof Motor is recommended for use in Class I, Division 1 Groups C, D and Class II, Division 1 Groups F, G rated work sites. The 17 HP unit is compatible with three-phase 415/440V AC, 50/60 Hz. This Class F insulation rated explosion proof motor features a 215T motor frame and can be installed with industrial systems via an integrated mounting foot.

The EXP-MTR-3P-415.440V-17HP-1.5K-215T is a fractional explosion proof motor for flammable work sites. This thermally protected unit operates with three-phase 415/440V AC, 50/60 Hz. The 17 HP motor offers 18.09/17.06 amps with 91.7% full-load efficiency. Capable of generating 1500 RPM, this motor is totally enclosed and fan-cooled (TEFC).

The IP55-rated explosion proof motor features an ambient temperature rating of 40°C. Equipped with aluminum end shields, this unit is protected by a 215T motor frame and features Class F insulation, with 1.15 service factor.

Wiring: The EXP-MTR-3P-415.440V-17HP-1.5K-215T comes with 24" of +2/-0 leads for electrical connections and an unassembled aluminum conduit box.

Mount: The EXP-MTR-3P-415.440V-17HP-1.5K-215T is foot mounted for supporting the motor's weight for sturdy, secure installations. Feet components are typically fixed on the surface, which reduces unnecessary movements during operation.

Applications: Hazardous locations, industrial facilities, pumps, mixers, conveyors, manufacturing, food processing, chemical plants and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Frequently Asked Questions (FAQ)

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [HigResPic1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)