

MT-ISX-FP-1P-4200V-0.75KVA-120V-N3R-M2

750 VA Isolation Transformer - 4200V Primary - 120V Secondary - 1PH/N3R - w/ Primary Fuses - Fully Potted/Encapsulated

Product ID: 309880

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-ISX-FP-1P-4200V-0.5KVA-120V-N3R-M2 Fully Potted Isolation Transformer

Phase: Single Phase
Frequency: 60 Hz
kVA: 0.750 (750 VA)
Primary Voltage: 4200V AC
Secondary Voltage: 120V AC
Winding Material: Aluminum
Impedance: -
Insulation: 130°C
Temperature Rise: 115°C
Seismic Zone: -
Primary Termination: Leadwires
Primary Fuses: Included
Secondary Termination: Leadwires
Mounting: Wall
Sound Level: Meets NEMA ST-20 Standards
Enclosure Material: NEMA Type 3R Heavy Duty Ventilated
Finish: ANSI 61 Grey Finish
Dimensions: (*Please note that dimensions are approximate and subject to change*)
9.06"-H x 4.37"-W x 4.20"-D
Weight: (*Please note that weight is approximate and subject to change*) 15 lb

Approvals/Ratings

NRTL Listed for United States
CSA Certified
NRTL Certified to C22.2 No. 47
NRTL Certified to UL 506
Fully Potted / Encapsulated
Isolation Transformer

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-214-616-6180

E-mail: sales@larsonelectronics.com

The MT-ISX-FP-1P-4200V-0.75KVA-120V-N3R-M2 from Larson Electronics

is a 4200V 1 Phase Fully Potted Energy Efficient Isolation Transformer that is powerful, reliable and designed with the environment in mind. Suitable for both indoor and outdoor applications, the MT-ISX-FP-1P-4200V-0.75KVA-120V-N3R-M2 provides increased reliability, protection against critical equipment failures and an extra level of protection by isolating the power source from the connected device. The lower operating costs, lower heat emissions, and lower cost of ownership make this transformer ideal for a wide range of applications and businesses.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

Transformer Features: With a transformer rating of 0.75 kVA (750 Volt Amps), the MT-ISX-FP-1P-4200V-0.75KVA-120V-N3R-M2 isolation transformer is a single phase unit with a primary voltage of 4200V. It also provides a secondary voltage of 120V. Featuring robust construction, this unit's cores are manufactured with non-aging, cold-rolled silicon steel laminations using state of the art technology. This fully potted unit boasts a low cost of ownership and is highly energy efficient. Lower heat emissions mean less cooling is needed as well. The Standard Type 3R enclosure makes the unit suitable for both indoor and outdoor applications and it can be wall mounted. The unit also features 130°C insulation with a 115°C temperature rise and is rated IP14.

Benefits: The MT-ISX-FP-1P-4200V-0.75KVA-120V-N3R-M2 encapsulated isolation transformer offers many benefits to the consumer. Precision cut aluminum transformer winding material help to improve performance. The close tolerances used during manufacturing also eliminates burrs which hinder performance. Each core is specially coated to prevent the ingress of moisture and are electrically balanced to minimize axial forces during short circuit situations. This fully potted transformer provides owners with significant energy savings as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turn into cost savings for owners in the form of lower energy bills and decreased cost of ownership. This transformer is designed for panel mounting.

Safety: The MT-ISX-FP-1P-4200V-0.75KVA-120V-N3R-M2 is an isolation transformer which means that it provides operators with an increased level of protection against electric shock. An isolation transformer can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected. The MT-ISX-FP-1P-4200V-0.75KVA-120V-N3R-M2 achieves these safety features by separating or "isolating" the powered device from the power source and insulation between the primary and secondary power sources.

Applications: Power supplies for sensitive equipment such as computers, medical devices, or laboratory instruments.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Frequently Asked Questions (FAQ)

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [Operations Manual](#)
- [HigResPic1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)