Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MT-TT-120.240V-750VA-28V-M2

750 VA 1-Ph Toroidal Transformer - 120/240V Input - 28V Output - 60 Hz W/ Resin Filling

Product ID: 311087

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-TT-120.240V-750VA-28V-M2 Toroidal Transformer

Type: Toroidal Transformer
Phase: Single Phase
Frequency: 60 Hz
Input Voltage: 120/240V
Output Voltage: 28 V
Capacity: 750 VA
Load Current: 26 A
Temperature Rise: TBD
Insulation Class: TBD
Iron Loss: TBD
Copper Loss: TBD
Efficiency: TBD
Input Termination: 3-Wires, Blue-Black-Brown, 12" Length
Output Termination: 2-Wires, Blue-Black, 12" Length
Operating Temperature: -40°C to +40°C
Resin Filling: Included
Core Material: Silicon Steel
Mounting: Mounted Through Bolt, Rubber Mat. X2, Iron Cover, Flat Washer, Lock Washer and nut
Dimensions: 5.12"-Outer Size, 3.15"-Height
Weight: 15.65 lbs

Approvals/Ratings

cUL Listed
CE Listed
UL Listed
CSA Listed

Special Orders - Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

The MT-TT-120.240V-750VA-28V-M2 from Larson Electronics is a toroidal transformer. It's a type of electrical transformer constructed with a torus or donut shaped core. Its primary and secondary windings are wound across the entire surface of the torus core, separated by an insulating material. It's a passive machine that transfers electrical energy from one circuit to another using a magnetic field to induce an electromotive force.
Transformer Features: With a 750 VA Rating, the MT-TT-120.240V-750VA-28V-M2 is a single phase toroidal transformer with an input voltage rating of 120/240V (3-Wires) and an output voltage rating of 28V (2-Wires). Transformer cores are typically made from silicon steel.
Mounting: Connected directly to the PCB. Adding a lead through a hole in the PCB does this. It's held in place by being soldered on the other side. The unit also features an operating temperature range of -40°C to +40°C.
Applications: These transformers are commonly used in applications requiring high signal resolution, such as audio systems, medical devices, measuring instruments, and power analyzers.
Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **Wiring Diagram**
- **HigResPic1**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**