

MPD-SWGR-LV-FS-CTC-3P-4W-800V-2500A-BM-N3R-M1

LV Switchgear Cabinet- 800 V 3-phase, 4-wire - 2500A, 9X250A Outgoing- NEMA 3R

Product ID: 311493

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MPD-SWGR-LV-FS-CTC-3P-4W-800V-2500A-BM-N3R-M1 LV Switchgear Cabinet

Unit Type: Low Voltage Switchgear Cabinet

Line-In: N/A (customer provided)

Line-In Cord Cap: N/A (customer provided)

Line-In Connections: N/A

Line-In Orientation: N/A

Nominal Voltage: 800 V AC

Rated Max Voltage: 1.2 kV

Rated BIL Voltage: 30 KV

Continuous And Load Interrupting Current: 2500A

Short-Time And short-Circuit Interrupting Current: 65 KA

Phase (PH): 3-Phase

Frequency (Hz): 60 Hz (60-Cycles)

Wire: 4-wire

Neutral Connection: Included

Made in the USA

Features Of Every Vertical Section

Structural design and anchorage adequate to resist loads imposed by 125 mph wind.

Space heater operating at one-half or less of rated voltage, sized to prevent condensation, controlled by thermostats to maintain temperature of each section above expected dew point.

Louvers equipped with insect and rodent screens and filters, and arranged to permit air circulation while excluding rodents and exterior dust.

Weatherproof ground-fault circuit interrupter duplex receptacles

Skid Mounted: Mount each shipping group on an integral base frame as a complete weatherproof unit

Metering Section:

Consists Of Pre-wired Form 9S ring-type meter socket (13-jaw)

Consists Of Pre-wired revenue-grade CTs with 400:5 ratio and a TRF of 3.0 to

Ratings

ANSI and IEEE Standards for Switchgear

NEMA 3R Indoor Use

accommodate up to 1200A
Consists Of Meter test bypass switch

Main Breaker Protective Features:

Adjustable trip settings
Ground fault protection
Bonding jumper between neutral and ground is installed inside the main breaker compartment and furnished with a ground fault current sensor

Branch Breakers (Air Insulated Breaker): (9) 250A

Complies With IEEE C37.74
Complies With IEEE C37.60
Complies With IEEE C2
Complies With IEEE C37.20.3
Complies With Utility Company's (PSEG) Primary
Metering Specification Standard CS-8735
Complies With IEEE C57.12.28
Complies With IEEE C37.2
Complies With IEEE 1815
Complies With IEEE 386
Complies With IEEE C62.11

Support Frame And Enclosure Base Material: Powder Coated Steel

Enclosure Finish: Munsell™ 5BG 7.0/0.4 Light Grey (ANSI #70)

Enclosure Type: NEMA 3R Ventilated, Weatherproof

Mounting: Integral skid mounting frame, designed for mounting on a concrete pad, suitable to allow skidding or rolling of the switchgear in any direction, and with provision for anchoring the frame to the pad

Dimensions: TBD

Weight: TBD

Shipping Dimensions: TBD

Shipping Weight: TBD

Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Made in the USA

The Larson Electronics MPD-SWGR-LV-FS-CTC-3P-4W-800V-2500A-BM-N3R-M1 Low Voltage Switchgear Cabinet provides centralized access to breakers in rugged work sites. This unit consists of five cabinets and is compatible with three-phase 800 V AC. Designed for indoor applications, the NEMA 3R system features three branch breakers.

****PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS****

The MPD-SWGR-LV-FS-CTC-3P-4W-800V-2500A-BM-N3R-M1 low voltage switchgear cabinet protects, controls and isolates equipment in industrial facilities. Compatible with three-phase 800 V AC, the unit features a Incoming 2500 A main circuit breakers & 9 x 250A Outgoing Circuit Breakers. The primary switch has 3 CTs 400/5A connected to hot sequence Meter to monitor V, A, KVA, KW, PF, Hz also has Multi-Function Protection Relay with the following (50) Instantaneous Overcurrent, (51) Phase Time Overcurrent & (51G) Time Delay Ground Overcurrent.

Enclosure Design: A ventilated design promotes natural cooling and improves performance. The enclosure is NEMA 3R rated and can be used in indoor areas.

Certification: This switchgear cabinet complies with ANSI and IEEE standards.

Applications: This switchgear is suitable for indoor use and applications including, but not limited to, construction sites, plant maintenance, plant turnarounds, manufacturing operations, shows, exhibits, and warehouse operations.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Frequently Asked Questions (FAQ)

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [HigResPic1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)