Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

MPD-DS-WML-NFDS-DC-4P-4W-1000VDC-400A-DF-BM-N3R

400 Amp Non-Fused Manual DC Disconnect Safety Switch - 1000V DC - 4-Pole, 4-Wire - NEMA 3R

Product ID: 312743

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).

Image: MPD-DS-WML-NFDS-DC-4P-4W-1000VDC-400A-DF-BM-N3R

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MPD-DS-WML-NFDS-DC-4P-4W-1000VDC-400A-DF-BM-N3R Disconnect Switch - Non Fused Disconnect

Unit Type: Service Entrance Non Fused Disconnect Switch
Line-In: N/A (Customer Provided)
Line-In Cord Cap: N/A (Customer Provided)
Line-In Connections: Terminal Lugs
Line-In Orientation: Bottom Feed
Voltage (V): 1000V DC
Phase (PH): -
Frequency (Hz): -
Protection Method: N/A (Customer Provided)
Protection Type: N/A (Customer Provided)
Protection Ampacity: -
Mains Rating (Amps): 400A
Interrupting Rating: 10 kA @ 1000V DC
Horsepower (Standard):
Max Motor Full Load Amps Rating:
Disconnect Means: Manual via Handle
Neutral Connection: -
Line-Out: N/A (Customer Provided)
Line-Out Cord Cap: N/A (Customer Provided)

Ratings

NRTL Listed Service Equipment
NRTL Listed to UL 98 Dead Front Switch Boards
NEMA 3R Rated for Indoor and Outdoor Use
Made in the USA

Line-Out Connection: Terminal Lugs, Accepts 750MCM-1/0
Line-Out Orientation: Bottom Feed
Form Factor: Rectangular, Slim-profile Enclosure w/ Lockable Door
Door: (1) Left Hinged Door w/ Pad Lockable Handle
Enclosure Material: 11GA Sheet Steel
Enclosure Finish: ANSI 49 Grey
Enclosure Type: NEMA 3R Ventilated
Mount: Wall Mount
Dimensions: -
Weight: -
Shipping Dimensions: -
Shipping Weight: -

Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

Special Orders - Special Requirements

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Made in the USA

The MPD-DS-WML-NFDS-DC-4P-4W-1000VDC-400A-DF-BM-N3R from Larson Electronics Power Distribution Non Fused Disconnect Switch is designed for reliable, safe, and convenient power distribution at industrial work sites. Designed for wall mounting installations, the disconnect switch is protected by a NEMA 3R rated, steel enclosure with a ventilated design.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

The MPD-DS-WML-NFDS-DC-4P-4W-1000VDC-400A-DF-BM-N3R service entrance disconnect switch provides a safe and reliable way for operators in industrial settings to tap into and utilize power sources independently of the work area. Compatible with high voltage 1000V DC, the disconnect switch features a manual operating handle. This 4-pole, 4-wire disconnect carries a 10 kA at 1000V DC interrupt rating.

Operation: The dead front disconnect switch features a locking door. The door provides access to a permanently attached operating handle, which is used for manually disconnecting or connecting power.

Enclosure Design: The disconnect switch is protected by an 11GA sheet steel enclosure with ANSI 49 grey finish. A ventilated design promotes natural cooling and improves performance. The enclosure is NEMA 3R rated for protection against water, moisture and debris. This rating allows the non fused disconnect to be used in indoor and outdoor areas.

Certification: This disconnect switch is NRTL listed to UL 98 dead front switchboards and NRTL listed for service equipment.

Mount: Operators can mount the service entrance disconnect on walls.

Customization: The MPD-DS-WML-NFDS-DC-4P-4W-1000VDC-400A-DF-BM-N3R can be customized to meet specific operating and power requirements. Example of customizations include:

• Making the non-fused disconnect portable and certified to NRTL UL 1640 for portable

equipment

• Adding single pole camlock connectors for quick connections

• Adding heaters for cold environments

• Aiding alarm relays for trip notification down stream

• Adding powering meters

Applications: This switchgear is suitable for indoor/outdoor use and applications including, but not limited to, motors, solar, railway, and other high voltage DC applications.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Image: MPD-DS-WML-NFDS-DC-4P-4W-1000VDC-400A-DF-BM-N3R

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MPD-DS-WML-NFDS-DC-4P-4W-1000VDC-400A-DF-BM-N3R

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Image: MPD-DS-WML-NFDS-DC-4P-4W-1000VDC-400A-DF-BM-N3R

Image: MPD-DS-WML-NFDS-DC-4P-4W-1000VDC-400A-DF-BM-N3R

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **HigResPic1**(https://www.larsonelectronics.com/images/product/HigResPic1/312743.JPG)
- **HigResPic2**(https://www.larsonelectronics.com/images/product/HigResPic2/312743.JPG)
- **HigResPic3**(https://www.larsonelectronics.com/images/product/HigResPic3/312743.JPG)
- **HigResPic4**(https://www.larsonelectronics.com/images/product/HigResPic4/312743.JPG)
- **HigResPic5**(https://www.larsonelectronics.com/images/product/HigResPic5/312743.JPG)
- **Video1**(https://www.youtube.com/watch?v=h09GF5O4MYU)
- **Video2**(https://www.youtube.com/watch?v=aOJY5E9e33I)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)