Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

## MT-HV-CCVT-R7-1P-GXK-145KV-SX.LM-CL0.3WXMYZ-60HZ

# 145 KV High Voltage Coupling Capacitor Voltage Transformer - 138000Y/80000 Grounded Wye Primary, 115/72 V Secondary, Class 0.3, WXMYZ

**Product ID: 313486**

**Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).**



Image: MT-HV-CCVT-R7-1P-GXK-145KV-SX.LM-CL0.3WXMYZ-60HZ

**Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.**

**MT-HV-CCVT-R7-1P-GXK-145KV-SX.LM-CL0.3WXMYZ-60HZ High Voltage Coupling Capacitor Voltage Transformer**

**Type:** High Voltage Coupling Capacitor Voltage Transformer (HV-CCVT)
**Phase:** Single Phase
**Frequency:** 60 Hz
**Primary Voltage Rating:** 138000Y/80000 Grounded Wye
**Maximum System Voltage:** 145 KV
**Primary Voltage BIL Rating:** 650 KV
**Primary Min. Creepage Distance:** 142 inches
**System Short Circuit:** 31.5 kA
**Voltage Rating Factor:** 1.2 (Cont.) / 1.5 (30 Sec.)
**Secondary Voltage:** 115/72V Dual Windings, Single Phase
**Rated Capacitances:** 5000 pF
**No. Of Coupling Capacitors:** (2)
**Creepage distance:** TBD
**Insulation Fluid:** Oil-paper-quartz (Non-PCB)
**Bushing Material:** Porcelain
**Bushing Painting:** Munsell™ 5BG 7.0/0.4 Light Grey (ANSI #70)
**Primary Bushing Insulator Material:** Porcelain
**Primary Termination:** The primary terminal (H1) is NEMA 4-inch, 4-hole copper pad terminal. The terminal conducting surface is horizontal. The current transfer point is tinned or silver plated

**Approvals/Ratings**

IEC/EN60044-1, BS7626 Compliant
Two Years Of Warranty

**Secondary Termination:** The secondary winding connections are terminated on a terminal block mounted in the secondary terminal box.
**Secondary terminal box:** Included, NEMA 4 Insulation Class, equipped with a detachable, undrilled gland plate. The terminal box is provided with a drain. The terminal box is adjacent to and adjoin the transformer base housing. The junction box includes a large access door and provision for entry of three conduits (1.5 inch maximum diameter) for CPS connection.
**Grounding Pads:** Included, The transformer is provided with two (2) NEMA 2-hole ground pads. One ground pad is located near the secondary junction box. The holes in the ground pads are threaded for 1/2"-13 UNC bolts. The threads are protected with a rust inhibitor and with flanged cups of a non-corrosive material press fitted into threaded openings.
**ANSI Metering Accuracy Rating:** 0.3
**Burdens:** WXMYZ
**Oil Level Gauge:** Included
**Fill Plug:** Included
**Drain Valve:** Included, equipped with Sampling device.
**Heater:** Included, 120/240 VAC, 1-Phase
**Lifting Provisions:** Included
**Base Housing Material:** Steel
**Elevation:** <3300 feet
**Seismic Zone:** Low, IEEE 693
**Wind Load:** <115 mph
**Ice/Snow Load:** 20 psf
**Operating Temperature Range:** -40°C to +50°C
**Housing Painting:** Munsell™ 5BG 7.0/0.4 Light Grey (ANSI #70)
**Mounting:** Pedestal (vertical)
**Dimensions:** 23.22"-W, 28.2"-L, 125"-H
**Total Weight:** 1,598.35 lbs

**Special Orders - Requirements**
Contact us for special requirements
**Toll Free:**1-800-369-6671
**Intl:** 1-903-270-1187
**E-mail:** sales@larsonelectronics.com

**The MT-HV-CCVT-R7-1P-GXK-145KV-SX.LM-CL0.3WXMYZ-60HZ from Larson Electronics is a 145KV Single Phase High Voltage Coupling Capacitor Voltage Transformer that is powerful, reliable, and innovatively designed. This is an ideal solution for measuring and monitoring voltages being used on cables.**

**Transformer Features:** The MT-HV-CCVT-R7-1P-GXK-145KV-SX.LM-CL0.3WXMYZ-60HZ is a single phase high voltage coupling capacitor current transformer with a maximum voltage of 145KV. Featuring compact and innovative construction, this unit's cores are manufactured with high-quality silicon steel laminations using state of the art technology. The unique quartz filling minimizes the quantity of oil and provides a mechanical support to the cores and primary winding. Due to the low center of gravity the MT-HV-CCVT-R7-1P-GXK-145KV-SX.LM-CL0.3WXMYZ-60HZ is very suitable for areas with low seismic activity.

This unit is compatible with floor mounting and base mounting. The unit also features an operating temperature range of -40°C to +50°C.

**Applications:** Voltage Monitoring, Switchgear, Distribution Systems, Generator Sets, Metering

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

# Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MT-HV-CCVT-R7-1P-GXK-145KV-SX.LM-CL0.3WXMYZ-60HZ

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MT-HV-CCVT-R7-1P-GXK-145KV-SX.LM-CL0.3WXMYZ-60HZ



Image: MT-HV-CCVT-R7-1P-GXK-145KV-SX.LM-CL0.3WXMYZ-60HZ

**Export Control Classification Number (ECCN):** EAR99

Links (Click on the below items to view):

- **Dimensional Drawing 2D**( https://www.larsonelectronics.com/images/product/DimensionalDrawing/313486.PDF )
- **HigResPic1**( https://www.larsonelectronics.com/images/product/HigResPic1/313486.JPG )
- **HigResPic2**( https://www.larsonelectronics.com/images/product/HigResPic2/313486.JPG )
- **HigResPic3**( https://www.larsonelectronics.com/images/product/HigResPic3/313486.JPG )
- **HigResPic4**( https://www.larsonelectronics.com/images/product/HigResPic4/313486.JPG )
- **Video1**( https://www.youtube.com/watch?v=pXV6zJym8pk )
- **ISO 9001 Certification**( http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF )
- **Business Certificate**( https://www.larsonelectronics.com/images/pdfdocs/w9.PDF )
- **Shipping Time Map**( https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf )