

MPD-SWGR-LV-FS-CTC-3P-4W-480V-2000A-BM-N3R

LV Switchgear Cabinet- 480 V 3-phase, 4-wire - 2000A disconnect, 3X350A, 3X200A, 2X100A

Outgoing- NEMA 3R

Product ID: 313937

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MPD-SWGR-LV-FS-CTC-3P-4W-480V-2000A-BM-N3R LV Switchgear Cabinet

Unit Type: Low Voltage Switchgear Cabinet

Line-In: N/A (customer provided)

Line-In Cord Cap: N/A (customer provided)

Line-In Connections: N/A

Line-In Orientation: N/A

Nominal Voltage: 480 V AC

Rated Max Voltage: 1.2 kV

Rated BIL Voltage: 30 KV

Continuous And Load Interrupting Current: 2000A

Short-Time And short-Circuit Interrupting Current: 50 KA

Phase (PH): 3-Phase

Frequency (Hz): 60 Hz (60-Cycles)

Wire: 4-wire

Neutral Connection: Included

Made in the USA

Features Of Every Vertical Section

Structural design and anchorage adequate to resist loads imposed by 125 mph wind.

Space heater operating at one-half or less of rated voltage, sized to prevent condensation, controlled by thermostats to maintain temperature of each section above expected dew point.

Louvers equipped with insect and rodent screens and filters, and arranged to permit air circulation while excluding rodents and exterior dust.

Weatherproof ground-fault circuit interrupter duplex receptacles

Skid Mounted: Mount each shipping group on an integral base frame as a complete weatherproof unit

Metering Section:

Consists Of Pre-wired Form 9S ring-type meter socket (13-jaw)

Ratings

ANSI and IEEE Standards for Switchgear

Consists Of Pre-wired revenue-grade CTs with 400:5 ratio and a TRF of 3.0 to accommodate up to 1200A

Consists Of Meter test bypass switch

Main Breaker Protective Features:

Adjustable trip settings

Ground fault protection

Bonding jumper between neutral and ground is installed inside the main breaker compartment and furnished with a ground fault current sensor

Outgoing Breaker: 3x200A MCCB
2x100A

NEMA 3R Indoor/Outdoor Use

Complies With IEEE C37.74

Complies With IEEE C37.60

Complies With IEEE C2

Complies With IEEE C37.20.3

Complies With Utility Company's (PSEG) Primary Metering Specification Standard CS-8735

Complies With IEEE C57.12.28

Complies With IEEE C37.2

Complies With IEEE 1815

Complies With IEEE 386

Complies With IEEE C62.11

Support Frame And Enclosure Base Material: Powder Coated Steel

Enclosure Finish: Munsell™ 5BG 7.0/0.4 Light Grey (ANSI #70)

Enclosure Type: NEMA 3R Ventilated, Weatherproof

Mounting: Integral skid mounting frame, designed for mounting on a concrete pad, suitable to allow skidding or rolling of the switchgear in any direction, and with provision for anchoring the frame to the pad

Dimensions: TBD

Weight: TBD

Shipping Dimensions: TBD

Shipping Weight: TBD

Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Made in the USA

The Larson Electronics MPD-SWGR-LV-FS-CTC-3P-4W-480V-2000A-BM-N3R Low Voltage Switchgear Cabinet provides centralized access to breakers in rugged work sites. This unit consists of five cabinets and is compatible with three-phase 480 V AC. Designed for indoor and outdoor applications, the NEMA 3R system features three branch breakers.

The MPD-SWGR-LV-FS-CTC-3P-4W-480V-2000A-BM-N3R low voltage switchgear cabinet protects, controls and isolates equipment in industrial facilities. Compatible with three-phase 480 V AC, the unit features a disconnect switch rated 2000A that provides a way to completely cut off power to the switchgear and all connected circuits for maintenance, emergency shutdowns, or fault isolation, an incoming 3350A main circuit breakers, 3 x 200A, 2 x 100A Outgoing Circuit Breakers. The primary switch has 3 CTs 400/5A connected to hot sequence Meter to monitor V, A, KVA, KW, PF, Hz also has Multi-Function Protection Relay with the following (50) Instantaneous Overcurrent, (51) Phase Time Overcurrent & (51G) Time Delay Ground Overcurrent.

Enclosure Design: A ventilated design promotes natural cooling and improves performance. The enclosure is NEMA 3R rated and can be used in indoor and outdoor areas.

Certification: This switchgear cabinet complies with ANSI and IEEE standards.

Applications: This switchgear is suitable for indoor/outdoor use and applications including, but not limited to, construction sites, plant maintenance, plant turnarounds, manufacturing operations, shows, exhibits, and warehouse operations.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [HigResPic1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)