Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MT-PSTH-R7-3P-GTD-30MVA-GMQ-HT-LT-X6-AMFF-CZ-2ZZ-M1

30/40/50 MVA Hermetically Sealed Substation Power Transformer- 92000Y/53120 Grounded Wye Primary, 13200Y/7620 Grounded Wye Secondary - ONAN/ONAF/ONAF, Mineral Oil - Light Grey - NEMA 4X

Product ID: 314124

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-PSTH-R7-3P-GTD-30MVA-GMQ-HT-LT-X6-AMFF-CZ-2ZZ-M1 Substation Transformer

Transformer Type: Substation Power Transformer, Hermetically Sealed Type
Transformer Configuration: Liquid Filled
Transformer Feed Type: Radial Feed
Operation: Step-Down Operation (Not Approved for Step-Up)
Phase: Three Phase
Capacity (w/o Fans) 30 MVA (30,000 KVA)
Capacity (w/ Fans, Stage 1): 40 MVA (40,000 KVA)
Capacity (w/ Fans, Stage 2): 50 MVA (50,000 KVA)
Vector Group: YNyn2+d
Primary Voltage: 92000Y/53120
Primary Voltage Switch: N/A
Primary Line Voltage Class: 115 kV Class
Primary Neutral Voltage Class: 15 kV Class
Primary Phasor: Grounded Wye
Primary Line BIL: 450 KV
Primary Neutral BIL: 450 KV
Secondary Voltage: 13200Y/7620
Secondary Line Voltage Class: 15 kV Class
Secondary Neutral Voltage Class: 15 kV Class
Secondary Phasor: Grounded Wye
Secondary Line BIL: 110 KV
Secondary Neutral BIL: 110 KV

Ratings

Meets/Exceeds DOE 2016 Efficiency Ratings
Meets/Exceeds CSA Efficiency Ratings
Complies with ANSI / IEEE C57.12.00
Complies with ANSI / IEEE C57 12.28
Complies with ANSI / IEEE C57 12.29
Complies with ANSI / IEEE C57 12.34
Complies with CSA C88-16
Complies with CSA C227.4
Complies with ANSI / IEEE C57 12.35
Complies with ANSI / IEEE C57.12.70
Complies with ANSI / IEEE C57.12.110
Complies with ANSI / IEEE C57.12.131
Complies with CSA C227.5
Complies with ANSI / IEEE C62.11
Complies with ANSI / IEEE C62.22
Complies with ANSI Z535.4
Complies with ANSI / IEEE 386
Complies with ANSI / IEEE C2
Complies with ANSI / IEEE C37.47
Complies with CSA C802.1
Complies with ASTM D3487
Complies with ASTM D6871

Tertiary Voltage: 13200V
Tertiary Voltage Class: 15 kV Class
Tertiary Phasor: Delta, Buried
Tertiary BIL: 110 kV
Tertiary MVA Rating: 11.2/17.93/18.67 MVA
Frequency: 60 Hz
Temperature Rise: 55°C
Insulation Rating: Class E Insulation
Cooling Class: ONAN/ONAF/ONAF
Forced Air (Fans): Included, Two-Stages, 115V-1Ph rating, totally Enclosed, Individually Protected Type, Fan Blades Of One-Piece Cast aluminum, Galvanized Fan Guards. Fan Motors Are Totally Enclosed And Furnished Without Centrifugal Switches.
Cooling Radiator: Included, Has Upper And Lower Drain Plugs, ANSI #70 Light Grey, Contains Individual Shut-Off Valves, Interchangeable
L.V Tap Changer: 33-Position Load Tap Changer (LTC)
L.V Tap Qty: (16) FCAN Above Taps, (16) FCBN Below Taps
L.V Tap %: 5/8%
L.V Tap Changer Switch Rating: 25 KV
L.V Tap Changer Switch Location: L.V Side, Side Mounted In a Separate mineral oil Compartment equipped with the following:
1: Online Oil Filtration System
2: Dehydrating Breather, Messko MTrab DB100
3: Sudden Pressure Device, Qualitrol 900-014- 02
4: Sudden Pressure Seal-In Relay, Qualitrol 909-200- 01
5: Pressure Relieve Device, Messko MPrec (10psi)
6: Automatic Controller, Reinhausen ETOS MD-IV
7: Remote/Local Control Switch
8: Paralleling Operation Control System, ETOS MDIV (paralleling functionality included)
H.V Tap Changer: 5-Position De-Energized Tap Changer (DETC)
H.V Tap Qty: (2) FCAN Above Taps, (2) FCBN Below Taps
H.V Tap %: 5/8%
H.V Tap Changer Switch Rating: 25 kV
H.V Tap Changer Switch Location: H.V Side
Impedance (@ 33.6 MVA): 8.73% ± 10%
Primary Connection Type: Live Front
Primary Termination Arrangement: Inline, Top Mounted
Primary Termination: NEMA 4-Hole Pad Connectors
Primary Bushing Qty: (4)
Primary Bushing Rating: 115 KV Class, 550 KV BIL, Porcelain, ANSI #70 light Grey, Draw-Lead, Oil-Filled Condenser Bushing
Primary Neutral Connection: 25 KV Class, 150 KV BIL, Porcelain, ANSI #70 light Grey, Draw-Lead, Oil-Filled Condenser Bushing
Primary Surge Arrestors: Included, (3) Metal Oxide Polymer Housed Station Class, ANSI #70 Light Grey
Primary Surge Arrestor Voltage Rating: 90 KV
Primary Surge Arrestor MCOV Rating: 70 KV
Primary Line Bushing CT: Included, (2) Per Each Phase (1200:5 Ratio, 4.0 Thermal Rating Factor, C800 Accuracy Class, 8 Ohms Burden), (1) Per Each Phase (600:5 Ratio, 4.0 Thermal Rating Factor, C800 Accuracy Class, 8 Ohms Burden) & (1) Per Each Phase (600:5 Ratio, 4.0 Thermal Rating Factor, 0.15sB1.8 Accuracy Class, 1.8 Ohms Burden)
Primary Neutral Bushing CT: Included, (2) 600:5 Ratio, 4.0 Thermal Rating Factor, C800 Accuracy Class, 8 Ohms Burden
Primary Over Current Protection (OCP): N/A
Primary Over Current Protection Holder: N/A
Primary Grounding Provisions: N/A
Secondary Connection Type: Live Front
Secondary Termination Arrangement: Inline,Top Mounted
Secondary Termination: NEMA 4-Hole Pad Connectors
Secondary Bushing Qty: (4)
Secondary Bushing Rating: 25 KV Class, 150 KV BIL, Porcelain, ANSI #70 light Grey, Bottom Conn., Oil-Filled Condenser Bushing
Secondary Neutral Connection: 25 KV Class, 150 KV BIL, Porcelain, ANSI #70 light Grey, Bottom Conn., Oil-Filled Condenser Bushing
Secondary Over Current Protection (OCP): N/A
Secondary Line Bushing CT: Included, (2) Per Each Phase (3000:5 Ratio, 4.0 Thermal Rating Factor, C800 Accuracy Class, 8 Ohms Burden) & (1) Per Each Phase (2000:5 Ratio, 4.0 Thermal Rating Factor, 0.15sB1.8 Accuracy Class, 1.8 Ohms Burden)

Complies with NEMA 260-1996
Complies with 10 CFR Part 431
Complies with CSA C2.1-06
Complies With IEEE Std 693-2018
Complies with CSA C50
Complies with CSA C88
Complies with CSA C88.1
Complies with CSA C802-3

Features

Penta-head Bolt Entry Assembly
Non-PCB Insulating Fluid
Tamper Proof Housing
Hinged Front Compartment Doors, Pad Lockable
Hot Stick Included, HV Door Mount
NEMA 4X Wiring Compartment

Efficiency (@ 33.6 MVA): 99.729%
Efficiency (@ 44.8 MVA): 99.681%
Efficiency (@ 56 MVA): 99.625%

Load Losses Based on 85°C Reference Temp.

Off-Load Loss (in watts): 38,000W
On-Load Loss (in watts): 188,000W
Total Load Loss (in watts) at 100%: 226,000W

Secondary Neutral Bushing CT: Included, (2) 1200:5 Ratio, 4.0 Thermal Rating Factor, C800 Accuracy Class, 8 Ohms Burden
Secondary Bushing PT: N/A
Secondary Surge Arrestors: Included, (3) Metal Oxide Polymer Housed Station Class, ANSI #70 Light Grey
Secondary Surge Arrestor Voltage Rating: 12 KV
Secondary Surge Arrestor MCOV Rating: 10.2 KV
Secondary Grounding Provisions: Included, (2) Grounding Pads Located On Diagonally Opposite Corners Of The Tank Base For Grounding Of The Transformer With Bolt Type Connectors For Connection To 2/0 to 500 KCMIL Stranded Copper conductor
Metering Current Transformer (CT): Included
Metering Panel: N/A
Auxiliary Control Panel : Included, Contains Power Sources 125 Vdc, 120/240 Vac-1Ph
Load Break Switch: N/A
Load Break Switch Qty: N/A
Load Break Switch Rating: N/A
Load Break Switch Location: N/A
Efficiency Standard(s): Meets ANSI/IEEE Standards
K-Factor Rating (Harmonic Mitigation): K-1 (Standard)
Insulation Fluid: Mineral Oil, Type II, Non-PCB Fluid
Fluid (Oil) Capacity*: TBD
Fluid (Oil) Weight*: 59,524.81
Silica Gel Breather: Included
Liquid Level Indicator: Included, Messko MTO Magnetic 6-Inch
Winding Temperature Indicator: Included Thermometer, Messko MTST160W(R)
Liquid Temperature Indicator: Included, Three-Stage Type, with minor alarm and major alarm contacts, (form "C" alarm contacts)
Pressure/Vacuum Indicator: Included, With Scale Range Of Plus Or Minus 10 PSI, w/ Bleeder Valve
Rapid Rise Relay: Included, Qualitrol 900-014- 02, w/ Seal-In-Relay Qualitrol 909-200-01
Pressure Relief Device: Included, Messko MPREC (10 psi)
Transformer Monitor And I/O Processor: Included, Schweitzer SEL-2414 Transformer Monitor (P/N: 241421ABA913A3A0131), An SEL-2725S Ethernet Switch installed to network the SEL-2411 I/O Controller, SEL-2414 Transformer Monitor, SEL-2411 Load Tap Changer Controller
Multi-gas online dissolved gas analysis monitor (DGA): Included
Fault Indicator: N/A
Gas Sampler Valve: N/A
Fill Valve: Included
Fill Valve Location: Top Mounted
Drain Valve: Included, 2” Globe Type With 3/8” Sampling Valve
Drain Valve Location: N/A
Winding Material: Copper
Ambient Temperature Rating: 40°C
Ambient Operating Temperature Range: -40°C to +40°C
Max. Sound Level: 78 dBA, Complies with NEMA TR1-2013
Elevation (Altitude): 3300ft (1000 meters) Above Sea Level
Core Material: Silicon Steel, Grain Oriented
Tank Material: Coated Steel
Cabinet Material: Coated Steel
Base Platform Material: Coated Steel
Hardware Material: Stainless Steel
Portability: Lifting lugs, provisions for jacking under base, w/ base construction suitable for using rollers or skidding
Housing Type: Metal Casing Liquid Filled Transformer
Enclosure Rating: NEMA 4X Weatherproof
Seismic Rating: High Seismic Level, Complies with IEEE Std. 693-2018
Paint Type: Weatherproof and UV Resistant Epoxy Coating and Undercoating
Finish Color: ANSI #70 Light Grey
Mounting: Pad Mounted
Cables: N/A
Conduit Opening: N/A
Tank Cover Access Handhole: Included
Dimensions*: 197"-W x 79"-D x 150"-H
Dry Weight (w/o Oil)*: TBD
Total Weight (Liquid Filled)*: 152,119 lbs
*Please note that numbers are approximate and subject to change

Total Losses at 55°C LL Temp.& 20°C NL Temp.

Total Load Loss (in watts) at 50%: 57,000W

Note: Losses offered are typical only, not guaranteed

Labeling:

Externally Stenciled (Painted) KVA Rating
Externally Stenciled (Painted) Voltage Rating
External Non-PCB Label
External Warning & Danger Label
External Barcode Label
Internal Busing & Accessory Labeling
Stainless Steel Riveted Nameplate

Factory Tests:

Winding Resistance Test
Pressure Integrity Test
Insulation Resistance Test
Voltage Ratio Error Test
Separate Source Voltage Withstand Test
Short-circuit Impedance Test
Load Loss (Wattage) Test
No-load Loss (Wattage) Test
Induced Voltage Withstand Test

Shipping:

Shipped on pallet on open flatbed
Palletized on Wooden Pallet w/ Skid Pockets
Pallet Skid Facing Outward Sides of Truck
Note: Crated shipping in lieu of palletizing can be done upon request for an additional fee

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

The MT-PSTH-R7-3P-GTD-30MVA-GMQ-HT-LT-X6-AMFF-CZ-2ZZ-M1 Hermetically Sealed Substation Transformer from Larson Electronics offers powerful, reliable, and efficient power distribution in outdoor locations. The low operating costs, low heat emissions, and low cost of ownership makes this transformer ideal for a wide range of applications and businesses. This transformer ensures extra space for storing oil and is equipped with breathers to facilitate air flow. The conservator transformer should be installed on supporting structures.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

Transformer Features: The industrial transformer features a primary voltage of three-phase 92000Y/53120 Grounded Wye and a secondary voltage of three-phase 13200Y/7620 Grounded Wye. This system is rated for 30 MVA (30,000 KVA) natural cooled, 40 MVA (40,000 KVA) first stage fan cooled and 50 MVA (50,000 KVA) second stage fan cooled. We offer systems with loop or radial feed, as well as dead front or live front primary connections. The transformer features a 33-position ON-load tap changer with sixteen, +/- 5/8% taps above and sixteen, +/- 5/8% taps below to allow small changes for voltage. There is a rapid rise relay present on the system.

The system features copper windings for high strength and thermal/electrical conductivity. This transformer consists of rectangular coil and five-legged wound core design with three coils and four core loops (this is for three-phase transformers only; single-phase units have one coil and two core loops).

The MT-PSTH-R7-3P-GTD-30MVA-GMQ-HT-LT-X6-AMFF-CZ-2ZZ-M1 has fans for forced air cooling. This non-sealed system features breathers for cooling when operating temperatures increase.

Temperature Rise: This unit features 55°C temperature rise for reduced heat waste, increased reliability and longer life. At 55°C temperature rise, the transformer offers 30 MVA (30,000 KVA) natural cooled, 40 MVA (40,000 KVA) first stage fan cooled and 50 MVA (50,000 KVA) second stage fan cooled. The transformer meets standard efficiency requirements. The combination of low temperature rise and high efficiency makes this unit suitable for use in outdoor areas.

Insulation Fluid: The MT-PSTH-R7-3P-GTD-30MVA-GMQ-HT-LT-X6-AMFF-CZ-2ZZ-M1 features mineral oil insulation fluid (ONAN/ONAF/ONAF). We offer transformers with biodegradable or FR-3 fluids, if needed.

Biodegradable Fluid: Biodegradable cooling fluid (vegetable oil) has a higher heat capacity compared to mineral oil, making the liquid safer to use and more reliable during operations. Vegetable oil has a higher flash point and fire point than mineral oil, hydrocarbon oil, silicone oil and synthetic ester. This cooling fluid is also non-toxic and can tolerate higher breakdown voltages than mineral oil. When operating at high temperatures, biodegradable cooling liquid sustains up to 120% load conditions, which helps preserve the transformer's lifespan and performance.

Gauges: The following gauges are included with the system: liquid level indicator, Fluid temperature indicator, Winding Temperature Indicator, pressure/vacuum indicator. Standard liquid level, temperature and pressure/vacuum gauges are analog dial types.

Fault Pressure Devices: There is a Rapid Pressure Rise Relay and Seal-In Relay on this unit.

Gas Relay: A gas relay with indicators for light gas and heavy gas is included with the transformer. The relay includes two Dry Type Form C auxiliary contacts (1NO + 1NC) for remote alarm when pressure rises above in-field set pressure located in auxiliary control cabinet.

Surge arresters: This system comes with surge arresters on both the primary and secondary sides.

Load Break Switch: The transformer is not equipped with a load break switch.

Valves: The MT-PSTH-R7-3P-GTD-30MVA-GMQ-HT-LT-X6-AMFF-CZ-2ZZ-M1 is equipped with a pressure relief valve.

Protection Fuses: This transformer does not have bayonet protection fuses on the primary side. For units without protection fuses, upstream protection is provided. We recommend provisions for protection fuses when possible, as blown fuses may require more frequent oil changes.
Mount: This hermetically sealed substation transformer is installed on supporting structures, such as the roof of the transformer main tank.
Benefits: The MT-PSTH-R7-3P-GTD-30MVA-GMQ-HT-LT-X6-AMFF-CZ-2ZZ-M1 transformer offers many benefits to consumers. This transformer provides owners with significant energy savings, as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turns into cost savings for owners in the form of lower energy bills and decreased cost of ownership.
Applications: General purposes, industrial sites, electrical rooms, underground vaults, manufacturing facilities, steel plants, offshore, commercial, military, processing plants, electric power distribution, utilities and more.
Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)


CAUTION
CAUTION



Warranty: 24 Months.

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **HigResPic1**
- **HigResPic2**
- **HigResPic3**
- **Video1**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**