Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MPD-MES-VCB-3P3W-13-15KV-600A-BE-FM-MET-CU-N3R-M1

Metal Enclosed Switchgear, 600 Amp, 15 KV AC, 3-Pole 3-Wire, 1 IN 3 OUT, Floor Mount, Bottom Entry, Copper Bus, NEMA 3R

Product ID: 314317

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MPD-MES-VCB-3P3W-13-15KV-600A-BE-FM-MET-CU-N3R-M1 Mental Enclosed Switchgear

Unit Type: Metal Enclosed Switchgear, Vacuum Circuit Breaker Switchgear
Line-In Connections: Terminal Lugs, Accepts 750MCM-1/0
Line-In Orientation: Bottom Feed
Nominal Voltage: 12470V
Voltage Rating: 15 KV AC, 3 Phase, 3 Wire
BIL Rating: 95 KV
Frequency: 60 Hz
Current: Alternate 3 Phase Current
Protection Method: N/A
Protection Type: N/A
Protection Fuses: N/A
Bus Rating: 600 A
Continuous Current Rating: 600 A
Interrupting Fault Current Rating: 25 kA
Short Circuit Current Rating: 25 kA
Bus Type: Silver-plated copper
Insulators: Cycloaliphatic epoxy

Ratings

NRTL Listed Service Equipment
NRTL Listed to UL 891 Dead Front Switch Boards
NEMA 3R Rated for Indoor/Outdoor Use
Made in the USA

Bay #1 (Source Way)

(1) 15kV, 600A, Air load break Switch

Bay #2 (Load Way)

(1) 15kV, 600A, Air load break Switch w/ Vacuum Circuit Breaker(

(1) SEL 787 Relay and (2) SEL 751 Relays, all with communication capabilities, associated communication devices, and wires to connect to the site SCADA network

(1) SEL 735 Power Meter with MODBUS communication capabilities, associated communication devices, and wires to connect to the site SCADA network

Bay #3 (Load Way)

(1) 15kV, 600A, Air load break Switch w/ Vacuum Circuit Breaker

(1) SEL 787 Relay and (2) SEL 751 Relays, all with communication capabilities, associated communication devices, and wires to connect to the site SCADA network

(1) SEL 735 Power Meter with MODBUS communication capabilities, associated communication devices, and wires to connect to the site SCADA network

Bay #4 (Load Way)

(1) 15kV, 600A, Air load break Switch w/ Vacuum Circuit Breaker

(1) SEL 787 Relay and (2) SEL 751 Relays, all with communication capabilities, associated communication devices, and wires to connect to the site SCADA network

(1) SEL 735 Power Meter with MODBUS communication capabilities, associated communication devices, and wires to connect to the site SCADA network

Control Cabinet: Mounted on the side of the enclosure, 18”-Width

Space Heaters: Included, w/ Thermostat

Metering Current & Potential Transformer (CT/PT): Included Mount and Termination CT/PT

Line-Out Connection: Terminal Lugs, Accepts 750MCM-1/0

Line-Out Orientation: Bottom Feed

Lifting Brackets: Included, Fitted on the Top of the Enclosure

Form Factor: Rectangular, Slim-profile Enclosure w/ Lockable Door, 2 incoming panels, 1 outgoing panel

Panel Configuration: 1 x Incoming panels, 3 x Outgoing panel

Mounting: Pad Mount/Floor Mount

Enclosure Material: 11 Gauge Hot Rolled Pickled and Oiled Steel

Enclosure Finish: Munsell™ 7GY 3.29/1.5 Bell Green
Enclosure Type: NEMA 3R, Ventilated
Dimensions: 60”H x 75”W x 69.75”D
Weight: 800 lbs
Shipping Dimensions: -
Shipping Weight: -

Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Made in the USA

The Larson Electronics MPD-MES-VCB-3P3W-13-15KV-600A-BE-FM-MET-CU-N3R-M1 Metal Enclosed Switchgear is designed for reliable, safe and convenient power distribution at industrial work sites. This switchgear includes one load interrupting disconnect switch and one automatic transfer switch. Designed for floor mounting installations. This bottom feed switchgear is protected by a NEMA 3R rated, steel enclosure with a ventilated design.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

The MPD-MES-VCB-3P3W-13-15KV-600A-BE-FM-MET-CU-N3R-M1 service entrance disconnect switch provides a safe and reliable way for operators in industrial settings to tap into and utilize power sources independently of the work

area. Compatible with 15 KV AC, the switchgear features a manual operating handle. This bottom feed disconnect carries a 25 kA at 15 KV AC interrupt rating.
Operation: The switchgear features front control panel and rear termination equipped with a locking door. The door provides access to a permanently attached operating handle, which is used for manually disconnecting or connecting power and bur bars (at rear). A dead front cover protects operators from the switches for safety. Operators can inspect the switches through the dead front via a vented cover. Removing the dead front allows access to the switches
Enclosure Design: The disconnect switch is protected by an 11GA sheet steel enclosure with ANSI green finish. A ventilated design promotes natural cooling and improves performance. The enclosure is NEMA 3R rated for protection against water, moisture and debris. This rating allows the fused disconnect to be used in indoor/outdoor areas.
Certification: This disconnect switch is NRTL listed to UL 891 dead front switchboards and NRTL listed for service equipment.
Mount: Operators can mount the service entrance disconnect on floors and flat surfaces.
Customization: The MPD-MES-VCB-3P3W-13-15KV-600A-BE-FM-MET-CU-N3R-M1 can be customized to meet specific operating and power requirements. Example of customizations include:
• Making the disconnect switches portable and certified to NRTL UL 1640 for portable equipment
• Adding single pole camlock connectors for quick connections
• Adding heaters for cold environments
• Aiding alarm relays for trip notification down stream
• Adding powering meters
Applications: This switchgear is suitable for indoor/outdoor use and applications including, but not limited to, solar equipment, construction sites, plant maintenance, plant turnarounds, hazardous location operations, shows, exhibits, and shipyard operations.
At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)


CAUTION
HIGH VOLTAGE


CAUTION





Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- HigResPic1
- HigResPic2
- HigResPic3
- HigResPic4
- HigResPic5
- HigResPic6
- HigResPic7
- HigResPic8
- HigResPic9
- ISO 9001 Certification
- Business Certificate
- Shipping Time Map