Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MT-PSTH-R7-3P-GXN-60MVA-DNN-HT-LT-A6-CMFF-CZ-2ZZ-M1

60-67.2/80-89.6/100-112 MVA Hermetically Sealed Substation Power Transformer, 230000Y/132790 Grounded Wye Primary, 22860V Delta Secondary, ONAN/ONAF/ONAF - 55-65°C - Light Grey - NEMA 4X

Product ID: 314733

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-PSTH-R7-3P-GXN-60MVA-DNN-HT-LT-A6-CMFF-CZ-2ZZ-M1 Substation Transformer	Ratings
Transformer Type: Substation Power Transformer, Hermetically Sealed Type	Meets/Exceeds DOE 2016 Efficiency Ratings
Transformer Configuration: Liquid Filled	Meets/Exceeds CSA Efficiency Ratings
Transformer Feed Type: Radial Feed	Complies with ANSI / IEEE C57.12.00
Operation: Step-Down Operation (Approved for Step-Up)	Complies with ANSI / IEEE C57 12.28
Phase: Three Phase	Complies with ANSI / IEEE C57 12.29
Capacity (w/o Fans, @55/65°C): 60 MVA (60,000 KVA)/67.2 MVA (67,200 KVA)	Complies with ANSI / IEEE C57 12.34
Capacity (w/ Fans, Stage 1, @55/65°C): 80 MVA (80,000 KVA)/89.6 MVA (89,600 KVA)	Complies With IEEE Std 693-2018
Capacity (w/ Fans, Stage 2, @55/65°C): 100 MVA (100,000 KVA)/112 MVA (112,000 KVA)	Complies with ASTM D3487
Vector Group: YNd11	Complies with ANSI / IEEE C57 12.35
Primary Voltage: 230000Y/132790	Complies with ANSI / IEEE C57.12.70
Primary Voltage Switch: N/A	Complies with ANSI / IEEE C57.12.110
Primary Line Voltage Class: 245 kV Class	Complies with ANSI / IEEE C57.12.131
Primary Phasor: Grounded Wye	Complies with ANSI / IEEE C62.11
Primary Line BIL: 1050 kV	Complies with ANSI / IEEE C62.22
Secondary Voltage: 22860V	Complies with ANSI / IEEE 386
Secondary Voltage Class: 25 kV Class	Complies with ANSI / IEEE C2
Secondary Phasor: Delta	Complies with ANSI / IEEE C37.47
Secondary BIL: 125 kV	Complies with ANSI Z535.4
Tertiary Winding Capacity: N/A	Complies with CSA C88
Tertiary Winding Voltage: N/A	Complies with CSA C802-3
Tertiary Winding Phasor: N/A	Complies with CSA C227.5

Tertiary Winding Voltage Class: N/A
Tertiary Winding Voltage BIL: N/A
Frequency: 60 Hz
Temperature Rise: 55-65°C
Insulation Rating: Class A Insulation
Cooling Class: ONAN/ONAF/ONAF
Forced Air (Fans): Included, Two-Stages, Totally Enclosed, Individually Protected Type, Fan Blades Of One-Piece Cast aluminum, Galvanized Fan Guards. Fan Motors Are Totally Enclosed And Furnished Without Centrifugal Switches, Fans are Krenz-Vent efficient and maintenance free. Fans are driven by totally enclosed weatherproof, ball bearing induction motors, rated 115/230 volts, single phase, 60 hertz, connected to present a balanced load (50/50) to a 208Y/120 three phase supply
Cooling Radiator: Included, Has Upper And Lower Drain Plugs, ANSI #70 Light Grey, Contains Individual Shut-Off Valves, Interchangeable
H.V Tap Changer: 5-Position De-energized Tap Changer (DETC)
H.V Tap Qty: (2) FCAN Above Taps, (2) FCBN Below Taps
H.V Tap %: 2.5%
H.V Tap Changer Switch Rating: 245 kV Class, 1050 kV Class
H.V Tap Changer Switch Location: H.V Side, Top Mounted In a Separate mineral oil Compartment
L.V Tap Changer: N/A
L.V Tap Qty: N/A
L.V Tap %: N/A
L.V Tap Changer Switch Rating: N/A
L.V Tap Changer Switch Location: N/A
Impedance (@ 60 MVA, 230/22.8 kV): 9.88%
Primary Connection Type: Live Front
Primary Termination Arrangement: Inline, Top Mounted
Primary Termination: NEMA 4-hole pad lugs for copper conductors
Primary Bushing Qty: (4)
Primary Line Bushing Rating: 245 KV Class, 1050 KV BIL, 600A, Porcelain, ANSI #70 Light Grey
Primary Neutral Connection: Included
Primary Surge Arrestors: Included, (3) Porcelain, Station Class, metal oxide surge arresters, ANSI #70 Light Grey
Primary Surge Arrestor Voltage Rating: 258 KV
Primary Surge Arrestor MCOV Rating: 207 KV rms
Primary Over Current Protection (OCP): N/A
Primary Bushing CT: Included, [(1) 600:5 Ratio, MR, C800 Accuracy Class, Thermal Rating Factor of 2.0] For Each Bushing, 240:5, CL3, 30VA LDC CT on H1 Bushing, and Hotspot CT on H2 Bushing
Primary Over Current Protection Holder: N/A
Primary Grounding Provisions: Included, (2) Grounding Pads Located On Diagonally Opposite Corners Of The Tank Base For Grounding Of The Transformer With Bolt Type Connectors For Connection To 2/0 to 500 KCMIL Stranded Copper conductor
Primary Neutral Bushing CT: Included, (1) 600:5 Ratio, MR, C800 Accuracy Class, Thermal Rating Factor of 2.0
Secondary Connection Type: Live Front
Secondary Termination Arrangement: Inline, Top Mounted
Secondary Termination: NEMA 8-Hole Pad connectors
Secondary Bushing Qty: (3)
Secondary Line Bushing Rating: 72 KV Class, 350 KV BIL, 1200A, Porcelain, ANSI #70 Light Grey
Secondary Neutral Connection: N/A
Secondary Over Current Protection (OCP): N/A
Secondary Line Bushing CT: Included, [(1) 1200:5 Ratio, MR, C800 Accuracy Class, Thermal Rating Factor of 2.0] For Each Bushing
Secondary Surge Arrestors: Included, (3) Porcelain, Station Class, metal oxide surge arresters, ANSI #70 Light Grey
Secondary Surge Arrestor Voltage Rating: 72 KV
Secondary Surge Arrestor MCOV Rating: 57 KV
Secondary Grounding Provisions: Included, (2) Grounding Pads Located On Diagonally Opposite Corners Of The Tank Base For Grounding Of The Transformer With Bolt Type Connectors For Connection To 2/0 to 500 KCMIL Stranded Copper conductor
Tertiary Bushing Rating: N/A
Tertiary Surge Arrestors: N/A
Tertiary Surge Arrestor Voltage Rating: N/A
Tertiary Surge Arrestor MCOV Rating: N/A
Tertiary Bushing CT: N/A
Metering Current Transformer (CT): Included
Metering Panel: Included
Auxiliary Control Panel: Included, Contains Power Sources 125 V DC and 120/208 V,

Complies with CSA C88-16
Complies with CSA C88.1
Complies with CSA C227.4
Complies with CSA C2.1-06
Complies with 10 CFR Part 431
Complies with NEMA 260-1996

Complies with ASTM D6871

Complies with CSA C50

Complies with CSA C802.1

Features

Penta-head Bolt Entry Assembly

Hot Stick Included, HV Door Mount

Non-PCB Insulating Fluid

Tamper Proof Housing
Hinged Front Compartment Doors, Pad Lockable
NEMA 4X Wiring Compartment

Efficiency %: TBD

Based on transformer operating at 50% of nameplate base kVA.

Load Losses Based on 75°C Reference Temp.
Off-Load Loss (in watts): TBD
On-Load Loss (in watts): TBD
Total Load Loss (in watts) at 100%: TBD

Total Losses at 55°C LL Temp.& 20°C NL Temp.
Total Load Loss (in watts) at 50%: TBD

Note: Losses offered are typical only, not guaranteed

Labeling:

3-Ph 4-Wire AC
Load Break Switch: N/A
Load Break Switch Qty: N/A
Load Break Switch Rating: N/A
Load Break Switch Location: N/A
Efficiency Standard(s): Meets ANSI/IEEE Standards
K-Factor Rating (Harmonic Mitigation): K-1 (Standard)
Pulse Drive Rating: N/A
Insulation Fluid: Mineral Oil, Type II, Non-PCB Fluid
Total Fluid (Oil) Capacity*: TBD
Total Fluid (Oil) Weight*: TBD
Silica Gel Breather: Included
Liquid Level Indicator: Included, Magnetic Type, Qualitrol LLCG 042, With (2) alarm contacts: (1) for low oil level alarm and (1) for critical low oil level alarm
Winding Temperature Indicator: Included Thermometer, Qualitrol ITM509-00390129 (Direct Winding), with fiber optic probes and RTD's
Liquid Temperature Indicator: Included, Qualitrol 104 SCADA style
Pressure/Vacuum Indicator: Included, Qualitrol 070-35C series with 351-2A PV bleeder and 050-35E PV gauge
Rapid Rise Relay: Included, A Rapid Rise (Qualitrol 900 series) sudden pressure device is accessible from the ground and connected to a Qualitrol 909-300-01 seal-in relay
Pressure Relief Device: Included, (2) cover-mounted extra-large mechanical type, (Qualitrol XPRD), mounted on diagonally opposite ends of the transformer cover, With automatic resealing operation, With 2-form "C" and 2-form "A" alarm contacts. "A" contact to I/O module. Other form "C" to terminal board 3, Includes mechanical signal for indication of device operation, Includes directional discharge outlet and applicable piping to direct discharge to a location approximately 1-foot above base of transformer, Includes screen at pipe exit to prevent animal ingress.
I/O Module: Included, Qualitrol ITM 509
Transformer Monitor: Included, Qualitrol 509DW Panel mounted Intelligent Transformer Monitor
Nitrogen Oil Preservation System: Included With A Nitrogen Tank And All Necessary Accessories, The Control System is The RNx INERTAIRE series manufactured by the ABB Power T&D Company
Pressure Reducer: Included, Three-Stage
Fault Gas Monitoring: Included, Megger Insulogix G2
Loss of DC Indicator: Included, A contact is provided to indicate the loss of main 125VDC supply to the transformer
Alarm and SCADA Controller: Included, A SEL-2411 Programmable Automation Controller, Schweitzer Engineering Laboratories part number 241101A3A3A3A5X1130 is installed as the transformer monitor
Fault Indicator: Included, Buchholz Relay
Gas Sampler Valve: N/A
Fill Valve: Included, 2" NPT upper filter valve, Globe type, With male 3" NPT vacuum connection with cap provided on the cover
Fill Valve Location: Top Mounted
Drain Valve: Included, 2" NPT combination drain and lower filter valve, Globe Type With 3/8" Sampling Valve
Drain Valve Location: within one (1) inch of the bottom of the tank
Winding Material: Copper
Maximum Ambient Temperature: 40°C
Ambient Operating Temperature Range: -10° to +40°C
Average Ambient Temperature (24 hour): 10°C
Precipitation: Driving rain, Fog, Snow, and Sleet
Airborne Contaminants: Flour-sand, Cottonwood Tree seed and fluff, and Dust (Including grain and coal)
Wind Loading: 114 mph sustained gusts Wind Load
Sound Level Rating (At ONAN/ONAF/ONAF): 72/73/74 dBA
Elevation (Altitude): 3,300 ft Above Sea Level
Core Material: Silicon Steel, Grain Oriented
Tank Material: Coated Steel
Cabinet Material: Coated Steel
Base Platform Material: Coated Steel
Hardware Material: Stainless Steel
Portability: Lifting lugs, provisions for jacking under base, w/ base construction suitable for using rollers or skidding
Housing Type: Metal Casing Liquid Filled Transformer
Enclosure Rating: NEMA 4X Weatherproof
Seismic Rating: Moderate, Complies with IEEE 693
Paint Type: Weatherproof and UV Resistant Epoxy Coating and Undercoating
Finish Color: Munsell™ 5BG 7.0/0.4 Light Grey (ANSI #70)

Externally Stenciled (Painted) KVA Rating
Externally Stenciled (Painted) Voltage Rating
External Non-PCB Label
External Warning & Danger Label
External Barcode Label
Internal Busing & Accessory Labeling
Stainless Steel Riveted Nameplate

Factory Tests:

Winding Resistance Test
No-load Loss (Wattage) Test
Insulation Resistance Test
Voltage Ratio Error Test
Induced Voltage Withstand Test
Short-circuit Impedance Test
Load Loss (Wattage) Test
Separate Source Voltage Withstand Test
Pressure Integrity Test

Shipping:

Shipped on pallet on open flatbed
Palletized on Wooden Pallet w/ Skid Pockets
Pallet Skid Facing Outward Sides of Truck
Note: Crated shipping in lieu of palletizing can be done upon request for an additional fee

Mounting: Supporting Structures
Conduit Opening: N/A
Tank Cover Access Handhole: Included
Transformer Foundation Dimensions: 240" x 120"
Transformer Overall Dimensions: 311.02"-W, 220.47"-D, 240.16"-H
Total Weight (Liquid Filled)*: 295,100 Lbs
*Please note that numbers are approximate and subject to change

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

The MT-PSTH-R7-3P-GXN-60MVA-DNN-HT-LT-A6-CMFF-CZ-2ZZ-M1 Hermetically Sealed Substation Power Transformer from Larson Electronics offers powerful, reliable, and efficient power distribution in outdoor locations. The low operating costs, low heat emissions, and low cost of ownership makes this transformer ideal for a wide range of applications and businesses. This transformer ensures extra space for storing oil and is equipped with breathers to facilitate air flow. The conservator transformer should be installed on supporting structures.
PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*
Transformer Features: The industrial transformer features a primary voltage of three-phase 230000Y/132790 Grounded Wye and a secondary voltage of three-phase 22860V Delta. This system is rated for 60 MVA (60,000 KVA) natural cooled, 80 MVA (80,000 KVA) first stage fan cooled and 100 MVA (100,000 KVA) second stage fan cooled. We offer systems with loop or radial feed, as well as dead front or live front primary connections. The transformer features a 5-position off-load tap changer with two, + 2.5 % taps above and two, - 2.5% taps below to allow small changes for voltage. There is a rapid rise relay present on the system. The system features copper windings for high strength and thermal/electrical conductivity. This transformer consists of rectangular coil and five-legged wound core design with three coils and four core loops (this is for three-phase transformers only; single-phase units have one coil and two core loops).
The MT-PSTH-R7-3P-GXN-60MVA-DNN-HT-LT-A6-CMFF-CZ-2ZZ-M1 has fans for forced air cooling.
Temperature Rise: This unit features 55/65°C temperature rise for reduced heat waste, increased reliability and longer life. At 55°C temperature rise, the transformer offers 60 MVA (60,000 KVA) natural cooled, 80 MVA (80,000 KVA) first stage fan cooled and 100 MVA (100,000 KVA) second stage fan cooled. At 65°C temperature rise, the transformer offers 67.2 MVA (67,200 KVA) natural cooled, 89.6 MVA (89,600 KVA) first stage fan cooled and 112 MVA (112,000 KVA) second stage fan cooled. The transformer meets standard efficiency requirements. The combination of low temperature rise and high efficiency makes this unit suitable for use in outdoor areas.
Insulation Fluid: The MT-PSTH-R7-3P-GXN-60MVA-DNN-HT-LT-A6-CMFF-CZ-2ZZ-M1 features mineral oil Insulation fluid (ONAN/ONAF/ONAF). We offer transformers with biodegradable or FR-3 cooling fluids, if needed.
Biodegradable Fluid: Biodegradable cooling fluid (vegetable oil) has a higher heat capacity compared to mineral oil, making the liquid safer to use and more reliable during operations. Vegetable oil has a higher flash point and fire point than mineral oil, hydrocarbon oil, silicone oil and synthetic ester. This cooling fluid is also non-toxic and can tolerate higher breakdown voltages than mineral oil. When operating at high temperatures, biodegradable cooling liquid sustains up to 120% load conditions, which helps preserve the transformer's lifespan and performance.
Gauges: The following gauges are included with the system: liquid level indicator, Fluid temperature indicator, Winding Temperature Indicator, pressure/vacuum indicator. Standard liquid level, temperature and pressure/vacuum gauges are analog dial types.
Fault Pressure Devices: There is a Rapid Pressure Rise Relay and Seal-In Relay on this unit.
Gas Relay: A gas relay with indicators for light gas and heavy gas is included with the transformer. The relay includes two Dry Type Form C auxiliary contacts (1NO + 1NC) for remote alarm when pressure rises above in-field set pressure located

in auxiliary control cabinet.
Surge arresters: This system comes with surge arresters on both the primary and secondary sides.
Load Break Switch: The transformer is not equipped with a load break switch.
Valves: The MT-PSTH-R7-3P-GXN-60MVA-DNN-HT-LT-A6-CMFF-CZ-2ZZ-M1 is equipped with a pressure relief valve.
Protection Fuses: This transformer does not have bayonet protection fuses on the primary side. For units without protection fuses, upstream protection is provided. We recommend provisions for protection fuses when possible, as blown fuses may require more frequent oil changes.
Mount: This substation power transformer installed on supporting structures, such as the roof of the transformer main tank.
Benefits: The MT-PSTH-R7-3P-GXN-60MVA-DNN-HT-LT-A6-CMFF-CZ-2ZZ-M1 transformer offers many benefits to consumers. This transformer provides owners with significant energy savings, as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turns into cost savings for owners in the form of lower energy bills and decreased cost of ownership.
Applications: General purposes, industrial sites, electrical rooms, underground vaults, manufacturing facilities, steel plants, offshore, commercial, military, processing plants, electric power distribution, utilities and more.
Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)


CAUTION
CAUTION



Warranty: 24 Months.

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **HigResPic1**
- **HigResPic2**
- **HigResPic3**
- **Video1**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**