Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

MPD-CPB-400KVAR-34500V-N4X-M1

400 KVAR Pad Mount Capacitor Bank - 34500Y/19920 Nominal Voltage, 3-Phase, NEMA 4X, Bell Green, W/ Capacitor Fuses, Load Break Switches, Voltage Transformer and Controller

Product ID: 314980

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: MPD-CPB-400KVAR-34500V-N4X-M1

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MPD-CPB-400KVAR-34500KV-N4X-M1 MV Pad Mount Capacitor Bank

Unit Type: MV Pad Mount Capacitor Bank
Phase: Three Phase
Wire: Four Wire
Nominal Voltage Rating: 34500Y/19920 Wye-N
Voltage Class: 35 kV
BIL: 150 kV
Capacitor Bank Rating: 400 KVAR
Capacitance Rating: 0.35 µF
Rated Frequency: 60 Hz
Load Break Switch: Included, (3) Joslyn Vacuum Load Break Switches Type VSV For Both Manual and Automatic Operation, w/ (1) Auxiliary Contact and (5) Pins in the Connector
Load Break Switch Rating: 600A Cont. and Load Break Current (600AF/100AT), 150 kV BIL, 25 kA Make and Latch Asymmetrical Current, 10000 OFF and 10000 ON Lifetime Switching Operations
Potential Transformer: Included, 12000-120 V, 1500 VA Rating, 100:1 Ratio, w/ (2) 1 A Primary Fuses (ABB Type CLE-PT, 6777C452 G08)
Current Limiting Fuse: Included, 8.3 kV Rating, Cooper Type NXC
Capacitor Controller: Included, w/ Front Panel Accessible Fuse and Battery, Fisher Pierce P/N: 5400N-PTS-FJ95XA with Beckwith, M-6280, w/ Radia and SCADA Capability
-Produces a 24-hr Voltage and Temperature Profile Using 5-10 minute intervals

Ratings

CSA Certified
UL Listed
Meets ANSI C57.12.28
NEMA 4X Rated for Outdoor Use
Two Years Of Warranty
Made in the USA

-Equipped with:
1. LCD Display Confirms All Settings
2. Battery - 10 Years Replaceable
3. Optical Communication Port
4. Electro-mechanical Counter
5. Temperature Sensor
6. Expanded 128K Memory
7. 120V AC, 60 Hz Operation
8. A Front Panel Toggle Switch For Manual or Automatic Operation
9. RS-232 Interface For Programming, Data Logging and Communication
10. Provision for Utilization of Auto Adaptive Controller to Minimize Capacitor Switching and Monitoring Both VAR and Power Factor Profiles

Capacitor Units: (1) 7.2 kV, 300 kVAR Two-Bushing Type Capacitor Units, Synthetic Insulation Film Dielectric Insulation Type, ANSI #70 Light Grey

Operating Temperature: -40°C to +45°C

Humidity: 90%

Seismic Zone: Low, Complies with IEEE 693

Wind Load: TBD

Snow Load: TBD

Altitude: TBD

Lifting: Top four lifting points and bottom forklift holes are both available

Door: (3) Hinged Doors w/ Pad Lockable Handle

Enclosure Material: 304 Stainless Steel

Enclosure Coating System: Primed with 3 mils of a polyamide epoxy Amercoat 385 and finished with 3 mils of an Amershield polyurethane

Enclosure Finish: Munsell™ 7GY 3.29/1.5 Bell Green

Enclosure Type: NEMA 4X Ventilated, Free Standing Tamper-proof and Weather-proof

Mount: Pad Mounted

Pad Dimensions: 72" x 94"

Dimensions: 51.2"-W x 70.87"-D x 102.36"-H

Weight: 3,747.86 lbs

Shipping Dimensions: TBD

Shipping Weight: TBD

Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-765-7664

E-mail: sales@larsonelectronics.com

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

The MPD-CPB-400KVAR-34500V-N4X-M1 is an automatically/manually switched, pad-mounted power factor correction capable device designed for medium voltage applications in installations requiring precise maintenance of target power factor in a very small footprint. Unit includes cleared fuse indicator lights and manual on/off switching easily accessible on the front cover. Built-in controller (with optional communication capabilities) controls banks of contactor-connected capacitors.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS

Capacitor Bank Features: The MPD-CPB-400KVAR-34500V-N4X-M1 is a Medium Voltage Three-Phase Pad Mount Capacitor Bank, 34500V, 400 KVAR.

Benefits: The MPD-CPB-400KVAR-34500V-N4X-M1 from Larson Electronics meets or exceeds efficiency standards for United States and Canada. This results is overall lower cost of ownership throughout the life of the capacitor bank.

Safety: The MPD-CPB-400KVAR-34500V-N4X-M1 is an automatic capacitor bank which means that it provides operators with an increased level of protection against electric shock and injury. A capacitor bank can also suppress electrical noise in sensitive devices and transfer power between two circuits which must not be connected.

Applications: Power Factor Correction.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MPD-CPB-400KVAR-34500V-N4X-M1

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MPD-CPB-400KVAR-34500V-N4X-M1

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MPD-CPB-400KVAR-34500V-N4X-M1

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: MPD-CPB-400KVAR-34500V-N4X-M1

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **HigResPic1**(https://www.larsonelectronics.com/images/product/HigResPic1/314980.JPG)
- **HigResPic2**(https://www.larsonelectronics.com/images/product/HigResPic2/314980.JPG)
- **HigResPic3**(https://www.larsonelectronics.com/images/product/HigResPic3/314980.JPG)
- **HigResPic4**(https://www.larsonelectronics.com/images/product/HigResPic4/314980.JPG)
- **HigResPic5**(https://www.larsonelectronics.com/images/product/HigResPic5/314980.JPG)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)