

MT-CNTCR-VA-R7-4P-AC-DC-30A-120A-56-BO-Z-Z-N1-M1

Contactor, 4-pole, 600 V AC, 30 A, 4 NO Main Contacts

Product ID: 315227

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-CNTCR-VA-R7-4P-AC-DC-30A-120A-56-BO-Z-Z-N1-M1 4-Pole Contactor

Unit Type: Contactor
Full Load Current: 30A
Resistive Current: 40A
Locked Rotor Current @ 240/277 VAC: 180A
Locked Rotor Current @ 480 VAC: 150A
Locked Rotor Current @ 600 VAC: 120A
Maximum Horsepower: 15 HP
Nominal Voltage: 480V
Rated Operation Voltage: 600V
Initial Dielectric Strength: 2.2 kV
Number Of Poles: (4)
Type Of Voltage: AC
Number Of NO Contacts For Main Contacts: (4)
Nominal Coil Voltage: 24V
Maximum Coil Voltage: 30V
Nominal Coil Resistance: 3.5
Maximum Pick Up Voltage: 18V
Minimum Drop Out Voltage: 6-15V
Nominal Inrush VA @ 50 Hz: 103 VA
Nominal Inrush VA @ 60 Hz: 95 VA
Nominal Sealed VA @ 50 Hz: 15 VA
Nominal Sealed VA @ 60 Hz : 11 VA
Contact Material: Silver Cadmium Oxide
ARC Cover: Included, Standard
Insulation Class: Class B (130°C)
Power Pole Termination: #10-32 screw or box lug
Recommended Tightening Torque: #10-32 screw: 22 in. lbs / Box lug: 25 in. lbs
Coil Terminals: Dual: .250" QC or #6-32 screw/.250" QC
Power Terminals: Dual .250" QC
Ambient Operation Temperature Range: -40°C to +65°C
Mounting: Bolt-on
Insulating Medium: Air
Protection Degree: NEMA 1
Overall Dimensions: 2.76"-W, 3.04"-D, 3.77"-H
Overall Weight: 1.25 lb
Shipping Dimensions: -
Shipping Weight: -

Ratings/Certifications

NRTL Listed Service Equipment
UL 508 File No. E227250 Class NLDX2, NLDX8
Semko/CE File No. EN 60947-4-1:2001
CSA File No. 221260 (1456104) Class 3211 04 / 3211 84
Made in the USA

Special Orders - Special Requirements

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com

Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

The MT-CNTCR-VA-R7-4P-AC-DC-30A-120A-56-BO-Z-Z-N1-M1 from Larson Electronics is a Four Pole Normally Open Contactor rated for 600 Volts AC and 30 AMPS AC for secure connections to circuits and motors in industrial sites where space is at a premium. This contactor is bolt-on mounted.

The MT-CNTCR-VA-R7-4P-AC-DC-30A-120A-56-BO-Z-Z-N1-M1 facilitates electrical connections in industrial facilities. This unit has the following features:

Coil Rating: 24 VAC

Auxiliary Contacts: N/A

Arc Cover: Standard

Applications: HVAC systems, industrial motors, compressors, chemical processing, welding, heating equipment, manufacturing sites and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Frequently Asked Questions (FAQ)

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [HigResPic1](#)
- [Video1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)