Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MTPC-HD-RB-PYM-218V-200HP-100HP-N3R

Rotary Phase Converter for 100HP Hard Loads, 218V 1PH to 3PH, 320 Amps Output, 200HP Idler, Pony Motor, NEMA 3R

Product ID: 316619

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MTPC-HD-RB-PYM-218V-200HP-100HP-N3R Rotary Phase Converter

Unit Type: Rotary Phase Converter
Phase Conversion: Single Phase to Three Phase
Kilowatt Rating: 150 KW
Kilo Volt-Amp Rating: 200 KVA
Idle Motor Horse Power: 200 HP
Single Phase Voltage Input: 218V
Minimum Fuse/Circuit Breaker Size: -
Maximum Fuse/Circuit Breaker Size: -
Minimum Wire (Input) to Converter: -
Minimum Electrical Service Required: 250 KVA
Idle Amps: -
Service Load Type: Hard motor loads
Three Phase Voltage Output: 218V
Maximum Single Motor Load HP: 100 HP
Recommended Combined HP: 100 HP
Optimal Output Amps: 320A
Maximum Output Amps: 450A
Maximum Resistive Amps: -
Voltage Balance: 2-5%
Minimum Wire to Device Load: -
Form Factor: Rectangular Enclosure, Cylindrical Idler w/ Four Legs
Color: Natural Gray
Weight: Panel – 98 lbs; Idler – 1,120 lbs
Dimensions: Panel – 26" W × 12" D × 26" H; Idler – 18" W × 18" D × 28" H

Ratings/Approvals

Indoor/Outdoor Use (NEMA 3R)
Built-in Pony Motor Starter
Start/Stop Push Button Switch
Accurate Voltage Balancing
Power Indicator Light
Made in the USA

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Shipping Weight: -

Shipping Dimensions: -

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)


CAUTION
HIGH VOLTAGE

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671


www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364





Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- HigResPic1
- HigResPic2
- HigResPic3
- HigResPic4
- HigResPic5
- HigResPic6
- HigResPic7
- HigResPic8
- HigResPic9
- HigResPic10
- Video1
- ISO 9001 Certification
- Business Certificate
- Shipping Time Map