Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

## Product ID: 318869

**Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).**



Image:

**Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.**

| MT-PSTC-R7-3P-DXN-90MVA-GMT-HT-LT-X6-BM-CZ-2ZZ-M1 Conservator Transformer | Ratings |
|---|---|
| **Transformer Type:** Substation Power Generator Step-Up Transformer, Conservator Type | Meets/Exceeds DOE 2016 Efficiency Ratings |
| **Transformer Configuration:** Liquid Filled | Meets/Exceeds CSA Efficiency Ratings |
| **Transformer Feed Type:** N/A | Complies with ANSI / IEEE C57.12.00 |
| **Operation:** Step-Down Operation (Not Approved for Step-Up) | Complies with ANSI / IEEE C57 12.28 |
| **Phase:** Three Phase | Complies with ANSI / IEEE C57 12.29 |
| **Capacity:** 90 MVA (90,000 KVA) | Complies with ANSI / IEEE C57 12.34 |
| **Vector Group:** Dyn11d11 | Complies with ANSI / IEEE C57 12.35 |
| **Primary Voltage:** 230000V | Complies with ANSI / IEEE C57.12.70 |
| **Primary Voltage Switch:** N/A | Complies with ANSI / IEEE C57.12.110 |
| **Primary Voltage Class:** 245 kV Class | Complies with ANSI / IEEE C57.12.131 |
| **Primary Phasor:** Delta | Complies with ANSI / IEEE C62.11 |
| **Primary BIL:** 900 KV | Complies with ANSI / IEEE C62.22 |
| **Secondary Voltage:** 12000Y/6930 | Complies with ANSI / IEEE 386 |
| **Secondary Voltage Class:** 15 kV Class | Complies with ANSI / IEEE C2 |
| **Secondary Phasor:** Grounded Wye | Complies with ANSI / IEEE C37.47 |
| **Secondary BIL:** 95 KV | Complies with ANSI Z535.4 |
| **Tertiary Voltage:** 13800V Delta | Complies with CSA C227.4 |
| **Frequency:** 60 Hz | Complies with ASTM D3487 |
| **Temperature Rise:** 65°C | Complies with ASTM D6871 |
| **Insulation Rating:** Class A Insulation | Complies with CSA C227.5 |
| **Cooling Class:** ONAN | Complies with CSA C802-3 |
| **Forced Air (Fans):** N/A | Complies with CSA C802.1 |
| **Cooling Radiator:** Included, Fabricated from steel, Has Upper And Lower Drain Plugs, ANSI #70 Grey, Contains Individual Shut-Off Valves, Interchangeable | Complies with NEMA 260-1996 |

**H.V Tap Changer:** 13-Position ON-Load Tap Changer (OLTC), MFR: Reinhausen, Type: VRS III, Capable Of Interface With SCADA For Position And Control

**H.V Tap Qty:** (4) FCAN Above Taps, (8) FCBN Below Taps

**H.V Tap %:** 1.25%

**H.V Tap Changer Switch Rating:** 245 KV

**H.V Tap Changer Switch Location:** H.V Side, Top Mounted In a Separate Mineral Oil Compartment equipped with the following:

**1.** Liquid Level Gauge W/ two Alarm Contacts And An additional Form “C” Contact For Low Level Rated At 20 Amps 125 VAC

**2.** Cover-mounted extra-large mechanical Pressure Relief Device (Provided By MR, Messko LPRD Type) with automatic resealing operation, 2-form "C" alarm contacts. “A” contact to I/O module. Other form “C” to terminal board, mechanical signal for indication of device operation

**3.** Drain Valve W/ Sampling Device

**4.** Filling Plug (located at the top of the compartment

**5.** A Lip To Prevent Oil Spills After Draining The Compartment

**6.** A drive mechanism with: drive motor (shall be easily accessible and not immersed in oil, powered by 240/120V ± 10%, single phase, 60 Hz source derived from the output of a circuit breaker), Local position indicator, Operation counter. The driving motor with its controls and interlocks are housed in an NEMA 4X weather-proof

**7.** MR OLTC Monitoring

**L.V Tap Changer:** N/A

**L.V Tap Qty:** N/A

**L.V Tap %:** N/A

**L.V Tap Changer Switch Rating:** N/A

**L.V Tap Changer Switch Location:** N/A

**Impedance (@ 90 MVA, 65ºC):** 15%

**Primary Connection Type:** Live Front

**Primary Termination Arrangement:** Inline, Standard Top Cover, Draw Lead Connect

**Primary Termination:** NEMA 4-Hole Pad connectors

**Primary Bushing Qty:** (3)

**Primary Bushing Rating:** 245 KV Class, 1175 KV BIL, 1200 A, Porcelain, ANSI #70 Grey, Includes Visible Oil Level Indicator "Sight Glass", Include test taps for power factor testing and condition monitoring, Oil-Filled Condenser Type

**Primary Neutral Bushing:** N/A

**Primary Over Current Protection (OCP):** N/A

**Primary Bushing CT:** Included, (2) Per Each Phase (1200:5 MR, C800 Accuracy Relaying Class, 2.0 Rating Factor) & (1) Per Each Phase (400:5 MR, 0.15B1.8 Accuracy Class, 2.0 Rating Factor)

**Primary Surge Arrestors:** Included, (3) Metal Oxide Polymer Housed Station Class, ANSI #70 Grey, Connected to stainless steel ground pad at the base of the transformer

**Primary Surge Arrestor Voltage Rating:** 245 kV

**Primary Surge Arrestor MCOV Rating:** 138 kV

**Primary Grounding Provisions:** Included, (2) Grounding Pads Located On Diagonally Opposite Corners Of The Tank Base For Grounding Of The Transformer With Bolt Type Connectors For Stranded Copper Conductor of 4/0 AWG cross-section

**Secondary Connection Type:** Live Front

**Secondary Termination Arrangement:** Inline, Standard Top Cover- Bottom connect

**Secondary Termination:** NEMA 4-Hole Pad connectors

**Secondary Bushing Qty:** (4)

**Secondary Bushing Rating:** 15 KV Class, 110 KV BIL, Porcelain, ANSI #70 Grey, Includes Visible Oil Level Indicator "Sight Glass", Include test taps for power factor testing and condition monitoring, Oil-Filled Condenser Type

**Secondary Neutral Bushing:** Included, 15 KV Class, 110 KV BIL, 2000 A

**Secondary Neutral Bushing Location:** Standard Top Cover- Bottom Connect

**Secondary Surge Arrestors:** Included, (3) Metal Oxide Polymer Housed Station Class, ANSI #70 Grey, Connected to stainless steel ground pad at the base of the

Complies With IEEE Std 693-2018

Complies with CSA C88.1

Complies with CSA C88-16

Complies with CSA C88

Complies with CSA C50

Complies with CSA C2.1-06

Complies with 10 CFR Part 431

**Efficiency %:** TBD

*Based on transformer operating at 50% of nameplate base kVA.*

**Load Losses Based on 75°C Reference Temp.**

**Off-Load Loss (in watts):** TBD

**On-Load Loss (in watts):** TBD

**Total Load Loss (in watts) at 100%:** TBD

**Total Losses at 55°C LL Temp.& 20°C NL Temp.**

**Total Load Loss (in watts) at 50%:** TBD

***Note:*** *Losses offered are typical only, not guaranteed*

**Features**

Hot Stick Included, HV Door Mount

NEMA 4X Wiring Compartment

Hinged Front Compartment Doors, Pad Lockable

Tamper Proof Housing

Penta-head Bolt Entry Assembly

High-Fire Point Insulating Fluid

Non-PCB Insulating Fluid

transformer
**Secondary Surge Arrestor Voltage Rating:** 15 KV
**Secondary Surge Arrestor MCOV Rating:** 12.7 kV
**Secondary Over Current Protection (OCP):** N/A
**Secondary Bushing CT:** Included, (3) Per Each Phase (4000:5 MR, C800 Accuracy Relaying Class, 2.0 Rating Factor
**Secondary Neutral Bushing CT:** Included, (1) (4000:5 MR, C800 Accuracy Relaying Class, 2.0 Rating Factor)
**Secondary Over Current Protection Holder:** N/A
**Secondary Grounding Provisions:** N/A
**Tertiary Winding CT:** Included, (1) (2000:5 MR, C800 Accuracy Relaying Class, 2.0 Rating Factor)
**Metering Current Transformer (CT):** Included
**Metering Panel:** Included
**Auxiliary Control Panel :** Included, Contains Power Sources (2) 125 Vdc, (1) 120/240 Vac-1Ph
**Load Break Switch:** N/A
**Load Break Switch Qty:** N/A
**Load Break Switch Rating:** N/A
**Load Break Switch Location:** N/A
**Efficiency Standard(s):** Meets ANSI/IEEE Standards
**K-Factor Rating (Harmonic Mitigation):** K-1 (Standard)
**Pulse Drive Rating:** N/A
**Insulation Fluid:** Mineral Oil, Type II, Non-PCB Fluid
**Fluid (Oil) Capacity*:** TBD
**Fluid (Oil) Weight*:** TBD
**Silica Gel Breather:** Included
**Liquid Level Indicator:** Included, Magnetic Type, With High and Low alarm contacts (form "C" alarm contacts). An additional form “C” contact for low level rated at 20 amps 125 VAC for sump basin water pump
**Winding Temperature Indicator:** Included Thermometer, Messko, Type: MT-ST/60 VMR/4C/4M
**Liquid Temperature Indicator:** Included, Three-Stage Type, with minor alarm and major alarm contacts, (form "C" alarm contacts)
**Pressure/Vacuum Indicator:** N/A
**Rapid Rise Relay:** Included, (63) Qualitrol 910-013-03
**Pressure Relief Device:** Included, (2) cover-mounted extra-large mechanical type, (Qualitrol XPRD), mounted on diagonally opposite ends of the transformer cover, With automatic resealing operation, With 2-form "C" and 2-form "A" alarm contacts. “A” contact to I/O module. Other form “C” to terminal board 3, Includes mechanical signal for indication of device operation, Includes directional discharge outlet and applicable piping to direct discharge to a location approximately 1-foot above base of transformer, Includes screen at pipe exit to prevent animal ingress.
**Transformer Monitor And I/O Processor:** Included, Schweitzer SEL-2414 Transformer Monitor (P/N: 241421ABA913A3A0131), An SEL-2725S Ethernet Switch installed to network the SEL-2411 I/O Controller, SEL-2414 Transformer Monitor, and SEL-2411 Load Tap Changer Controller
**Nitrogen Oil Preservation System:** N/A
**Pressure Reducer:** N/A
**Gas Relay:** Included
**Fault Indicator:** Included, Buchholz Relay
**Gas Sampler Valve:** N/A
**Fill Valve:** Included
**Fill Valve Location:** Top Mounted
**Drain Valve:** Included, 2” Globe Type With 3/8” Sampling Valve
**Drain Valve Location:** LV Side
**Winding Material:** Copper
**Ambient Temperature Rating:** 45°C
**Ambient Operating Temperature Range:** -10°C to +45°C

**Labeling:**

Externally Stenciled (Painted) KVA Rating
Externally Stenciled (Painted) Voltage Rating
External Non-PCB Label
External Warning & Danger Label
External Barcode Label
Internal Busing & Accessory Labeling
Stainless Steel Riveted Nameplate

**Factory Tests:**

Winding Resistance Test
Pressure Integrity Test Test
Insulation Resistance Test
Voltage Ratio Error Test
Load Loss (Wattage) Test
Short-circuit Impedance Test
Separate Source Voltage Withstand Test
No-load Loss (Wattage) Test
Induced Voltage Withstand Test

**Shipping:**

Shipped on pallet on open flatbed
Palletized on Wooden Pallet w/ Skid Pockets
Pallet Skid Facing Outward Sides of Truck
***Note:*** *Crated shipping in lieu of palletizing can be done*

*upon request for an additional fee*

**Wind Speed Withstand Rating (mi/h):** 55.9
**Sound Level:** Complies to NEMA TR1
**Elevation (Altitude):** 3300ft (1000 meters) Above Sea Level
**Core Material:** Silicon Steel, Grain Oriented
**Tank Material:** Coated Steel
**Cabinet Material:** Coated Steel
**Base Platform Material:** Coated Steel
**Hardware Material:** Stainless Steel
**Portability:** Lifting lugs, provisions for jacking under base, w/ base construction suitable for using rollers or skidding
**Housing Type:** Metal Casing Liquid Filled Transformer
**Enclosure Rating:** NEMA 4X Weatherproof
**Seismic Rating:** Zone 1
**Paint Type:** Weatherproof and UV Resistant Epoxy Coating and Undercoating
**Finish Color:** ANSI #70 Light Grey
**Mounting:** Supporting Structures
**Conduit Opening:** N/A
**Tank Cover Access Handhole:** Included
**Dimensions:** 396" x 315" x 425"
**Total Weight*:** 544,541.8
**Transport Weight*:** TBD
*Please note that numbers are approximate and subject to change

**Special Orders - Special Requirements**
Contact us for special requirements
**Toll Free:** 1-800-369-6671
**Intl:** 1-903-270-1187
**Fax:** 1-903-765-7664
**E-mail:** sales@larsonelectronics.com

**The MT-PSTC-R7-3P-DXN-90MVA-GMT-HT-LT-X6-BM-CZ-2ZZ-M1 Conservator Substation Transformer from Larson Electronics offers powerful, reliable, and efficient power distribution in outdoor locations. The low operating costs, low heat emissions, and low cost of ownership make this transformer ideal for a wide range of applications and businesses. This transformer ensures extra space for storing oil and is equipped with breathers to facilitate air flow. The conservator transformer should be installed on supporting structures.**

***PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS****

**Transformer Features:** The industrial transformer features a primary voltage of three-phase 230000V Delta and a secondary voltage of three-phase 12000Y/6930 Grounded Wye. This system is rated for 90 MVA (90,000 KVA). We offer systems with loop or radial feed, as well as dead front or live front primary connections. The transformer features a 13-position ON-Load tap changer with four +1.25% taps above and eight -1.25% taps below to allow small changes in voltage. There is a rapid rise relay present on the system.

The system features copper windings for high strength and thermal/electrical conductivity. This transformer consists of a rectangular coil and a five-legged wound core design with three coils and four core loops (this is for three-phase transformers only; single-phase units have one coil and two core loops).

The MT-PSTC-R7-3P-DXN-90MVA-GMT-HT-LT-X6-BM-CZ-2ZZ-M1 doesn't have fans or mounting provisions for fans. This non-sealed system features breathers for cooling when operating temperatures increase.

**Temperature Rise:** This unit features 65°C temperature rise for reduced heat waste, increased reliability and longer life. At 65°C temperature rise, the transformer offers 90 MVA (90,000 KVA). The transformer meets standard efficiency requirements. The combination of

low temperature rise and high efficiency makes this unit suitable for use in outdoor areas.

**Insulation Fluid:** The MT-PSTC-R7-3P-DXN-90MVA-GMT-HT-LT-X6-BM-CZ-2ZZ-M1 features mineral oil insulation fluid (ONAN). We offer transformers with biodegradable or FR-3 fluids, if needed.

**Biodegradable Fluid:** Biodegradable cooling fluid (vegetable oil) has a higher heat capacity compared to mineral oil, making the liquid safer to use and more reliable during operations. Vegetable oil has a higher flash point and fire point than mineral oil, hydrocarbon oil, silicone oil and synthetic ester. This cooling fluid is also non-toxic and can tolerate higher breakdown voltages than mineral oil. When operating at high temperatures, biodegradable cooling liquid sustains up to 120% load conditions, which helps preserve the transformer's lifespan and performance.

**Gauges:** The following gauges are included with the system: liquid level indicator, Fluid temperature indicator, winding temperature indicator, and pressure/vacuum indicator. Standard liquid level, temperature and pressure/vacuum gauges are analog dial types.

**Fault Pressure Devices:** There is a rapid pressure rise relay and Seal-In Relay on this unit.

**Gas Relay:** A gas relay with indicators for light gas and heavy gas is included with the transformer. The relay includes two Dry Type Form C auxiliary contacts (1NO + 1NC) for remote alarm when pressure rises above in-field set pressure located in auxiliary control cabinet.

**Surge arresters:** This system comes with surge arresters on both primary and secondary sides.

**Load Break Switch:** The transformer is not equipped with a load break switch.

**Valves:** The MT-PSTC-R7-3P-DXN-90MVA-GMT-HT-LT-X6-BM-CZ-2ZZ-M1 is equipped with a pressure relief valve.

**Protection Fuses:** This transformer does not have bayonet protection fuses on the primary side. For units without protection fuses, upstream protection is provided. We recommend provisions for protection fuses when possible, as blown fuses may require more frequent oil changes.

**Mount:** This conservator substation transformer installed on supporting structures, such as the roof of the transformer's main tank.

**Benefits:** The MT-PSTC-R7-3P-DXN-90MVA-GMT-HT-LT-X6-BM-CZ-2ZZ-M1 transformer offers many benefits to consumers. This transformer provides owners with significant energy savings, as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turns into cost savings for owners in the form of lower energy bills and decreased cost of ownership.

**Applications:** General purposes, industrial sites, electrical rooms, underground vaults, manufacturing facilities, steel plants, offshore, commercial, military, processing plants, electric power distribution, utilities and more.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

# Frequently Asked Questions (FAQ)

There are no Faqs

**Product ID: 318869**

**Warranty:** 24 Months.

**Export Control Classification Number (ECCN):** EAR99

Links (Click on the below items to view):

- **Operations Manual**( https://www.larsonelectronics.com//images/product/Manual/318869.PDF )
- **HigResPic1**( https://www.larsonelectronics.com//images/product/HigResPic1/318869.JPG )
- **Video1**( https://www.youtube.com/watch?v=4-JEyYeYcn8 )
- **Video6**( https://www.youtube.com/watch?v=olihKUo24KU )
- **Video7**( https://www.youtube.com/watch?v=Yez7eCilgDE )
- **Video8**( https://www.youtube.com/watch?v=Ac5BDPSy964 )
- **ISO 9001 Certification**( http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF )
- **Business Certificate**( https://www.larsonelectronics.com/images/pdfdocs/w9.PDF )
- **Shipping Time Map**( https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf )