

EPL-AEH-SS-8.12.6-N4X-TB36-MOD1

8" x 12" x 6" Hazloc Stainless Steel Junction Box - C1D2 ATEX - 36 Terminals - Type 4X IP66

Product ID: 320925

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: EPL-AEH-SS-8.12.6-N4X-TB36-MOD1

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPL-AEH-SS-8.12.6-N4X-TB36-MOD1 ATEX Rated Junction Box

Dimensions: 8" x 12" x 6"

Weight: -

Mechanical Resistance: Impact Energy 7 Nm

Ambient Temp: 20C to + 40C

Operating Temp: - 20C to +85C

Cover Type: Hinge - Concealed, Removable Pins

Body and Cover Material: 316 Stainless Steel

Terminals: (1) Row, (24) Terminals - Feed Through, (12) individual shield

Bus Bar: (1) 12"

Clamp Type: Screw Clamp

Hubs: (13) M20 [6 in each side, 1 in bottom] (2) M32 [Bottom]

Ratings

Class I, Division 2 Groups A,B,C,D

Class I, Zone 1&2 Groups IIA,IIB & IIC

Class II, Groups E,F,G

Class III

Ex e IIC Gb, Ex i IIC Gb

Ex tb IIIC Db IP66

Ex tb / Zone 21&22 AEx tb IIIC

T80C /T100C/T130C Db IP66

Type 3, 4 & 4X

EPDM Rubber Seal

Special Orders - Special Requirements

Contact us for special requirements

Intl: 1-903-270-1187

Toll Free: 1-800-369-6671

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The Larson Electronics EPL-AEH-SS-8.12.6-N4X-TB36-MOD1 Hazardous Location Stainless Steel Junction Box provides operators with a rugged enclosure that is designed to hold and protect equipment in flammable environments. This IP66-rated enclosure is ideal for Class I, Division 2 sites, as well as ATEX-rated environments and indoor or outdoor applications where flammable vapors, gases, or dusts exist or stand the potential to exist. Inside the enclosure, operators are provided access to 36 terminals on a single row.

****PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO EXPLOSION PROOF ENCLOSURES****

The EPL-AEH-SS-8.12.6-N4X-TB36-MOD1 hazardous location enclosure is made of 316 stainless steel and features an EPDM rubber seal. Equipped with a hinged cover that is concealed and contains removeable pins, this Type 4X junction box measures 8" x 12" x 6". The unit contains 36 terminals (24 feed through with numbers) on a single row, and 12 individual shield, a 12" bus bar and a screw clamp. Operators are provided access to mounting lugs for easy mounting on walls or surfaces. side hub configuration includes: (12) M20 for cable glands 6 in each side, (1) M20 for Stopping plug, (2) M32 for cable glands and in the bottom.

Applications: Offshore rigs, sewage and wastewater treatment plants, coal plants, gas facilities and any other sites where a hazardous location or ATEX-rated enclosure is needed.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.



Frequently Asked Questions (FAQ)

There are no Faqs



Image: EPL-AEH-SS-8.12.6-N4X-TB36-MOD1



Image: EPL-AEH-SS-8.12.6-N4X-TB36-MOD1



Image: EPL-AEH-SS-8.12.6-N4X-TB36-MOD1



Image: EPL-AEH-SS-8.12.6-N4X-TB36-MOD1



Export Control Classification Number (ECCN): EAR99



Links (Click on the below items to view):

- **HigResPic1**(<https://www.larsonelectronics.com/images/product/HigResPic1/320925.JPG>)
- **HigResPic2**(<https://www.larsonelectronics.com/images/product/HigResPic2/320925.JPG>)
- **HigResPic3**(<https://www.larsonelectronics.com/images/product/HigResPic3/320925.JPG>)
- **HigResPic4**(<https://www.larsonelectronics.com/images/product/HigResPic4/320925.JPG>)
- **HigResPic5**(<https://www.larsonelectronics.com/images/product/HigResPic5/320925.JPG>)
- **HigResPic6**(<https://www.larsonelectronics.com/images/product/HigResPic6/320925.JPG>)
- **HigResPic7**(<https://www.larsonelectronics.com/images/product/HigResPic7/320925.JPG>)
- **HigResPic8**(<https://www.larsonelectronics.com/images/product/HigResPic8/320925.JPG>)
- **HigResPic9**(<https://www.larsonelectronics.com/images/product/HigResPic9/320925.JPG>)
- **ISO 9001 Certification**(<http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF>)
- **Business Certificate**(<https://www.larsonelectronics.com/images/pdfdocs/w9.PDF>)
- **Shipping Time Map**(<https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf>)