

MPD-MCS-VCB-3P3W-22-15KV-600A-BE-FM-MET-CU-N3S-SAR-M1

Metal Clad Switchgear, 600 Amp, 15 kV AC, 3-Pole 3-Wire, 2 IN 2 OUT, Pad Mount, Bottom Entry, Copper Bus, NEMA 3S

Product ID: 322073

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: MPD-MCS-VCB-3P3W-22-15KV-600A-BE-FM-MET-CU-N3S-SAR-M1

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MPD-MCS-VCB-3P3W-22-15KV-600A-BE-FM-MET-CU-N3S-SAR-M1 Metal Clad Switchgear

Unit Type: Metal Clad Switchgear - Vacuum Disconnect Switch

Line-In Connections: Terminal Lugs, Accepts 750MCM-1/0

Line-In Orientation: Bottom Feed

Configuration: Live Front

Nominal Voltage: 12470 V AC, 3 Phase, 3 Wire

Maximum Voltage Rating: 15 KV AC

Rated Withstand Test Voltage at Power Frequency: 19 kV

Rated Withstand Test Voltage at Impulse: 95 kV

Rated Short Time Withstand current and duration: 50 kA

Short Circuit Breaking Capacity - Circuit Breaker: 50 kA

Rated Interrupting Time: 3 sec.

Closing & Latching Capability: 135 kA, Peak

Protection Method: N/A

Fuse Max. Rating: N/A

Fuse Holder Rating: N/A

Spare Fuses: N/A

Harmonic Filter Ratings: HD not to exceed 5%

Main Bus Continuous Current Rating: 600 A

Ratings

NRTL Listed Service Equipment

NRTL Listed to UL 891 Dead Front Switchboards

NEMA 3S Rated for Indoor and Outdoor Use

Made in the USA

Busbar Bracing: 25 kA
Busbar Interrupting Rating: 25 kA
Busbar Material: Copper
Busbar Plating: Tin Plated
No load mechanical endurance of Circuit Breaker: 10,000
Total clearing time at Isc (fault detection to arc extinguishing): < 100 ms
Ultra Fast Earthing Switch (UFES) : Included
Arc Fault Detection: Included, fiber optic sensor loop installed in the main bus and each cubicle/section of the switchgear as part of the UFES protection
Switchgear Mechanism: Draw-out circuit breakers
Padlocks: Included
Visibility of Grounding Contacts: Included
Auxiliary Contacts: Included
Additional Opening Coil: Included
Mechanical/Keyed Interlocks: Included
Ground Bus Material: Copper Tin Plated
Ground Lug Size: 4/0 AWG
Voltage Presence Indicator: Included
Voltage Transformer: Included, Cast epoxy type, 0.3W,X,M,Y,Z Accuracy Class
Current Transformer: Included, Torroal bushing type, C200 Accuracy Class
Protection Relays: Included
Communication Protocols: Modbus TCP/IP and IEC61850
Power Feeder Control and Automation: Included
Fault Indicators: Included
Maintenance Mode Switch (MMS): Included
Lockout Relay: Included
Metering Current & Potential Transformer (CT/PT): Included Mount and Termination CT/PT
Line-Out Connection: Terminal Lugs, Accepts 750MCM-1/0
Line-Out Orientation: Bottom Feed, with C-type bushing for dry cable connection, including provisions for control cable connection
Surge Arrestors: Included, (1) Per Each Phase, Intermediate class
Surge Arrestor Voltage Rating: 1 kV
Surge Arrestor MCOV Rating: 1 kV
Form Factor: Rectangular, Slim-profile Enclosure w/ Lockable Door, 2 incoming panels, 2 outgoing panels
Panel Configuration: 4 x Non-Fused Compartments
Housing Type: Compartmental Air-Filled Cabinet, (1) Front Left Hinged Door w/ Pad Lockable Handle and (1) Rear Right Hinged Door w/ Pad Lockable Handle, Fuse Door and Switch handle are Kirk Key Interlocked
Enclosure Material: #12GA Sheet Steel
Enclosure Finish: Munsell™ 7GY 3.29/1.5 Bell Green
Enclosure Type: NEMA 3S Ventilated
Operating Temperature Range: -11 ~ 24°C
Relative Humidity: 60%
Mounting: Pad Mounted
Dimensions: 75"-W x 69.75"-L x 45.5"-H
Weight: 1800 lbs
Shipping Dimensions: TBD
Shipping Weight: TBD

Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-765-7664

E-mail: sales@larsonelectronics.com

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Made in the USA

The Larson Electronics MPD-MCS-VCB-3P3W-22-15KV-600A-BE-FM-MET-CU-N3S-SAR-M1 Metal Clad Switchgear is designed for reliable, safe and convenient power distribution at industrial work sites. Designed for pad mounting installations. This bottom feed switchgear is protected by a NEMA 3S rated, steel enclosure with a ventilated design.

****PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS****

The MPD-MCS-VCB-3P3W-22-15KV-600A-BE-FM-MET-CU-N3S-SAR-M1 service entrance switchgear provides a safe and reliable way for operators in industrial settings to tap into and utilize power sources independently of the work area. Compatible with 15 kV AC, the switchgear features a manual operating handle. This bottom feed switchgear carries a 25 kA at 15 kV AC interrupt rating. The switchgear comes with and accepts three 2500-amp vacuum switches.

Operation: The switchgear features front control panel and rear termination equipped with a locking door. The door provides access to a permanently attached operating handle, which is used for manually disconnecting or connecting power and busbars (at rear). A dead front cover protects operators from the fuses for safety. Operators can inspect the fuses through the dead front via a vented cover. Removing the dead front allows access to the fuses.

Time Delay vs. Fast Acting Fuses Two of the most common types of fuses found in power distribution equipment are time delay and fast acting fuses.

Time Delay: Time delay fuses are tripped once overcurrent heat builds up enough to melt the fuse element over a period of time. That period of time varies between different time delay fuses depending on the application. Time delay fuses decrease the chances of false tripping. During startup, many components require a large current for a very short amount of time. In other words, a time delay fuse disconnects the circuit only when the overcurrent persists in the line.

Fast Acting: Fast acting fuses are tripped immediately upon sensing an overcurrent or short circuit in the line. They are ideal for electronics, components, or systems that cannot withstand sudden changes in current. A fast acting fuse will not withstand a temporary overload such as one that occurs during the startup process.

Enclosure Design: The switchgear is protected by an 11GA sheet steel enclosure with ANSI green finish. A ventilated design promotes natural cooling and improves performance. The enclosure is NEMA 3S rated for protection against water, moisture and debris. This rating allows the fused disconnect to be used in indoor and outdoor areas.

Certification: This disconnect switch is NRTL listed to UL 891 dead front switchboards and NRTL listed for service equipment.

Mount: Operators can mount the service entrance disconnect on floors and flat surfaces.

Customization: The MPD-MCS-VCB-3P3W-22-15KV-600A-BE-FM-MET-CU-N3S-SAR-M1 can be customized to meet specific operating and power requirements. Example of

customizations include:

- Making the fused disconnect portable and certified to NRTL UL 1640 for portable equipment
- Adding single pole camlock connectors for quick connections
- Adding heaters for cold environments
- Aiding alarm relays for trip notification downstream
- Adding power meters

Applications: This switchgear is suitable for indoor/outdoor use and applications including, but not limited to, solar equipment, construction sites, plant maintenance, plant turnarounds, hazardous location operations, shows, exhibits, and shipyard operations.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.



Frequently Asked Questions (FAQ)

There are no Fags



Image: MPD-MCS-VCB-3P3W-22-15KV-600A-BE-FM-MET-CU-N3S-SAR-M1



Image: MPD-MCS-VCB-3P3W-22-15KV-600A-BE-FM-MET-CU-N3S-SAR-M1



Image: MPD-MCS-VCB-3P3W-22-15KV-600A-BE-FM-MET-CU-N3S-SAR-M1



Image: MPD-MCS-VCB-3P3W-22-15KV-600A-BE-FM-MET-CU-N3S-SAR-M1



Export Control Classification Number (ECCN): EAR99



Links (Click on the below items to view):

- **HigResPic1**(<https://www.larsonelectronics.com/images/product/HigResPic1/322073.JPG>)
- **HigResPic2**(<https://www.larsonelectronics.com/images/product/HigResPic2/322073.JPG>)
- **HigResPic3**(<https://www.larsonelectronics.com/images/product/HigResPic3/322073.JPG>)
- **HigResPic4**(<https://www.larsonelectronics.com/images/product/HigResPic4/322073.JPG>)
- **HigResPic5**(<https://www.larsonelectronics.com/images/product/HigResPic5/322073.JPG>)
- **HigResPic6**(<https://www.larsonelectronics.com/images/product/HigResPic6/322073.JPG>)
- **HigResPic7**(<https://www.larsonelectronics.com/images/product/HigResPic7/322073.JPG>)
- **HigResPic8**(<https://www.larsonelectronics.com/images/product/HigResPic8/322073.JPG>)
- **HigResPic9**(<https://www.larsonelectronics.com/images/product/HigResPic9/322073.JPG>)
- **ISO 9001 Certification**(<http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF>)
- **Business Certificate**(<https://www.larsonelectronics.com/images/pdfdocs/w9.PDF>)
- **Shipping Time Map**(<https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf>)