Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

VFD-3P-500V-15HP-21A-DCM

15 HP Variable Frequency Device - 500V AC 3PH Input/Output - 21 Amps - 11kW

Product ID: 322308

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: VFD-3P-500V-15HP-21A-DCM

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

VFD-3P-500V-15HP-21A-DCM Variable Frequency Device

Unit Type: 3 Phase Delta, 3 Wire Variable Frequency Device
Dimensions: 6.1"-W x 9.8"-D x 16"-H
Weight: 18 lbs
Input/Output Voltage: 500V (380-500V) AC 3PH
Input Frequency Rating: 50/60 Hz
Output Current Rating: 21 Amps
Output Operating Frequency Range: 0 to 500 Hz
Kilowatts: 11 kW
HP: 15
Protection: Internal EMC filter, DC choke
Electromagnetic Compatibility Filter: EMC Filter
Dynamic Braking: Included
Number of Slots: (2) Expansion Slots
Starting Torque: 1 Hz/150%
Carrier Frequency: 1.0-16kHz, auto adjusted according to temperature and load
Frequency Accuracy: Digital setting: 0.01Hz, Analog Setting: Max frequency X 0.05%
Torque boost: Automatic torque boost; manual torque boost: 0.1%~30.0%
V/f curve: Linear, multiple point and square type (1.2 power, 1.4 power, 1.6 power, 1.8 power, square)
Inputs: 7 on-off programmable digital, 1 high-speed pulse, 2 programmable analog (AI1: 0~10V or 0/4~20mA A12: 0~10V or 0/4~20mA)

Features/Ratings

Variable Frequency Device
Keypad Display
3 Phase Delta, 3-Wire Configuration
NEMA 1 Rated
CE Certified

Outputs: 1 programmable open collector, 1 analog (open collector or high-speed pulse), 2 relay, 2 analog (0/4~20mA or 0~10V)
Analog Input/Output: 2 Input (0~10V or 0/4~20mA), 2 Output (0/4~20mA or 0~10V)
Motor Control Modes: Frequency, Speed, Open-loop speed, Open-loop torque
Motor Types: Induction, PM (IPM & SPM)
Overload: 110%
Display: Keypad
Communication: EtherNet, RS-485, BACnet MS/TP, Modbus TCP and RTU communication
Max. Overload: 110% for 1 minute
Operating Temp: –10°C to +40°C
Max Operating Humidity: 90% (non condensing)
Material: Coated board
Mounting: Wall/Panel Mounted
Color: Gray

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

The VFD-3P-500V-15HP-21A-DCM from Larson Electronics is a 3 Phase, 3-Wire Configuration Variable Frequency Drive that is suitable for improving AC motor performance in industrial operations. This fan-cooled unit features a three-phase 500V AC input/output voltage comparability. Designed for steady speed error, fast torque rise and protection from resonance vibrations, the device provides an output current of 21 amps and an operating frequency range of 0 to 500 Hz with 15 horsepower.

The VFD-3P-500V-15HP-21A-DCM offers accurate AC motor control in industrial facilities. This 11kw unit is compatible with three-phase nominal 500V (within the range of 380-500V) AC input/output voltage, provides an output current of 21 amps and an operating frequency range of 0 to 500 Hz. This device supports seven on-off programmable digital inputs, one high-speed pulse input and two programmable analog inputs, as well as one programmable open collector output, one analog output (open collector or high-speed pulse), two relay outputs and two analog outputs. The device also features a total of four operating modes: Keypad control, Terminal control, Serial communication control, and Frequency Setting Mode for digital setting, analog setting, pulse frequency setting, serial communication setting, multi-step speed setting & simple PLC, PID setting, etc.

The VFD-3P-500V-15HP-21A-DCM is designed for indoor applications and operating temperatures ranging between –10°C to +40°C. Operators may mount the variable frequency drive on compatible surfaces.

Applications: Speed control of AC motors, industrial machines, large compressors, energy savings and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Image: VFD-3P-500V-15HP-21A-DCM

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Image: VFD-3P-500V-15HP-21A-DCM

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Image: VFD-3P-500V-15HP-21A-DCM

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Image: VFD-3P-500V-15HP-21A-DCM

Export Control Classification Number (ECCN): EAR99

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Links (Click on the below items to view):

- **HigResPic1**(https://www.larsonelectronics.com/images/product/HigResPic1/322308.JPG)
- **HigResPic2**(https://www.larsonelectronics.com/images/product/HigResPic2/322308.JPG)
- **HigResPic3**(https://www.larsonelectronics.com/images/product/HigResPic3/322308.JPG)
- **HigResPic4**(https://www.larsonelectronics.com/images/product/HigResPic4/322308.JPG)
- **HigResPic5**(https://www.larsonelectronics.com/images/product/HigResPic5/322308.JPG)
- **HigResPic6**(https://www.larsonelectronics.com/images/product/HigResPic6/322308.JPG)
- **HigResPic7**(https://www.larsonelectronics.com/images/product/HigResPic7/322308.JPG)
- **HigResPic8**(https://www.larsonelectronics.com/images/product/HigResPic8/322308.JPG)
- **Video1**(https://www.youtube.com/watch?v=FM7BXInKJaY)
- **Video4**(https://www.youtube.com/watch?v=FM7BXInKJaY)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)