Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MT-PDT-CRC-R7-3P-GMQ-1MVA-YE-A6-HA-AZ-2Z-ZZ-Z-N1-M1

1 MVA Cast Resin Core Transformer, 13200Y/7620 Grounded Wye Primary, 480Y/277 Wye-N Secondary, AA/FA, Class R, Aluminum, W/ Fans

Product ID: 322368

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: MT-PDT-CRC-R7-3P-GMQ-1MVA-YE-A6-HA-AZ-2Z-ZZ-Z-N1-M1

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MT-PDT-CRC-R7-3P-GMQ-1MVA-YE-A6-HA-AZ-2Z-ZZ-Z-N1-M1 Cast Resin Core Transformer

Transformer Type: Cast Resin Core Transformer (CRC)
Transformer Configuration: Dry Type, Ventilated
Phase: Three Phase
Capacity: 1 MVA (1000 KVA)
Vector Group: YNyn0
Primary Voltage: 13200Y/7620V AC
Primary Voltage Class: 15 kV Class
Primary Phasor: Delta
Primary BIL: 110 KV
Secondary Voltage: 480Y/277
Secondary Voltage Class: 1.2 kV Class
Secondary Phasor: Wye-N
Secondary BIL: 30 KV
Frequency: 60 Hz
Temperature Rise: 150°C

Cooling Class: AA/FA

Forced Air (Fans): Included
Insulation Class: Class R (220°C)

Ratings

NRTL Listed for United States and Canada
Complies with ANSI / IEEE C57.12.00
Complies with ANSI / IEEE C57.12.01
Complies with ANSI / IEEE C57 12.35
Complies with ANSI / IEEE C57.12.59
Complies with ANSI / IEEE C57.12.70
Meets/Exceeds DOE 2016 Efficiency Ratings
Meets/Exceeds CSA Efficiency Ratings
Meets or Exceeds NEMA ST-20 Standards
Seismic Qualified for Earthquake Loads
NEMA 1 Indoor Steel Enclosure
CE Certified
RoHS Certified

Efficiency %: 99.2%
Based on transformer operating at 50% of nameplate base kVA.

Load Losses at 145°C Reference Temp.

Tap Changer: 5-Position Tap changer
Tap Qty: (2) FCAN Above, (2) FCBN Below
Tap %: 2.5%
Tap Changer Switch Location: HV Compartment
Impedance (at 120°C): 5% ± 7.5%
Primary Connection Type: Terminal Lugs
Primary Surge Arrestors: Included
Primary Surge Arrestor Voltage Rating: 15 kV
Primary Surge Arrestor MCOV Rating: 12.7 kV
Primary Overcurrent Protection (OCP): N/A
Primary Overcurrent Protection Method: N/A
Primary Grounding Provisions: N/A
Secondary Connection Type: Terminal Lugs
Secondary Surge Arrestors: N/A
Secondary Surge Arrestor Voltage Rating: N/A
Secondary Surge Arrestor MCOV Rating: N/A
Secondary Over Current Protection (OCP): N/A
Secondary Grounding Provisions: Lugs
Metering Current Transformer (CT): N/A
Transient Voltage Protection (TVP) System: N/A
Metering Panel: N/A
Auxiliary Control Panel: Included, for Fan control
Load Break Switch: N/A
Load Break Switch Qty: N/A
Load Break Switch Location: N/A
Efficiency Standard(s): DOE 2016, IEEE, ANSI
K-Factor Rating (Harmonic Mitigation): K-1 (Standard)
Temperature Sensors in Coil: Included
Temperature Gauge: Included
Seismic Bracing: Included
Weather Shield: N/A
Space Heaters: N/A
Winding Material: Aluminum
Ambient Temperature Rating: 40°C
Sound Level: 60 dBA
Elevation (Altitude) Rating: 3300ft (1000 meters) Above Sea Level
Enclosure Material: Coated Steel
Enclosure Rating: NEMA 1
System Form Factor: N/A
Paint Type: Epoxy Paint
Finish: ANSI 61 Grey
Mount: Pad Mount / Floor Mount
Dimensions: 64.96"L x 55.11"W x 70.86"H
Weight: 5,401 lbs
*Please note that numbers are approximate and subject to change

No Load Loss (in watts): +/- 1,760W
Full Load Loss (in watts): +/- 11,400W
Total Load Loss (in watts): +/- 13,160W

Note: *Losses offered are typical only, not guaranteed*

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

The MT-PDT-CRC-R7-3P-GMQ-1MVA-YE-A6-HA-AZ-2Z-ZZ-Z-N1-M1 Cast Resin Transformer from Larson Electronics converts three-phase 13200Y/7620 Grounded Wye electrical to three-phase 480Y/277 Wye-N. This power distribution unit provides operators the ability to safely tap into and distribute 1 MVA AC power from a variety of sources, such as direct grid power. The entire system is secured to a skid mount platform.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

Transformer Features: With a transformer rating of 1000 KVA, the industrial dry type transformer features a primary voltage of three-phase 13200Y/7620V AC Grounded Wye and a secondary voltage of three-phase 480Y/277V Wye-N. This transformer is equipped with a 5-position tap changer with five +/-2.5% taps (two FCAN above and two FCBN below) to allow small changes for voltage. The system has aluminum windings for high strength and electrical conductivity. This cast coil transformer features coils casted in epoxy resin under a vacuum using molds. The structure makes this type of transformer ideal for installations in extreme weather environments, offshore platforms, mining and rugged sites.

The MT-PDT-CRC-R7-3P-GMQ-1MVA-YE-A6-HA-AZ-2Z-ZZ-Z-N1-M1 has fans for forced air cooling.

Transformer Efficiency: The Class R transformer meets standard efficiency requirements. High efficiency makes this unit suitable for use in electrical rooms, air conditioned spaces in buildings, underground vaults and similar locations

Temperature Sensor: The MT-PDT-CRC-R7-3P-GMQ-1MVA-YE-A6-HA-AZ-2Z-ZZ-Z-N1-M1 is equipped with temperature sensors inside the system for controls and monitoring. A monitoring service is not included with the transformer.

Temperature Gauge: This transformer comes with a temperature gauge.

Load Break Switch: This CRC transformer does not include a load break switch. We can add a load break switch at an additional cost.

Surge Arresters: This transformer includes surge arresters on the primary side. Designed for over-voltage and transient voltage protection, the components prevent damage caused by lightning, internal switching or voltage surges. We can offer models without surge arresters that have mounting provisions for customer-provided surge arresters.

Control Transformer: This CRC transformer does not include a control transformer. We can add a control transformer for operating equipment at an additional cost.

Seismic Bracing: This system does not include seismic bracing. We can add seismic bracing for added protection in areas prone to earthquakes at an additional cost.

Weather Shield: This transformer does not include a weather shield. We can add a weather shield for protection in outdoor areas, humid environments and rodents at an additional cost.

Space Heaters: This system does not include a space heater. We can add a space heater for preventing condensation during extended shutdown at an additional cost.

Enclosure Design: This CRC transformer is protected by a steel housing. The enclosure carries a NEMA 1 rating for protection from exposure to moisture, rain, dust and debris.

Mount: The power distribution unit is mounted atop a skid plate base that allows this transformer to easily be moved from one location to another using a forklift. The skid platform is designed for serious use and is ruggedly constructed to withstand demanding conditions and heavy duty industrial applications. The industrial grade skid platform can be modified to meet the needs of job-site requirements.

Benefits: The MT-PDT-CRC-R7-3P-GMQ-1MVA-YE-A6-HA-AZ-2Z-ZZ-Z-N1-M1 transformer offers many benefits to consumers. This transformer provides owners with significant energy savings, as well as offering environmental benefits. Higher efficiency not only extends the life of the transformer, but also turns into cost savings for owners in the form of lower energy bills and decreased cost of ownership.

Applications: General purposes, industrial sites, electrical rooms, underground vaults, manufacturing facilities, steel plants, offshore, commercial, military, processing plants, electric power distribution, utilities, public locations and more.

Larson Electronics is a manufacturer and as such can build stationary and portable transformer systems to your specifications. Although we carry several models of power distribution transformer systems, we can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your needs, please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Image: MT-PDT-CRC-R7-3P-GMQ-1MVA-YE-A6-HA-AZ-2Z-ZZ-Z-N1-M1

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Image: MT-PDT-CRC-R7-3P-GMQ-1MVA-YE-A6-HA-AZ-2Z-ZZ-Z-N1-M1



Image: MT-PDT-CRC-R7-3P-GMQ-1MVA-YE-A6-HA-AZ-2Z-ZZ-Z-N1-M1

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **HigResPic1**(https://www.larsonelectronics.com/images/product/HigResPic1/322368.JPG)
- **HigResPic2**(https://www.larsonelectronics.com/images/product/HigResPic2/322368.JPG)
- **HigResPic3**(https://www.larsonelectronics.com/images/product/HigResPic3/322368.JPG)
- **HigResPic4**(https://www.larsonelectronics.com/images/product/HigResPic4/322368.JPG)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)