Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

ATEX-EPF-HPSM-24-1HP-3P-415V

24" Explosion Proof Fan - 6860 CFM - 1.5 HP - 1800 RPM - 415V - ATEX/IECEx Rated

Product ID: 322386

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).




Image: ATEX-EPF-HPSM-24-1HP-3P-415V

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

ATEX-EPF-HPSM-24-1HP-3P-415V Explosion Proof High Volume Ventilation Fan

Type: High Pressure High Volume Ventilation Fan
Propeller Dimensions: 24" Diameter
Propeller Material: Spark-Resistant Cast Aluminum
Weight: 79 lb
Voltage: 415 V AC 3 Phase
Motor: 1.5HP Fully Enclosed Explosion Proof
Rotations Per Minutes (RPM): 1800
Peak CFM (@ 0" SP): 6860
Max Sound Levels @ 5`: 35.4 (sones), 79.67 (db)
Max Decibels @ 5': 80 dBA
Wiring: Hard-Wired via Junction Box
Mounting: Permanent Mount

Ratings/Features:

ATEX/IEC Rated Flameproof Motor
Zone 1 and 2, Groups IIA and IIB
Ex d - IE2
T4 Temperature Rating
Spark-Resistant Propeller
Up To 6860 CFM Air Movement
Rated for ATEX/IECEx Hazardous Environments
Made in the USA

Special Orders - Special Requirements

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail:sales@larsonelectronics.com

Made in the USA

The ATEX-EPF-HPSM-24-1HP-3P-415V from Larson Electronics is a high pressure, high

volume explosion proof ventilation fan that operates on 415 V AC voltage. This high volume explosion proof ventilation fan features a 24" diameter spark resistant cast aluminum blade that moves air at a rate of up to 6860 cubic feet per minute (CFM) for superior ventilation and air movement. The ATEX-EPF-HPSM-24-1HP-3P-415V is powered by a fully enclosed and ATEX/IECEx rated explosion proof 1.5 horsepower motor.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO THIS PRODUCT

The ATEX-EPF-HPSM-24-1HP-3P-415V explosion proof fan is rated for ATEX/IECEx Zones 1 and 2, Groups IIA and IIB hazardous environments. The 24" diameter propeller on this explosion proof high pressure ventilation fan is constructed from cast aluminum to resist sparking further increasing the safety of the hazardous environment in which the fan is being utilized. This three phase explosion proof ventilation fan has a 1.5 horsepower fully enclosed motor that can spin the propeller at a rate of 1800 RPM.

Voltage: The ATEX-EPF-HPSM-24-1HP-3P-415V explosion proof ventilation fan operates on 415 V AC.

Wiring: The ATEX-EPF-HPSM-24-1HP-3P-415V is a hard-wired ventilation fan that should be installed according to national, state and local eletrical and mechanical codes.

Applications: Class I Group D and Class II Groups F & G hazardous areas that require ventilation including but not limited to the following: clean rooms, marijuana extraction rooms, laboratory hoods, oil refineries, grain mills, chemical plants, welding shops, chemical storage areas and battery changing areas.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Made in USA Quality

1. Fully enclosed explosion proof 1HP motor.
2. Spark-resistant cast aluminum 24" diameter propeller.
3. Class I Group D and Class II Groups F & G rated.
4. 38 V operation.
5. Moves up to 6860 cubic feet of air per minute.
6. Fully assembled and ready to install

CFM Static Pressure (SP) Ratings

0" SP - 6860 CFM
2. 1/8" SP - 6560 CFM
3. 1/4" SP - 6240 CFM
4. 3/8" SP - 5900 CFM
5. 1/2" SP - 5426 CFM

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

There are no Faqs




Image: ATEX-EPF-HPSM-24-1HP-3P-415V

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Image: ATEX-EPF-HPSM-24-1HP-3P-415V

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Image: ATEX-EPF-HPSM-24-1HP-3P-415V

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Image: ATEX-EPF-HPSM-24-1HP-3P-415V

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **HigResPic1**(https://www.larsonelectronics.com/images/product/HigResPic1/322386.JPG)
- **HigResPic2**(https://www.larsonelectronics.com/images/product/HigResPic2/322386.JPG)
- **HigResPic3**(https://www.larsonelectronics.com/images/product/HigResPic3/322386.JPG)
- **HigResPic4**(https://www.larsonelectronics.com/images/product/HigResPic4/322386.JPG)
- **HigResPic5**(https://www.larsonelectronics.com/images/product/HigResPic5/322386.JPG)
- **HigResPic6**(https://www.larsonelectronics.com/images/product/HigResPic6/322386.JPG)
- **HigResPic7**(https://www.larsonelectronics.com/images/product/HigResPic7/322386.JPG)
- **HigResPic8**(https://www.larsonelectronics.com/images/product/HigResPic8/322386.JPG)
- **HigResPic9**(https://www.larsonelectronics.com/images/product/HigResPic9/322386.JPG)
- **HigResPic10**(https://www.larsonelectronics.com/images/product/HigResPic10/322386.JPG)
- **Video1**(https://www.youtube.com/watch?v=CW5nxSIwliQ)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)